



GAGE DATA

Location	Reading	Discharge	C.R.P.	Date
Nebr. City	9.0	36,000	+0.9	25 Sept '68

Note:
All soundings are depths in feet below C.R.P.
(Design flow of 30,000 c.f.s. at Sioux City.)

NOTES:
 ▲ WESTON IS THE ORIGIN OF THE GRID COORDINATE SYSTEM.
 ALL AZIMUTHS ON THIS SHEET REFER TO TRUE SOUTH AT ▲ AS SHOWN.
 GRID DIVERGENCE AS SHOWN.
 ELEVATIONS REFER TO MEAN SEA LEVEL AS ZERO.
 O 1980 ADJUSTED INLEASE.
 1:600 MILEAGE SHOWN IN TITLE. THIS DRAWING HAS BEEN REDUCED TO ONE-HALF THE ORIGINAL SCALE.
 ◀ BEND CHANGE.

Revised to show latest field data

DATE	DESIGNED	DRAWN	APPROVED

U. S. ARMY ENGINEER DISTRICT, OMAHA
CORPS OF ENGINEERS
OMAHA, NEBRASKA

COMPILED BY: J.M.K.	MISSOURI RIVER
DRAWN BY: J.M.K.	HYDROGRAPHIC SURVEY
TRACED BY: J.M.K.	STRUCTURE 613.30 TO 610.00
CHECKED BY: G.C.S.	LOWER COPELAND BEND
SUBMITTED BY: J.M.K.	AND
ONE CHANNEL STAB SEC	UPPER COPELAND BEND
APPROVED: <i>Charles L. Blinn</i>	DATE: 25 SEPT 1968
CHIEF, CIVIL ENGR BRANCH	
APPROVED: <i>W.A.M.E.</i>	SCALE: 1 INCH = 480 FEET
COL. C. E. DISTRICT ENGINEER	DRAWING NUMBER: MCC-18E68-23