



Location	Reading	Discharge	C.R.P.	Date
Nebr. City	9.0	36,500	+0.9	6 Sep '68
Nebr. City	8.5	34,500	+0.4	9 Sep '68

Note:
All soundings are depths in feet below C.R.P.
(Design flow of 30,000 c.f.s. at Sioux City.)

DATE	DESCRIPTION	MADE	APPR'D
	Revised to show latest field data		

U. S. ARMY ENGINEER DISTRICT, OMAHA
CORPS OF ENGINEERS
OMAHA, NEBRASKA

MISSOURI RIVER
**HYDROGRAPHIC SURVEY
STRUCTURE 555.20 TO 551.35
HEMMIES AND
UPPER COTTIER BENDS**

COMPILED BY: M. E. B.
DRAWN BY: A. G. D.
TRACED BY: A. G. D.
CHECKED BY: G. C. S.

SUBMITTED BY: *H. E. Christian*
CHIEF CHANNEL STAB. SEC.

APPROVED: *John F. Hopp*
CHIEF ENGINEERING DIVISION

DATE: 6 SEP 1968

SCALE AS SHOWN
DRAWING NUMBER
MCC-18E68-5

COL. C. E. DISTRICT ENGINEER

NOTES:
 ▲ WESTON IS THE ORIGIN OF THE GRID COORDINATE SYSTEM
 ALL AZIMUTHS ON THIS SHEET REFER TO TRUE SOUTH AT Δ 228
 GRID DIVERGENCE = +0°23'12.9"
 ○ 1960 ADJUSTED MILEAGE
 1890 MILEAGE SHOWN IN TITLE
 ⚠ BEND CHANGE

SCALE 1 INCH = 400 FEET

THIS DRAWING HAS BEEN REDUCED TO ONE-HALF THE ORIGINAL SCALE.