


**SURVEY OF
MISSOURI-NEBRASKA BOUNDARY
ATCHISON COUNTY, MISSOURI
TOWNSHIP 66 NORTH, RANGE 42 WEST
AND
NEMAHA COUNTY, NEBRASKA
TOWNSHIP 6 AND 7 NORTH,
RANGE 15 AND 16 EAST**



GRID NORTH
1" = 1000'

- DENOTES 2 3/4" X 3/8" MISSOURI DNR MONUMENT SET
- DENOTES FOUND 8" X 8" CONCRETE MONUMENT (1904)
- DENOTES COMPUTED CORNER
- M = MEASURED GROUND (U.S. STANDARD FOOT) DISTANCE
- R = DENOTES RECORD DISTANCE
- Δ DENOTES MISSOURI GEOGRAPHIC REFERENCE SYSTEM
- PROJECT GRID FACTOR 1.0000251
- CONVERGENCE ANGLE AT G.R.S. EAST BASE -07°45'11.53"

RANGE 43 WEST
RANGE 42 WEST

RANGE 15 EAST
RANGE 16 EAST

McKISSICK'S ISLAND

MISSOURI
RIVER

Surveyor's Certificate

This survey is a retracement of a survey ordered by the U.S. Supreme Court, Decision No. 5 Original, submitted February 24, 1904 and decided December 19, 1904. The survey was completed April 6 to April 19, 1905, under the direction of Honorable A. Hazlett and Honorable J.W. Halliburton, Commissioners, by Daniel W. Pike, Engineer, on behalf of the State of Missouri, and J.C. Stevens, Engineer, on behalf of the State of Nebraska.

This is to Certify that this survey was executed in accordance with the requirements for the Standards of Property Boundary Surveys adopted by the Missouri Board of Architects, Professional Engineers, and Land Surveyors. We have this day made a survey of the hereon described property and the results of said survey are as shown on this plat.

WITNESS hand and seal this Twenty-Seventh (27th) day of April, 1999.


John E. Gill, L.S.
Missouri License 1724
NUMBER LS-1724
MISSOURI DEPARTMENT OF NATURAL RESOURCES
DIVISION OF GEOLOGY AND LAND SURVEY

General Notes

1. Bearings are in reference to Missouri Coordinate System 1983.
2. Missouri State Plane Coordinates based upon "GRS Station East Base" and "Missouri GRS Station B 263".
3. The class of property surveyed is Rural Property, as defined by the Missouri Minimum Standards for Property Boundary Surveys.
4. Concrete monuments were originally placed 4 feet in the ground and were composed of concrete, 8" X 8" in cross section by 5 feet in length reinforced by a projecting 2 1/4" X 2 1/4" X 1/4" angle. The original concrete monuments were marked with the letter "M" on one side and the letter "N" on the opposite side.

NO.	REVISIONS	BY	DATE	DES	DATE	SCALE
	ADDITIONAL INFORMATION SHOWN BETWEEN PTS. 24-28		5/11/99	DRN	4/22/99	1" = 1000'
	ADDED TOWNSHIP & RANGE INFORMATION		5/13/99	CHK	FILE:	
				APPD	STATE_LINES_FINAL (3)	

**MISSOURI DEPARTMENT OF NATURAL RESOURCES
DIVISION OF GEOLOGY AND LAND SURVEY**



CIVIL ENGINEERS - SURVEYORS
501 North Market, Maryville, MO 64468
4730 Frederick, St. Joseph, MO 64506
115 South 16th, Clarinda, IA 51632

SHEET
1 OF 2

C:\SCL\WORK\STATE_LINES_FINAL.dwg Thu May 13 10:06:25 1999 STATION #3