General Land Office • Original Field Notes

Book Number

29

The images in this file are photographs of the notes of the original surveys of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The original surveys in Nebraska began in the mid 1850's and were completed in the mid 1880's. The Nebraska office of the Surveyor General was closed June 30, 1886.

1

Vol. 1 R. 1

T.1-4 N.
R. 1 E.

3.

a

Field Notes of the Subdivision lines in Township No 1 North of Range No 1 East of the 6th Principal Meridian in the Territory of Nebraska. By Thomas. H. Doyle Sp. Sur under his contract No. 204, bearing date the 27 day of June 1857

~~Commenced 29th day of June 1857~~
~~Completed July 4th 1857~~

Subdivision Commenced June 29th 1857
Subdivision Completed July 4th 1857.

Township No 1 N Range No 1 East of the 6th P. M.

The names and duties of Assistants

Nelson. McCollum	Chainman
Nikolas Bukelas	Chainman
A. C. Hickey	Axeman
David McCollum	Flagman
Monroe. M. Caldwell	Compassman

Township 1 N. Range 1 East

6	36	5	27	4	21	3	16	2	9	1
36		35		26		21		15		9
7	35	8	26	9	20	10	15	11	8	12
34		33		26		20		14		7
18	33	17	25	16	19	15	14	14	7	13
32		32		24		19		13		6
19	31	20	24	21	18	22	12	23	6	24
30		30		24		18		11		5
30	29	29	23	28	17	27	11	26	4	25
29		28		22		17		10		4
31	28	32	22	33	16	34	10	35	3	36

United States of America

State of Missouri } We George M Tilford John Plummer S Campbell F Kuhn Robert Mack & Z Kahler do Sollomnly Swear that we will execute the duties of Chain carriers: that we will level the cahain upon uneaven ground and plumb the tally pins whether by Sticking or droping the same that we will report the true distance to all notable objects and the true length of all lines that we assist in measuring to the best of our Skill and ability

G. M. Tilford
John T Plummer
Robert Mack
Frederic Kuhn
Zachariah Kahler
Sarah Campbell

Subscribed and Sworne to before me this 27 day of June A.D. 1857 Brood Wayne of The City of Weston Missouri

J Nelson McCollum do Solemenly Swear that J will faithfully execute the duties of Chain Carrier. that J will level the Chain upon uneven Ground. and plumb the tally pins. whether by Sticking or dropping the Same. That J will report the true distance to all notable objects and the true lenght of lines that J assist in mesuring to the best of my Skill and ability

Nelson his mark McCollum

Sworn to and Subscribed before me this 28th day June 1857

James S Magill
Justice of the Peace

I Nicholas Beechler do solemnly swear that I will faithfuly execute the duties of Chain Carrier, that I will level the Chain upon uneven ground and plum the tally pins, neither by sticking or dropping the same. that I will report the true distance to all notable objects and the true length of all lines that I assist in measuring. to the best of my skill and ability

Nicholas Beechler

Sworn to and subscribed before me this 28th day June A.D. 1857

James S Magill
Justice of the Peace

We Alexander C. Pickey and David McCollum do solemnly swear that we will well and truly perform the duties of Axeman and Flagman, according to instructions given me and to the best of our skill and ability

A C Pickey
David McCollum

Sworn to and subscribed before me this 28th day June A.D. 1857 J S Magill Justice of the Peace

I Monroe M. Caldwell do solemnly swear that I will execute the duties of Compassman according to instructions given me the best of my skill and ability

Monroe M. Caldwell

Sworn to and subscribed before me this 28th day June A.D. 1857

James S Magill
Justice of the Peace

Township No 1 N Range No 1 East of the 6th P. M.

Chains

To determine the proper adjustment of my compass for Subdividing this Township. I commence at the Corner to Township 1 North Ranges 1 and 2 East. and run North on a Blank line along the East Boundary of Section 36

Variation 12.00 E

40.00 A point 25 lks East of Quarter Sec. Corner

80.10 A point 54 lks East of Corner to Sections 25 and 36

To retrace this line or run parallel thereto my compass must be adjusted to a Variation of 12.25 East

Subdivision commenced June 29th 1857

From the corner to sections ~~1 2~~ 35, 36 on the Base line. I run North between Sections 35 and 36

Variation 12.23 E

40.00 set a Lime Stone 20 inches long 12 inches wide and 3 inches thick for Quarter Sec Corner

Township No 1 N Range No 1 East of 6th P.M.

Chains	
80.00	Set a Lime Stone 24 inches long 17 inches wide and 2½ inches Thick for corner to Sections 25. 26. 35. 36
	Land Rolling prairie Soil 3rd rate
	East on a Random line between sections Sec 25 and 36
	Variation 12. 23 East
30.00	Ravine runs N W.
40.00	Set Sod for temporary Quarter Sec corner
72.97	Intersected East Boundary of Township 3 Mls North of corner to Sec 25 and 36 From which corner from West on a true line between Sec 25 and 36
	Variation 12. 22 East
38.98	Set a Lime Stone 19 inches long 11 inches wide and 3 inches thick for Quarter Sec Corner
77.97	The corner to Sec 25. 26. 35. 36
	Land Rolling prairie Soil 3rd rate
	North between Sec 25 and 26
	Variation 12. 23 E
20.00	Ravine runs N E

Township No 1 N Range No 1 East of the 6th P.M.

Chains	
40.00	Set a Lime Stone 17 inches long 13 inches wide and 3 inches Thick for Quarter Sec Corner
64.00	Ravine runs N W.
80.00	Set a Lime Stone 23 inches long 17 inches wide and 3 inches thick for Corner to Sections 23. 24. 25. 26
	Land Rolling Soil 3rd rate
	East on Random line between Section 24 & 25
	Variation 12. 23 E
40.00	Set Stone for temporary Quarter Sec Corner
60.00	Ravine runs N E.
79.88	Intersected ~~intersected~~ East Boundary of Township 2½ Mls south of corner to Sec 24 and 25. From which corner from West on a true line between Sec 24 & 25
	Variation 12. 33 East.
39.94	Set a Lime Stone 18 inches long 14 inches wide and 2½ inches thick for Quarter Sec Corner
79.88	The corner to Sections 23. 24. 25. 26
	Land Rolling Soil 3rd rate

Township No 1 N. Range No 1 East of the 6th P.M.

Chains

North between Sec 23 and 24

Variation 12.30 E

40.00 Set a Lime Stone 18 inches long 15 inches wide and 2½ inches thick for Quarter Sec Corner

46.00 Marine runs West,

80.00 Set a Lime Stone 23. inche long 12 inche wide and 3 inches thick for Corner to Sec 13.14.23.24

Land Rolling Soil 3rd rate

East on Random line between Sec 13 & 24

Variation 12.30 East,

40.00 Set Stone for temporary Quarter Sec Corner

79.94 Intersects East Boundary of Township 8 lks South of corner to Sec 13 and 24

From which Corner I run.

West on true line between Sec 13 & 24

Variation 12.33 East

39.97 Set a Lime Stone 23 inches long 15 inches wide and 2½ inches thick for Quarter Sec Corner

79.94 The corner to Sec Twns 13.14.23.24

Land Rolling prairie soil 3rd rate

Township No 1 N of Range No 1 E East of the 6th P.M.

Chains

North between Sec 13 and 14

Variation 12.30 East

20.00 Leave prairie and Enter timber Bearing N E and S W

32.00 Leave Timber and Enter prairie Bearing N E and S W.

40.00 Set a Lime Stone 18 inches long 12 inches wide and 4 inche thick for Quarter Section Corner

60.00 Stream 20 lks wide runs N E

80.00 Set a Sand Stone 24 inches long 11 inches wide and 4 inches thick for corner to Sec 11.12.13.14

Land Rolling Soil 3rd rate

Timber Oak and Elm

East on a Random line between Section 12 & 13

Variation 12.30 E

14.00 Stream 20 lks wide runs N E.

And Enters Bush & Vines Bear N E & S W

21.00 Same Stream 20 lks wide runs S E.

30.00 Same Stream 20 lks wide runs N E

33.00 Leave thicket and Enter prairie Bear N E & S W,

40.00 Set Stone for temporary Quarter Sec Corner

63.00 Leave prairie and Enter timber Bearing N and S,

64.00 Stream 10 lks wide runs North

Township No 1 N. of Range No 1 East of the 6th P.M.

Chains	
10.00	Centes prairie Bearing N and South.
80.12	Intersected East Boundary of Township 20 lks South of corner to Sec 12 and 13 From which corner I run, West on a true line between Sec 12 and 13 Variation 12.38 E
40.04	set a Sand stone 12 inches long 12 inches wide and 3 inches thick for a Quarter Sec Corner
80.12	The corner to sections 11, 12, 13, 14 Land Rolling soil 2nd rate Timber Oak and Elm, Under Growth Gooseberry, Plum bushes and vines

North between sections 11 and 12
Variation 12.30 E

26.00	Stream 10 lks wide runs S E.
40.00	set a Sand stone 16 inches long 8 inches wide and 7 inches thick for Quarter Sec Corner
80.00	set a Sand stone 17 inches long 8 inches wide and 7 inches thick for corner to Sec 1, 2, 11, 12 Land Rolling soil 3rd rate

Township No 1 N Range No 1 East of the 6th P.M.

Chains
East on a Random line between Sections 1 and 12
Variation 12.30 E

40.00	set Stone for a temporary Quarter Sec to come
80.26	Intersected East Boundary of Township 30 lks South of corner to Sections 1 and 12 From which corner I run West on a true line between Sec 1 and 12 Var 12.42 E
40.13	set a Sand Stone 17 inches long 9 inches wide and 4 inches thick for Quarter Sec Corner
80.26	The corner to sections 1, 2, 11, 12 Land Rolling soil 3rd rate

North on a Random line between Sections 1 and 2
Variation 12.30 East

40.00	set a Stone for temporary Quarter Sec Corner
80.60	Intersected North boundary of Township 28 lks West of corner to Sections 1 and 2 From which corner I run South on a true line between Sec 1 and 2 Variation 12.18 East

Township No 1 N Range No 1 East of the 6th P.M.

Chains	
40.00	Set a Sand Stone 13 inches long 12 inches wide and 6 inche thick for Quarter Sec Corner
80.00	The corner to sections 1. 2. 11. 12
	Land Surface Rolling Soil 3rd rate
	June 29th 1857
	North between Sections 34 and 35
	Variation 12.30 East.
40.00	Set a Lime Stone 21 inches long 12 inches wide and 8 inches thick for Quarter Sec corner
80.00	Set Lime Stone 24 inches longe 18 inches wide and 2½ inches thick for ~~Quarter~~ Sec Corner
	corner to Sec 26. 27. 34. 35
	Land Rolling Soil 3rd rate
	East on a Random line between Sec 26 and 35
	Variation 12 30 East
20.00	Raving runs N E.
40.00	set stone for temporary Quarter Sec Corner
80.14	Intersected N and S line 3 lks South of corner to 23. 26. 35. 36 From which corner I run
	West on true line between Sections 26 and 35
~~40.07~~	~~Set a Lime Stone~~ Variation 12.31 E

Township No 1 N of Range No 1 East of 6th P.M.

Chains	
40.07	Set a Lime Stone 19 inches long 14 inches wide and 3 inches thick for Quarter Section Corner
80.14	The corner to Sec 26. 27. 34. 35
	Land Rolling prairie Soil 2nd rate
	North between Sec 26 and 27
	Variation 12.30 E
20.00	Raving runs N W.
40.00	Set a Lime Stone 24 inches long 23 inches wide and 2½ inches thick for Quarter Sec Corner
80.00	Set Lime Stone 26 inches long 20 inches wide and 2½ inches thick for Corner to Sec 22. 23. 26. 27
	Land Rolling prairie Soil 2nd rate
	East on a Random line between Sec 23 & 26
	Variation 12.30 East
40.00	Set Stone for temporary Quarter Sec Corner
73.00	Raving runs North.
80.08	Intersected N and S line 2 chns West of Corner to Sec 23. 24. 25. 26
	From which Corner I run
	West on a true line between Sec 23 and 24

Township No 1 N Range No 1 East of the 6th P.M.

Chains	
	Variation 12.28 E
40.04	Set a Lime Stone 20 inches long 12 inches wide and 3 inches thick for 2 quarter Sec corner
80.08	The corner to Sec 22. 23. 26. 27
	Land Rolling prairie soil 3rd rate
	North between Section 22 and 23
	Variation 12.30 East
40.00	Set a Lime Stone 20 inches long 10 inches wide and 3 inches thick for 2 quarter Sec corner
46.00	Leave prairie and Enter Timber Bar N E and S W
48.00	Stream 10 lks wide runs N E.
50.00	Leave Timber and enter prairie Bar N E & S W
61.00	Same Stream 10 lks wide runs N W. and Enter Timber Bearing N W & S E
66.00	Same Stream 10 lks wide runs N E
68.00	Same Stream 12 lks wide runs N W
71.00	Same Stream 12 lks wide runs N E.
73.00	Leave timber and Enter prairie Bar N E & S W
80.00	Set a Lime Stone 24 inches long 17 inches wide and 3 inches thick for corner to sections 14. 15. 22. 23.

Township No 1 N Range No 1 East 6th P.M.

Chains	
	Land Rolling soil 2nd rate
	Timber Oak, Elm, Walnut, and Hickory.
	East on a Random line between Sections 14 and 23
	Variation 12.30 E
14.00	Leave prairie and Enter Timber Bar N E and S W
14.50	Stream 10 lks wide runs N E
17.00	Leave Timber and enter prairie Bar N E & S W
40.00	Set Stone for temporary 2 quarter Sec corner
45.00	Ravine runs N W
70.00	Ravine runs North
80.04	Intersected Varnt Line 4 lks North of corner to Sec 13. 14. 23. 24 From which corner of run West on true line between Sec 14 and 23
	Variation 12.32 East
40.02	Set a Lime Stone 22 inches long 12 inches wide and 4 inches thick for Quarter Sec. Corner
80.04	The corner to Sec 14. 15. 22. 23
	Land Rolling soil 3rd rate
	Timber Oak and Elm

Township No 1 N Range No 1 East 6th P.M. No.

Chains	
	North between Sections 14 & 15 —
	Variation 12.30 E
41.00	Set a Sand Stone 19 inches long 11 inches wide and 7 inches thick for Quarter Sec Corner
41.00	Stream 20 lks wide runs N E.
75.00	Ravine runs S E.
80.00	Set a Sand Stone 22 inches long 9 inches wide and 7 inches thick for corner to Sec 10.11.14.15 —
	Land Surface Broken Soil 3rd rate
	East on Random line between Sec 11 and 14
	Variation 12.30 East
41.00	Set Sod for temp Quarter Sec corner
79.91	Intersected N and S line 4 lks South of corner to Sec 11.12.13.14
	From which corner I run
	West on a true line between Sec 11 and 14
	Variation 12.32 E
39.95	Set a Sand Stone 14 inches long 9 inches wide and 6 inches thick for Quarter Sec Corner
79.91	The corner to Sections 10.11.14.15 —
	Land Rolling prairie Soil 2nd rate

Township No 1 N Range No 1 East 6th P.M. No.

Chains	
	North between sections 10 and 11
	Variation 12.30 East
37.00	Stream 10 lks wide runs E
40.00	Set a Limestone 22 inches long 8 inches wide and 4 inches thick for Quarter Sec Corner
80.00	Set a Limestone 21 inches long 9 inches wide and 5 inches thick for corner to Sec 2.3.10.11
	Land Rolling Soil 3rd Rate
	East on a Random line between Sec 2 and 11
	Variation 12.30 East
16.00	Stream 3 lks wide runs South
41.00	Set temporary Quarter Sec corner
79.60	Intersected N and S line 60 lks North of corner to sections 1.2.11.12
	From which corner I run
	West on a true line between Sec 2 and 11
	Variation 12.05 E
39.80	Set a Sand Stone 18 inches long 9 inches wide 5 inches thick for Quarter Sec corner
79.60	The corner to sections 2.3.10.11
	Land Rolling prairie Soil 2nd rate

Township No 1 N Range No 1 East 6th Pr Mo

Chain	
	North ~~bet~~ on a Random line between Section 2 and 3
	Variation 12.30 E
30.00	Ravine runs East.
40.00	Set Stake for temporary Quarter Sec corner
80.70	Intersected North Boundary of Township 30 lks East of Corner to Sec 2 and 3. From which corner from South on a true line between Sec 2 and 3
	Variation 12.43 E
40.70	Set a Sand Stone 23 inches long 8 inches wide and 4 inches thick for Quarter Sec Corner
80.70	The corner to Sec 2.3.10.11
	Land Rolling soil 3rd rate
	June 30th 1857
	North between Sections 33 and 34
	Variation 12.00 East
9.00	Road Bears N W and S E
23.00	Ravine runs N E
40.00	Set a Lime Stone 23 inches long 12 inches wide and 2 1/2 inches thick for Quarter Sec corner

Township No 1 N Range No 1 East 6th Pr Mo

Chain	
80.00	Set a Lime Stone 26 inches long 18 inches wide and 3 inches thick for corner to section 27.28.33.34
	Land Rolling prairie Soil 3rd rate
	East on Random line between Sections 27 and 34
	Variation 12.30 East
40.00	Set Sod for temporary Quarter Section corner
46.00	Ravine runs North.
79.96	Intersected N and S line 7 lks South of corner to section 26.27.34.35
	From which corner from West on true line between Sections 27 and 34
	Variation 12.33 East
39.98	Set a Lime Stone 17 inches long 13 inches wide and 3 inches thick for Quarter Sec corner
79.96	The corner to sections 27.28.33.34
	Land Broken Soil 3rd rate
	North between Sections 27 and 28
	Variation 12.30 East
30.00	Ravine runs N E.
40.00	Set a Lime Stone 21 inches long 16 inches wide an 3 in. thick for a Quarter Sec Corner

Township No 1 N Range No 1 East 6th P. M.

Chns	
70.00	Ravine runs East.
80.00	Set a Lime Stone 27 inches long 19 inches wide and 2½ inches thick for corner to Sec 21.22.27.28
	Land Rolling prairie Soil 3rd rate
	East on a Random line between Sections 22 & 27
	Variation 12.30 E
40.00	Set Sod for temporary Quarter Sec corner
65.00	Stream 5 lks wide runs N E.
80.10	Intersected Nand S line 9 lks South of corner to Sec 23.22.26.27
	From which corner of run
	West on a true line between Sections 22 and 27
	Variation 12.34 E
40.05	Set a Sand Stone 18 inches long 15 inches wide and 3 inches thick for Quarter Sec corner
80.10	The corner to Sec 21.22.27.28
	Land Rolling prairie Soil 3rd rate
	North between Sections 21 and 22
	Variation 12.30 E
40.00	Set a Sand Stone 17 inches long 14 inches wide and 3 inches for Quarter Sec corner

Township No 1 N Range No 1 East 6th P. M.

Chns	
70.00	Ravine runs N W
80.00	Set a Sand Stone 19 inches long 15 inches wide 3 inches thick for corner to Sections 15.16.21.22
	Land Surface Broken Soil 3rd rate
	East on a Random line between Sections 15 and 22
	Variation 12.30 East
40.00	Set Stake for temporary Quarter Sec corner
41.00	Ravine runs North
80.18	Intersected Nand S line 24 lks North of corner to Sec 14.15.22.23
	From which corner of run,
	West on a true line between Sec 15 and 22
	Variation 12.20 East
40.09	Set a Sand Stone 15 inches long 12 inches wide and 3 inches thick for Quarter Sec corner
80.18	The corner to Sections 15.16.21.22
	Land Rolling prairie Soil 3rd rate
	North between Sections 15 and 16
	Variation 12.30 East
10.00	Ravine runs N E.
40.00	Set Sand Stone 18 inches long 13 inches wide

Township No 1 N Range No 1 East 6th P.M. Ind.

Chain	
	and 4 inches thick for Quarter sec corner
47.00	Stream 20 lks wide runs N.E.
80.02	Set a Sand Stone 22 inches long 7 inches wide and 3 inches thick for corner to sec 9, 10, 15, 16
	Land Rolling prairie Soil 3rd rate
	East on Random line between sections 10 and 15
	Variation 12.30 E
40.00	Set Sod for temporary Quarter sec Corner
80.16	Intersected N and S line 32 lks North of corner to sections 10, 11, 14, 15
	From which corner I run
	West on a true line between Sec 10 & 15
	Var 12.17 East
40.08	Set a Sand Stone 21 inches long 10 inches wide and 3 inches thick for Quarter sec corner
80.16	The corner to sections 9, 10, 15, 16
	Land Rolling prairie Soil 3rd rate
	North between Sections 9 and 10
	Variation 12.30 E
40.00	Set a Sand Stone 15 inches long 10 inches wide and 4 inches thick Quarter Section Corner

Township No 1 N Range No 1 East 6th P.M. Ind.

Chain	
57.00	Varies runs East
80.02	Set a Sand stone 27 inches long 7 inches wide and 6 inches thick for corner to sections 34, 2, 10
	Land Rolling prairie Soil 3rd rate
	East on a Random line between Sections 3 and 10
	Variation 12.30 E
38.00	Stream 10 lks wide runs S. East
40.00	Set stone for temporary Quarter sec corner
80.15	Intersected N and S line 38 lks North of corner to sections 2, 3, 10, 11
	From which corner I run
	West on a true line between sections 3 and 10
	Variation 12.14 East
40.07	Set a Sand Stone 18 inches long 8 inches wide and 5 inches thick for Quarter Section corner
80.15	The corner to section 3, 4, 9, 10
	Land Rolling prairie Soil 3rd rate
	North on a Random line between Sections 3 and 4
	Variation 12.30 East
40.00	Set stake for temporary Quarter sec corner

Township No 1 N Range No 1 East 6th P.M.

Chs	
71.00	Stream 10 lks wide runs S E.
80.75	Intersected North Boundary of Township 24 lks East of the corner to sec 3 & 4
	From which corner I run
	South on a true line between sections 3 and 4
	Variation 12.40 E
40.75	Set a Sand Stone 20 inches long 12 inches wide and 4 inches thick for Quarter sec Corner
80.75	The corner to sections 3. 4. 9. 10
	Land Rolling prairie Soil 2nd rate
	July 1st 1857
	North between Sections 32 and 33
	Variation 12.00 East
40.00	set a Lime Stone 18 inches long 12 inches wide and 3 inches thick for Quarter sec corner
75.00	Road Bearing N W and S E
80.00	set a Lime Stone 20 inches long 18 wide and 2 1/2 inches thick for corner to sec 28. 29. 32. 33
	Land Rolling prairie Soil 3rd rate
	East on a Random line between sections 28 and 33

Township No 1 N Range No 1 E 6th P.M.

Chs	
	Variation 12.30 E
10.00	Roaring runs N E
40.00	set Stone for temporary Quarter sec corner
80.12	Intersected N and S line 21 lks North of corner to sections 27. 28. 33. 34
	From which Corner I run
	West on a true line between sections 28 & 33
	Variation 12.21 E.
40.06	Set a Lime Stone 26 inches long 20 inches wide and 2 1/2 inches thick for Quarter sec corner
80.12	The corner to sections 28. 29. 32. 33
	Land Rolling prairie Soil 3rd rate
	North between sections 28 and 29
	Variation 12.30 E.
36.00	Roaring runs N E
40.00	set a Lime Stone 21 inches long 19 inches wide and 2 1/2 inches thick for Quarter sec Corner
80.00	set a Lime Stone 28 inches long 17 inches wide and 3 inches thick for Corner to sec 20. 21. 28. 29
	Land Rolling prairie soil 3rd rate

Township No 1 N Range No 1 East 6th P.M. No 2

Chains

East on a Random line between Sec 21 and 28

Variation 12.30 E

40.00 Set a Sod for temporary Quarter Sec corner

80.20 Intersected N and S line 20 lks South of corner to Sec 21, 22, 27, 28. From which corner of run West on a true line between sections 21 and 28

Variation 12.38 E

40.10 Set a Lime Stone 21 inches long 10 inches wide and 3 inches thick for Quarter Sec corner

80.20 The corner to sections 20. 21. 28. 29

Land Rolling Soil 3rd rate

North between Sections 20 and 21

Variation 12.30 E

40.00 set a Lime Stone 18 inches 13 inches wide and 3 inches thick for a Quarter section corner

64.00 Ravine runs N E

80.00 Set a Lime Stone 24 inches long 10 inches wide and 3 inches thick for corner to Sec 16. 17. 20. 21

Land Rolling prairie soil 3rd rate

East on a Random line between sections 16 and 21

Variation 12.30 East

Township No 1 N Range 1 East of 6th P.M.

Chains

15.00 Ravine runs North

40.00 Set Stone for temporary Quarter Sec corner

60.00 Ravine runs N E

80.17 Intersected N and S line 22 lks South of corner to sec 13. 16. 21. 22

From which corner of run West on a true line between sections 16 + 21

Variation 12.39 E

40.08 Set a Lime Stone 21 inches long 10 inches wide and 3 inches thick for Quarter Sec corner

80.17 The corner to sections 16. 17. 20. 21

Land Rolling Prairie Soil 3rd rate

North between Sec 16 and 17

Variation 12.30 E

40.00 set a Lime Stone 23 inches long 10 inches wide and 3 inches thick for Quarter Sec corner

43.50 Stream 20 lks wide runs East

80.00 Set a Lime Stone 29 inches long 17 inches wide and 3 inches thick for corner to Sec 8. 9. 16. 17

Land Rolling prairie soil 3rd rate

Township No 1 N Range No 1 East 6th P.M.

Chns

East on a Random line between Sections 9 and 16

Variation 12.30 E

40.00 set sod for temporary Quarter Sec corner

80.10 Intersected N and S line 41 lks South of corner to sections 9, 10, 15, 16

From which corner of run

West on a true line between section 9 and 16

Variation 12.47 E

40.03 Set a Lime Stone 21 inches long 14 inches wide and 2½ inches thick for Quarter section Corner

80.10 The corner to sections 8, 9, 16, 17

Land Rolling prairie soil 3rd rate

North between Sections 8 and 9

Variation 12.30 East

40.00 Set a Lime Stone 24 inches long 13 inches wide and 2½ inches thick for Quarter Sec Corner

80.00 Set a Lime Stone 20 inches long 21 inches wide and 2½ inches thick for corner to sections 4, 5, 8, 9, Land Rolling prairie soil 3rd rate

East on a Random line between Sections 4 and 9

Variation 12.30 E

Township No 1 N Range No 1 E 6th P.M.

Chs

40.00 Set sod for temp Quarter Sec corner

80.20 Intersected N and S line 13 lks South of corner to sections 3, 4, 9, 10

From which corner of run

West on a true line between sections 4 and 9

Variation 12.30 E

40.10 Set a Lime Stone 20 inches long 12 inches wide and 2½ inches thick for Quarter Sec corner

80.20 The corner to sections 4, 5, 8, 9

Land Rolling prairie soil 3rd rate

North on a Random line between sections 4 and 5

Variation 12.30 E.

40.00 Set sod for temporary Quarter Section corner

80.76 Intersected North boundary of Township 30 lks west of corner to sec 4 and 5

From which corner of run

South on a true line between sections 4 & 5

Variation 12.17 E

40.76 Set a Lime Stone 24 inches long 21 inches wide and 2½ inches thick for Quarter sec corner

Township No 1 N Range No 1 East 6th Pr Mer

Chains	
80.16	The corner to sections 4.5.8.9
	Land Rolling prairie soil 3rd rate
	July 2nd 1857
	North between sections 31 and 32
	Variation 12.00 East
40.00	Set a Lime Stone 23 inches long 14 inches wide
	and 3 inches thick for Quarter sec corner
80.00	Set a Lime stone 26 inches long 12 inches wide
	and 4 inches thick for corner to sections 29.30
	31.32. Land Rolling prairie soil 3rd rate
	East on a Random between sections 29 and 32
	Variation 12.30 East
4.00	Ravine runs N W
40.00	Set sod for temporary Quarter sec corner
75.00	Road Bearing N W and S E
80.12	Intersected N and S line 28 lks South of
	Corner to sections 28.29.32.33
	From which corner of run
	West on a true line between 29 and 32
	Variation 12.42 East
40.00	Set a Lime stone 22 inches long 13 inches wide

Township No 1 N Range No 1 East 6th Pr Mer

Chains	
	and 3 inches thick for Quarter section corner
80.12	The corner to 29.30.31.32
	Land Rolling prairie soil 3rd rate
	West on a Random line between sec 30 and 31
	Variation 12.30 East
31.00	Ravine runs N E.
40.00	Set stake for temporary Quarter sec corner
81.50	Intersected West Boundary of Township 6 lks
	South of corner to section 30 and 31
	From which corner of run
	East on a true line between sections 30 and 31
	Variation 12.28 East
41.50	Set a Lime stone 21 inches long 15 inches wide
	and 3 inches thick for Quarter section corner
81.50	The corner to sections 29.30.31.32
	Land Rolling prairie soil 3rd rate
>	North between section 29 and 30
	Variation 12.30 East
13.00	Ravine runs N W
40.00	Set a Lime Stone 21 inches long 12 inches wide

Township No 1 N Range No 1 East 6th P.M.

Chains	
	and 3 inches thick for Quarter sec corner
80.00	set a Lime Stone 28 inches long 10 inches wide
	and 3 inches thick for corner to sections
	19. 20 29. 30
	Land Rolling prairie soil 3rd rate
	East on a Random line between sections 20 & 29
	Variation 12.30 East
40.00	set Stone for temporary Quarter sec corner
42.00	Ravine runs N W
71.00	Road Bearing N and S E
80.15	Intersected N and S line 21 lks South of
	corner to sections 20. 21. 28. 29
	From which corner of run
	West on a true line between sec 20 and 29
	Variation 12.39 East
40.07	set a Lime Stone 20. inches long 12 inches wide
	and 3 inches thick for a Quarter sec corner
80.15	The corner to sections 19. 20, 29. 30
	Land Rolling prairie soil 3rd rate
	West on a Random line between Section 19 and 30
	Variation 12.30 E

Township No 1 N Range No 1 East 6th P.M.

Chains	
10.00	Ravine runs North
40.00	Set Stone for temporary Quarter sec corner
81.52	Intersected West Boundary of Township 20 lks
	South of corner to section 19 and 30
	From which corner of run
	East on a true line between sections 19 and 30
	Variation 12.22 East
41.52	Set a Lime Stone 21 inches long 10 inches wide
	and 3 inches thick for Quarter section corner
81.52	The corner to section 19. 20. 29. 30
	Land Rolling prairie soil 3rd rate
	North between Sections 19 and 20
	Variation 12.30 East
40.00	set a Lime Stone 26 inches long 12 inches wide
	and 3 inches thick for Quarter section corner
70.00	Ravine runs West
80.00	Set Lime Stone 20 inches long 10 inches wide
	and 3 inches thick for corner to sec 17. 18, 19. 20
	Land Rolling prairie soil 3rd rate

Township No 1 N Range No 1 East 6th P.M. No.

Chains

East on a Random line between Sections 17 and 20

Variation 12.30 East

40.00 Set stone for temporary Quarter Sec corner

46.00 Road Bears N and S

80.30 Intersected N and S line 14 lks North of corner to sections 16, 17, 20, 21

From which corner I run

West on a true line between Sec 17 and 20

Variation 12.24 East

40.15 Set a Lime stone 23 inches long 12 inches wide and 3 inches thick for a Quarter section corner

80.30 The corner to sections 17, 18, 19, 20

Land Rolling prairie soil 2nd Rate

West on a Random line between Section 18 & 19

Variation 12.30 East

10.00 Racine runs N E

40.00 set stone for temporary Quarter section corner

81.30 Intersected West Boundary of Township 58 lks south of corner to Sec 19 & 18

~~West~~ From which corner I run

East on a true line between sec 18 and 19

Township No 1 N Range No 1 East 6th P.M. No.

Chains

Variation 12.05 East

41.30 Set a Lime stone 22 inches long 14 inches wide and 2 1/2 inches thick for Quarter sec corner

81.30 The corner to Sections 17, 18, 19, 20

Land Rolling prairie soil 3rd rate

North between Sections 17 and 18

Variation 12.30 East

6.00 Same prairie and Enters timber Bears N E and S W

7.00 Stream 4 lks wide runs N E

20.00 Stream 20 lks wide runs N E

30.00 ~~Leaves~~ Leaves timber and Enters prairie N E and S W

35.00 Same Stream 30 lks wide runs S W

40.00 Set a Lime Stone 20 inches long 9 inches wide and 3 inches thick for Quarter Sec corner

44.00 Same Stream 40 lks wide runs ~~S~~ E

80.00 Set a Lime stone 28 inches long 16 inches wide and 3 inches thick for corner to sections 7, 8, 17, 18. Land Rolling soil 2nd Rate

Timber Oak and Cottonwood

East on a Random line between Sec 8 and 17

2nd Township No 1 N Range No 1 East 6th P.M. No 4

Chains

Variation 12.30 East

35.00 Ravine runs South

40.00 set stone for temp Quarter Section corner

73.00 Road Bears N W and South.

80.24 Intersected N and S line 16 lks south of corner to sec thru 8.9.16.17

From which corner I run

West on a true line between sections 8 and 17

Variation 12.37 East

40.12 set a Lime Stone 17 inches long 15 inches wide and 2½ inches thick for a Quarter sec corner

80.24 The corner to sec. 7.8.17.18

Land Rolling prairie soil 3rd rate

July 3rd 1857

West on a Random line between sec 7 and 18

Variation 12.30 East

27.00 Ravine runs South

40.00 Set Stake for temporary Quarter sec corner

42.00 Stream 20 lks wide runs S E

81.18 Intersected West Boundary of Township 78 lks South of Corner to sections 7 and 18

2nd Township No 1 N Range 1 East 6th P.M. No 4

Chains

From which Corner I run

East on a true line between Sections 7 and 18

Variation 11.57 East

41.18 Set a Lime Stone 21 inches long 10 inches wide and 3 inches thick for Quarter Sec corner

81.18 The corner to sections 7.8.17.18

Land Rolling prairie soil 3rd rate

North between sec 7 and 8

Variation 12.30 East

40.00 Set a Sand Stone 17 inches long 14 inches wide and 8 inches thick for Quarter sec corner

80.00 Set a Sand Stone 21 inches long 15 inches wide and 3 inches thick for corner to sec 5.6.7.8

Land Rolling prairie soil 3rd rate

East on a Random line between section 5 and 8

Variation 12.30 East

40.00 Set Stone for temporary Quarter sec corner

65.00 Road Bears N W & S E

80.10 Intersected N and S line 13 lks south of corner to sections 4.5.8.9

Township No 1 North Range 1 East 6th P.M. No 4

Chains

From which corner of run

West on a true line between sections 5 & 8

Variation 12.35 East

40.05 set a sand stone 16 inches long 14 inches wide and 3 inches thick for quarter section corner

80.10 The corner to sections 5, 6, 7, 8

Land Rolling prairie soil 3rd rate

West on a Random line between Sec 6 and 7

Variation 12.00 East

40.00 set sod for temporary quarter section corner

80.90 Intersected West Boundary of Township 40 lks South of corner to sec 6 and 7

From which corner of run

East on a true line between sec 6 and 7

Variation 11.45 East

40.80 Set sand stone 19 inches long 15 inches wide and 3 inches thick for quart sec corner

80.90 The corner to sec 5, 6, 7, 8

Land Rolling prairie soil 3rd rate

South on a Random line between sections 5 and 6

Variation 12.30 East

Township No 1 N Range No 1 East 6th P.M. No 4

Chain

40.00 set stone for temporary quarter section corner

81.30 Intersected North Boundary of Township 38 lks East of corner to section 5 and 6

From which corner of run

South on a true line between sec 5 and 6

Variation 12.54 East

41.30 set a sand stone 14 inches long 12 inches wide and 3 inches thick for quarter sec corner

81.30 The corner to section 5, 6, 7, 8

Land Rolling prairie soil 3rd rate

July 4th 1857

The quality of land in this Township is considerably under the common average. Timber chiefly Oak and cotton wood, and is very scarce. Water sufficient for ordinary demands There are several good quarries of Stone principally Sand in southern part of the Township. No Settlement in the Township.

We hereby certify that we assisted Thomas. H. Doyle. Deputy Surveyor. in Subdividing Township number One North of the Base line of Range number One East of the 6th Principal meridian, and said Township has been in all respects to the best of our Knowledge and belief. well and faithfully surveyed. and boundary Monuments planted according to the instructions furnished by the Surveyor General

Nelson his mark McCollum Chainman
Nikolas Bichler Chainman
A Risley Axeman
David McCollum Flagman
Morse. M. Caldwell Compassman

Sworn to and Subscribed before me this 5th day August A D 1857

James S Magill
Justice of the Peace

List of Names

A list of the names of the individuals employed to assist in running measuring or marking the lines and corners described in the foregoing field notes Township No 1 North of Range No 1 East of the 6th Principal Meridian, showing the respective capacities in which they acted

Nelson McCollum	Chainman
Nickolas Beckler	Chainman
A. C. Richey	Axeman
David McCollum	Flagman
Monroe M. Caldwell	Compassman

Plotted

Field notes
of the survey of the subdivisional
lines of Township No. 2 North of Range
No. 1 East of the 6th Pl. Mdn. N. T.
Surveyed by
T. H. Doyle. Dep. Sur
Under his Contract No. 204. bearing
date June 27th A D 1857.

Subdivision Commenced July 8th 1857.
Subdivision Completed July 14th 1857.

Names and duties of assistants

George M. Tilford Compassman
Robert Mack. Chainman
Zacharius Kohlen "
Samuel Campbell Flagman
Frederick Kuhn. Marker.

Township 2 N. Range 1 East

6	35	5	25	4	19	3	13	2	8	1
34		33		25		19		13		7
7	33	8	24	9	18	10	12	11	7	12
32		32		24		18		12		6
18	31	17	23	16	17	15	11	14	6	13
30		30		23		17		11		5
19	29	20	22	21	16	22	10	23	5	24
29		28		22		16		10		4
30	28	29	21	28	15	27	9	26	3	25
27		26		20		15		9		3
31	26	32	20	33	14	34	8	35	2	36

Field Notes of the subdivision lines in Township 2 N. Range 1 E. 6th P.M. Mer.

Sh. To determine the proper adjustment of my Compass for subdividing this Town-ship. I Commence at the Corner to Townships 1 & 2 N. Ranges 1 & 2 E and run North on a blank line along the East Boun-dary of ~~section~~ section 36.

Variation 11° 30' East

39.90 To a point 16 lks. East of Quarter sec. Corner.

79.86 To a point 34 lks. East of Corner to sect. 25 & 36.

To retrace this line or run parallel there-to my Compass must be adjusted to a Variation of 12° 00' East.

Subdivision Commenced July 8th 1857.

From the Corner to sections 1, 2, 35 & 36. on the South Boundary of the Township Run

North. between sections 35 and 36.

Variation 12° 00' East

40.00 Set a limestone, 18 in. long 12 in. wide, & 3 in. thick

Township 2 N. Range 1, E. 6th P. M.

for quarter section Corner.

80,00 Set a Limestone, 22 in. Long, 8 in. wide & 4 in. thick for corner to sect. 25. 26. 35 & 36.

Land gently rolling - Soil 1st rate.

East on a random line between sect. 25 & 36.

Variation 11° 45' East.

14,00 Brook 5 lks. wide - runs S.

40,00 Set a stone for temporary quarter sec. Corner

79,76 Intersected the East Boundary of the Township 10 lks. South of the corner to sect. 25 & 36. from which Corner I run West on a true line between sect. 25 & 36.

Variation 11° 49' East

39,88 Set a Limestone, 20 in. Long, 12 in. wide & 3 in. thick. for quarter section Corner

79,76 The Corner to sect. 25. 26. 35 & 36.

Surface gently rolling - Soil 1st rate.

North between sections 25 & 26

Variation 12° 15' East.

40,00 Set a Limestone, 16 in. Long, 12 in. wide & 3 in. thick, for quarter section Corner.

80,00 Set a Limestone 18 in. Long, 12 in. wide & 3 in. thick, for Corner to sections 23, 24, 25 & 26.

Surface gently rolling - Soil 1st rate.

East on a random line between sect. 24 & 25.

Variation 11° 45' East.

40,00 Set a Stone for temporary quarter sec. Corner.

80,26 Intersected the East Boundary of the Township 11 lks. North of Corner to sect. 24 & 25. from which Corner I run West on a true line between sect. 24 & 25.

Variation 11° 40' East.

40,13 Set a Limestone, 16 in. Long, 12 in. wide & 3 in. thick, for quarter section Corner.

80,26 The Corner to sect. 23. 24. 25 & 26.

Surface gently rolling.

Soil 1st rate.

Township 2 N. Range 1 E. 6th P.M.

North, between secs. 23 & 24,
Variation 12° 15' East.

40,00 Set a limestone 15 in. long, 14 in. wide & 3 in. thick, for quarter section Corner.

80,00 Set a limestone 20 in. long, 12 in. wide & 3 in. thick, for Corner to secs. 13, 14, 23 & 24.

Surface level - Soil 1st rate.

East on a random line between secs. 13 & 24.
Variation 11° 45' East.

34,00 Branch 5 lks. wide runs S.E.

40,00 Set stone for temporary quarter sec. Corner.

80,14 Intersected the East Boundary of the Township 18 lks. North of Corner to secs. 13 & 24. from which Corner I run

West on a true line between secs. 13 & 24.
Variation 11° 37' East.

40,07 Set a limestone 16 in. long, 12 in. wide & 3 in. thick, for quarter sec. Corner

80,14 The Corner to secs. 13, 14, 23 & 24.

Township 2 N. Range 1 E. 6th P.M.

Surface gently rolling - Soil 1st rate.

North, between secs. 13 & 14.
Variation 12° 00' East.

33,00 Branch 5 lks. wide runs S.E.

40,00 Set a limestone 16 in. long, 14 in. wide & 3 in. thick for quarter sec. Corner.

80,00 Set a limestone, 18 in. long, 14 in. wide & 4 in. thick for Corner to secs. 11, 12, 13 & 14.

Surface gently rolling - Soil 2nd rate.

East on a random line between secs. 12 & 13.
Variation 11° 45' East.

40,00 Set a stone for temporary quarter sec. Corner.

80,24 Intersected the East Boundary of the Township 44 lks. North of Corner to secs. 12 & 13. from which Corner I run

West on a true line between secs. 12 & 13.
Variation 11° 26' East

40,12 Set a limestone, 18 in. long, 14 in. wide & 2½ in. thick,

Township 2 N. Range 1 E. 6th P.M. Mdn.

for Quarter section Corner

80.24 The Corner to sec. 11, 12, 13 & 14.

Surface gently rolling - Soil 2nd rate,

North between sec. 11 & 12,

Variation 11° 45' East,

40.00 Set a limestone, 16 in. long, 12 in. wide & 3 in. thick, for Quarter sec. Corner,

80.00 Set a limestone, 18 in. long, 14 in. wide & 3 in. thick, for Corner to sec. 1, 2, 11 & 12,

Surface level - Soil 2nd rate

East on a random line, between sec. 1 & 12,

Variation 11° 45' East,

40.00 Set a Stake, for temporary Quarter sec. Corner

79.90 Intersected the East Boundary of the Town-ship 20 lks. North of Corner to sec. 1 & 12 from which Corner I run

West on a true line between sec. 1 & 12,

Variation 11° 36' East,

Township 2 N. Range 1 E. 6th P.M. Mdn.

39.95 Set a limestone 22 in. long, 18 in. wide, & 2½ in. thick, for Quarter section Corner

79.90 The Corner to sec. 1, 2, 11 & 12,

Surface rolling - Soil 1st rate,

North on a random line between sec. 1 & 2,

Variation 11° 45' East

40.00 Set a stone for temporary Quarter sec. Corner,

79.10 Intersected the North Boundary of the Town-ship 8 lks. East of the Corner to sec. 1 & 2, from which Corner I run

South on a true line between sec. 1 & 2,

Variation 11° 49' East

39.10 Set a limestone 18 in. long, 12 in. wide, & 3 in. thick for Quarter section Corner,

79.10 The Corner to sec. 1, 2, 11 & 12,

Surface rolling - Soil 1st rate,

July 8th 1857

North between sections 34 & 35

Variation 12° 15' East,

Township 2 N. Range 1 E. 6th P.M. Mdn.

13,00 Branch 6 lks. wide runs S.E.

40,00 Set a limestone, 16 in. long, 13 in. wide & 3 in. thick, for quarter section Corner.

80,00 Set Sandstone, 22 in. long, 14 in. wide & 2½ in. thick, for Corner to sects. 26, 27, 34 & 35.

Surface level - Soil 1st rate

East, on a random line between sects. 26 & 35

Variation 11° 45' East

40,00 Set stone for temporary Quarter sec. Corner,

79,60 Intersected the N & S. line 14 lks. S. of Corner to sects. 25, 26, 35 & 36, from which Cor. Sun West, on a true line between sects. 26 & 35,

Variation 11° 51' East

39,80 Set a Sandstone, 15 in. long, 12 in. wide, & 3 in. thick for Quarter sec. Corner,

79,60 The Corner to sects. 26, 27, 34 & 35,

Surface gently rolling Soil 1st rate,

North. between sections 26 & 27,

Township 2 N. Range 1 E. 6th P.M. Mdn.

Variation 12° 15' East

40,00 Set a Sandstone 18 in. long, 14 in. wide & 3 in. thick, for Quarter sec. Corner,

80,00 Set a Sandstone 18 in. long, 12 in. wide & 3 in. thick, for Corner to sects. 22, 23, 26 & 27.

Surface gently rolling Soil 1st rate,

East on a random line between sects. 23 & 26,

Variation 11° 45' East,

40,00 Set a stone for temporary Quarter sec. Corner,

79,64 Intersected the N & S. line 4 lks. S. of Corner to sects. 23, 24, 25 & 26, from which Cor. Sun West, on a true line between sects. 23 & 26,

Variation 11° 46' East,

39,82 Set a Sand Stone, 20 in. long, 12 in. wide & 3 in. thick, for Quarter section Corner,

79,64 The Corner to sections 22, 23, 26 & 27,

Surface gently rolling Soil 1st rate,

North, between sections 22 & 23,

Township 2 N. Range 1 E. 6th P.M.

Variation 12° 15' East.

40,00 Set a Sandstone 18 in. long, 12 in. wide & 3 in. thick, for quarter sec. Corner.

80,00 Set a Sandstone, 18 in long, 14 in. wide & 2½ in. thick, for Corner to sec. 14, 15, 22 & 23. Surface gently rolling - Soil 1st rate.

East on a random line between sec. 14 & 23.

Variation 11° 45' East.

40,00 Set stone for temporary quarter sec. Corner.

80,40 Intersected the N. & S. line 8 lks. South of the Corner to sec. 13, 14, 23 & 24, from which Cor. Sun West on a true line between sec. 14 & 23.

Variation 11° 48' East.

40,20 Set a Sandstone 16 in. long, 12 in. wide & 3 in. thick, for quarter sec. Corner.

80,40 The Corner to sec. 14, 15, 22 & 23. Surface gently rolling - Soil 1st rate.

North between sections 14 & 15.

Township 2 N. Range 1 E. 6th P.M.

Variation 11° 45' East.

40,00 Set a Sandstone, 16 in. long, 12 in. wide & 3 in. thick, for quarter sec. Corner.

80,00 Set a Sandstone, 20 in. long, 18 in. wide & 3 in. thick, for Corner to sec. 10, 11, 14 & 15. Surface level - Soil 1st rate.

East on a random line between sec. 11 & 14.

Variation 11° 45' East.

40,00 Set a stone for temporary quarter sec. Corner.

80,30 Intersected the N. & S. line, 18 lks. South of the Corner to sec. 11, 12, 13 & 14, from which Cor. Sun West, on a true line between sec. 11 & 14.

Variation 11° 55' East.

40,15 Set a Sandstone, 18 in. long, 18 in. wide & 2½ in. thick, for quarter sec. Corner.

80,30 The Corner to sec. 10, 11, 14 & 15. Surface gently rolling - Soil 1st rate.

North between sections 10 & 11.

Township 2 N. Range 1 E. 6th P.M.

Variation 11° 45' East.

40,00 Set a Sandstone, 14 in. long, 12 in. wide & 3 in. thick, for Quarter sec. Corner.

80,00 Set a Sandstone, 18 in. long, 18 in. wide & 3 in. thick, for Corner to Sec. 2, 3, 10 & 11. Surface level - Soil 1st rate.

East on a random line between Sec. 2 & 11.

Variation 11° 45' East.

40,00 Set stone for temporary Quarter sec. Corner

80,40 Intersected the N. & S. line, 30 lks. South of the Corner to sec. 1, 2, 11 & 12, from which Cor. Tree West, on a true line between sec. 2 & 11.

Variation 11° 38' East

40,20 Set a Sandstone 28 in. long, 14 in. wide & 2½ in. thick, for Quarter sec. Corner

80,40 The Corner to sec. 2, 3, 10 & 11

Surface gently rolling - Soil 1st rate.

North on a Random line between sec. 2 & 3.

Township 2 N. Range 1 E. 6th P.M.

Variation 11° 45' East.

40,00 Set stone for temporary Quarter sec. Corner.

79,15 Intersected the North Boundary of the Township, 20 lks. West of Corner to sec. 2 & 3. from which Corner Drum South on a true line, between sec. 2 & 3.

Variation 11° 37' East.

39,18 Set a Sandstone, 15 in. long, 12 in. wide & 3 in. thick, for Quarter sec. Corner.

79,18 The Corner to sec. 2, 3, 10 & 11.

Surface level - Soil 1st rate.

July 9th 1857.

North, between sec. 33 & 34.

Variation 12° 15' East.

40,00 Set a Sandstone, 16 in. long, 14 in. wide & 3 in. thick, for Quarter section Corner.

80,00 Set a Sandstone 18 in. long, 12 in. wide & 3 in. thick, for Corner to sec. 27, 28, 33 & 34.

Surface gently rolling

Soil 1st rate.

Township 2 N. Range 1 E. 6th P.M. Mdn.

East on a random line between secs. 27 & 34.
Variation 11° 45' East

40.00 set stone for temporary quarter sec. Corner
61.00 Branch 10 lks. wide - runs S. E.
79.88 Intersected the N & S. line 20 lks. N. of Corner to secs. 26, 27, 34 & 35, from which Cor. I run
West, on a true line between secs. 27 & 34.
Variation 11° 36' East
39.94 Set a Sandstone, 18 in. long, 12 in. wide & 3 in. thick, for quarter sec. Corner
79.88 The Corner to secs. 27, 28, 33 & 34.
Surface gently rolling - soil 1st rate

North, between sections 27 & 28
Variation 12° 15' East
40.00 Set a sandstone 18 in. long, 12 in. wide & 3 in. thick, for quarter sec. Corner,
80.00 Set a limestone 18 in. long, 12 in. wide, & 3 in. thick for Corner to secs. 21, 22, 27 & 28.
Land gently rolling. Soil 1st rate.

Township 2 N. Range 1 E. 6th P.M. Mdn.

East on random line between secs. 22 & 27.
Variation 11° 45' East.

36.00 Branch 3 lks. wide runs S. E.
40.00 Set a stone for temporary quarter sec. Corner,
79.86 Intersected the N & S. line, 50 lks. North of the Corner to secs. 22, 23, 26, & 27, from which Corner I run
West, on a true line between secs. 22 & 27.
Variation 11° 24' East
39.93 Set a Sandstone 18 in. long 14 in. wide & 4 in. thick, for quarter sec. Corner,
79.86 The Corner to secs. 21, 22, 27 & 28.
Surface gently rolling - Soil 1st rate.

North, between sections 21 & 22.
Variation 12° 15' East.
40.00 Set a limestone, 16 in. long, 11 in. wide, & 3 in. thick, for quarter sec. Corner,
80.00 Set a limestone, 19 in. long, 13 in. wide, & 3 in. thick, for Corner to secs. 15, 16, 21 & 22

Township 2 N. Range 1 E. 6th P.M.

Surface gently rolling - Soil 1st rate

East on a random line between sec. 15 & 22.
Variation 11° 30' East

1.00 Branch 5 lks. wide - Course South.
40.00 Set a Stone for temporary Quarter sec. Corner.
79.90 Intersected the N. & S. line 10 lks. South of the Corner to sec. 14, 15, 22 & 23. from which Corner I run

West on a true line between sec. 15 & 22.
Variation 11° 34' East.

39.95 Set a Sandstone, 15 in. long, 11 in. wide, & 3 in. thick, for Quarter sec. Corner.
79.90 The Corner to sec. 15, 16, 21 & 22.
Surface gently rolling - Soil 1st rate.

North, between sections 15 & 16.
Variation 11° 45' East.

40.00 Set a Sandstone 16 in. long, 11 in. wide & 3 in. thick for Quarter sec. Corner

Township 2 N. Range 1 E. 6th P.M.

80.00 Set a Limestone, 19 in. long, 14 in. wide & 3 in. thick, for Corner to sec. 9, 10, 15 & 16.
Surface gently rolling Soil 1st rate

East on a Random line between sec. 10 & 15.
Variation 11° 30' East.

40.00 Set Stone for temporary Quarter sec. Corner
79.96 Intersected the N. & S. line, 20 lks. S. of the Corner to sec. 10, 11, 14 & 15, from which Cor I run

West on a true line between sec. 10 & 15.
Variation 11° 38' East.

39.98 Set a Sandstone, 16 in. long, 11 in. wide, & 3 in. thick, for Quarter sec. Corner.
79.96 The Corner to sections 9, 10, 15 & 16.
Surface gently rolling - Soil 1st rate.

North, between sections 9 & 10
Variation 11° 45' East

40.00 Set a Limestone 18 in. long, 12 in. wide, & 3 in. thick, for Quarter sec. Corner.

Township 2 N. Range 1 E. 6th Prl. Mdn.

80,00 Set a limestone, 19 in. long, 14 in. wide, & 3 in thick, for Corner to sec. 3. 4. 9 & 10. Surface gently rolling - Soil 1st rate.

East on a random line between sec. 3 & 10
Variation 11° 30' East.

40,00 Set a stone for temporary Quarter sec. Corner
80,04 Intersected the N. & S. line, 30 lks. South of the Corner to sec. 2, 3, 10 & 11, from which Cor. bears West on a true line between sec. 3 & 10,
Variation 11° 45' East.

40,02 Set a Sandstone 18 in. long, 13 in. wide, & 3 in. thick for a Quarter sec. Corner.
80,04 The Corner to sec. 3. 4. 9 & 10.
Surface level - Soil 1st rate.

North on a random line between sec. 3 & 4.
Variation 11° 45' East.

40.00 Set a stone for a temporary Quarter sec. Corner
79.22 Intersected the North Boundary of the

Township 2 N. Range 1 E. 6th Prl. Mdn.

Township 30 lks. West of Corner to sec. 3 & 4, from which Corner bears South on a true line between sec. 3 & 4,
Variation 11° 35' East.

39.22 Set a Sandstone 16 in. long, 14 in. wide, & 3 in. thick, for Quarter sec. Corner,
79.22 The Corner to sections 3. 4. 9 & 10.
Surface gently rolling - Soil 1st rate.
July 11th 1857.

North between sections 32 & 33.
Variation 12° 15' East.

31,50 Branch 5 lks. wide, runs S. E.
40,00 Set a Sandstone, 15 in. long, 12 in. wide & 3 in thick, for Quarter sec. Corner.
80,00 Set a Sandstone, 19 in. long, 14 in. wide, & 3 in. thick, for Corner to sec. 28. 29. 32, & 33,
Surface gently rolling - Soil 1st rate

East on a random line between sec. 28 & 33

Township 2 N. Range 1, E, 6th P.M. Mer.

Variation 11° 45' East.

40.00 Set a Stone, for temporary Quarter sec. Corner

79.80 Intersected the N & S. line, 11 lks. North of the Corner to sect. 27, 28, 33 & 34, from which Corner Doun

West, on a true line, between sect. 28 & 33

Variation 11° 40' East

39.90 Set a Sandstone 16 in. Long, 8 in. wide, & 4 in. thick for Quarter sec. Corner.

79.80 The Corner to sections 28, 29, 32 & 33.

Surface gently rolling - Soil 1st rate

North, between sections 20 & 29.

Variation 12° East.

40.00 Set a Sandstone, 14 in. Long, 12 in. wide & 3 in. thick, for Quarter sec. Corner

80.00 Set a Sandstone, 19 in. Long, 12 in. wide, & 3 in. thick, for Corner to sect. 20, 21, 28 & 29.

Surface gently rolling - Soil 1st rate.

Township 2 N. Range 1 E, 6th P.M. Mer.

East, on a random line between sect. 21 & 28.

Variation 11° 45' East

40.00 Set a temporary Quarter sec. Corner

79.94 Intersected the N & S. line, 8 lks. North of the Corner to sect. 22, 27 & 28, from which Corn. Doun

West, on a true line between sect. 21 & 28.

Variation 11° 42' East.

39.97 Set a Sandstone, 18 in. Long, 12 in. wide, & 3 in. thick for Quarter section Corner.

79.94 The Corner to sections 20, 21, 28 & 29.

Surface gently rolling - Soil 1st rate

North between sections 20 & 21.

Variation 12° East

40.00 Set a Sandstone, 18 in. long, 15 in. wide, & 2½ in. thick for Quarter sec. Corner,

80.00 Set a Sandstone, 20 in. long, 16 in. wide, & 3 in. thick, for Corner to sect. 16, 17, 20 & 21.

Surface level - Soil 1st rate,

Township 2 N. Range 1 E. 6th P.M.

East on a random line between sec. 16 & 21.
Variation 11° 45' East.

40,00 Set a stone for temporary Quarter sec. Corner

79,88 Intersected the N. & S. line, 12 lks. North of Corner to secs. 15, 16, 21 & 22 from which Cor. Sun West, on a true line between secs. 16 & 21.
Variation 11° 40' East.

39,94 Set a Sandstone, 14 in. long, 14 in. wide & 3 in. thick for Quarter sec. Corner.

79,88 The Corner to sections 16, 17, 20 & 21
Surface gently rolling - Soil 1st rate.

North between sections 16 & 17.
Variation 11° 45' East

40,00 Set a Sandstone, 15 in. long, 12 in. wide & 3 in. thick, for Quarter sec. Corner

80,00 Set a Sandstone, 24 in. long, 16 in. wide & 3 in. thick, for Corner to sections. 8, 9, 16 & 17.
Surface gently rolling - Soil 1st rate.

Township 2 N. Range 1 E. 6th P.M.

East on a random line between secs. 9 & 16.
Variation 11° 45' East.

40,00 Set a stone for temporary Quarter sec. Corner

79,78 Intersected the N. & S. line. 30 lks. South of the Corner to secs. 9, 10, 15 & 16, from which Cor. Sun West, on a true line between secs. 9 & 16.
Variation 11° 58' East

39,84 Set a Sandstone, 20 in. long, 8 in. wide & 3 in. thick, for Quarter sec. Corner

79,78 The Corner to secs. 8, 9, 16 & 17.
Surface gently rolling - Soil 1st rate

North between sections 8 & 9.
Variation 11° 45' East.

40,00 Set a Sandstone, 18 in. long, 10 in. wide & 3 in. for Quarter sec. Corner.

80,00 Set a Sandstone, 15 in. long, 14 in. wide & 3 in. thick for Corner to secs. 4, 5, 8 & 9.
Surface gently rolling.
Soil 1st rate.

Township 2 N. Range 1 E. 6th P.M. Mdn.

East on a random line between sec. 4 & 9.
Variation 11° 45' East.

40,00 Set a stone for temporary Quarter sec. Corner

79,70 Intersected the N. & S. line 40 lks. South of the Corner to secs. 3, 4, 9 & 10, from which Corner I run

West, on a true line between secs. 4 & 9.
Variation 12° 22' East.

39,85 Set a sandstone, 18 in. long, 12 in. wide & 3 in. thick, for Quarter sec. Corner.

79,70 The Corner to secs. 4, 5, 8 & 9.
Surface level - Soil 1st rate

North, on a random line between secs. 4 & 5.
Variation 11° 45' East

40,00 Set a stone for temporary Quarter sec. Corner

79,25 Intersected the North boundary of the Township 10 lks. West of Cor. to secs. 4 & 5, from which Corner

South on a true line between secs. 4 & 5
Variation 11° 45' East

Township 2 N. Range 1 E. 6th P.M. Mdn.

39,28 Set a sandstone, 16 in. long, 11 in. wide & 3 in. thick, for Quarter sec. Corner.

79,28 The Corner to secs. 4, 5, 8 & 9.
Surface gently rolling - Soil 1st rate
July 12th 1857.

North between sections 31 & 32.
Variation 12° 15' East.

40,00 Set a sandstone, 18 in. long, 12 in. wide, & 3 in. thick, for Quarter sec. Corner.

80,00 Set a sandstone, 20 in. long, 14 in. wide & 4 in. thick, for Corner to secs. 29, 30, 31 & 32.
Surface gently rolling - Soil 1st rate

East on a random line between secs. 29 & 32.
Variation 11° 45' East.

19,00 Branch 6 lks. wide - Course S.E.

40,00 Road bears N. & S.

40,00 Set a stone for temporary Quarter sec. Corner

79,50 Intersected the N. & S. line, 16 lks. North of the Corner to secs. 28, 29, 32 & 33, from which Cor. I run

Township 2 N. Range 1 E. 6th P.M. Mdn

West on a true line between sects 29 & 32.
Variation 11° 39' East

39,75 Set a Sandstone, 16 in. long, 12 in. wide & 3 in. thick for quarter sec. Corner.

79,50 The Corner to sects 29. 30. 31 & 32.
Surface gently rolling - Soil 1st rate

West on a random line between sects 30 & 31,
Variation 11° 45' East,

40,00 Set a stone for temporary quarter sec. Corner

79,30 Intersected the West Boundary of the Township 40 lks. North of Corner to sects 30 & 31. from which Corner I run
East on a true line between sects 30 & 31.
Variation 12° 02' East,

39,30 Set a Sandstone 16 in. long, 12 in. wide & 3 in. thick for quarter sec. Corner

79,30 The Corner to sects 29, 30, 31, & 32.
Surface rolling - Soil 1st rate

Township 2 N. Range 1 E. 6th P.M. Mdn

North between sections 29 & 30.
Variation 12° 15' East,

40,00 Set a Sandstone 15 in. long, 14 in. wide, & 3 in. thick for quarter sec. Corner.

80,00 Set a Sandstone 18 in. long, 14 in. wide & 3 in. thick, for Corner to sects 19, 20, 29 & 30,
Surface gently rolling - Soil 1st rate

East, on a random line between sects 20 & 29.
Variation 11° 45' East

1,50 Branch 5 lks. wide - Course South

34,00 Road bears N & S,

40,00 Set a stone for temporary quarter sec. Corner

79,68 Intersected the N & S. line 17 lks. North of the Corner to sects 20, 21, 28 & 29. from which Cor. I run
West on a true line, between sections 20 & 29.
Variation 11° 38' East,

39,84 Set a Sandstone 16 in. long, 12 in. wide, & 3 in. thick for quarter sec. Corner

79,68 The Corner to sects 19, 20, 29 & 30

Township 2 N. Range 1 East 6th P.M.

Surface gently rolling
Soil 1st rate

West on a random line between sect. 19 & 30.
Variation 12° East

40.00 Set stone, for temporary quarter sec. Corner
78.83 Intersected the West boundary of the Township 10 lks North of Corner to sect. 19 & 30 from which Corner Drawn
East on a true line, between sects 19 & 30.
Variation 12° 04' E.

36.83 Set a sandstone, 16 in. long, 4 in. wide, & 3 in. thick, for quarter sec. Corner
78.83 The Corner to sections 19, 20, 29 & 30,
Surface gently rolling
Soil 1st rate.

North, between sections 19 & 20.
Variation 12° East

40.00 Set a sandstone 16 in. long, 13 in wide & 3 in. thick

Township 2 N. Range 1 E. 6th P.M. Mdn.

for quarter sec. Corner
80.00 Set a sandstone, 20 in. long, 14 in. wide & 3 in. thick, for Corner to sects. 17, 18, 19 & 20.
Surface gently rolling Soil 1st rate

East, on a random line between sects 17 & 20.
Variation 11° 45' East

32.00 Road bears N. & S.
40.00 Set a stone for temporary quarter sec. Corner
79.88 Intersected the N. & S. line 3 lks. South of the Corner to sect. 16, 17, 20 & 21. from which Cor. Drawn
West on a true line between sects 17 & 20,
Variation 11° 46' East
39.94 Set a sandstone 18 in. long, 16 in. wide, & 2½ in. thick for quarter sec. Corner
79.88 The Corner to sections 17, 18, 19, & 20,
Surface gently rolling
Soil 1st rate,

West on a random line between sections 18 & 19.

Township 2 N. Range 1 E. 6th P.M. Mdn.

Variation 12° East

40,00 Set a Stone for a temporary Quarter sec. Corner

78,76 Intersected the West Boundary of the Township 23 lks. North of the Corner to secs. 18 & 19, from which Corner I run

East on a true line between secs. 18 & 19.

Variation 12° 10' East

38,76 Set a Sandstone, 15 in. long, 12 in. wide & 3 in. thick for Quarter sec. Corner

78,76 The Corner to secs. 17, 18, 19 & 20

Surface gently rolling - soil 1st rate

North, between sections 17 & 18.

Variation 11° 45 East

40,00 Set a Sandstone 15 in. long, 12 in. wide, & 3 in. thick, for Quarter sec. Corner

80,00 Set a Sandstone, 18 in. long 14 in. wide & 3 in thick for Corner to secs. 7, 8, 17 & 18.

Surface level soil 1st rate.

Township 2 N. Range 1 E. 6th P.M. Mdn.

East, on random line between secs. 8 & 17

Variation 11° 45' East

37,00 Road bears N & S.

40,00 Set a Stone for temporary Quarter sec. Corner

79,76 Intersected the N & S. line, 26 lks. S. of the Corner to secs. 8, 9, 16 & 17, from which Cor. I run

West, on a true line, between secs. 8 & 17.

Variation 11° 57' East

39,88 Set a Sandstone, 20 in. long, 12 in. wide & 3 in. thick, for Quarter sec. Corner.

79,76 The Corner to secs. 7, 8, 17 & 18.

Surface level - soil 1st rate

July 13th 1857.

West on a random line, between secs. 7 & 18

Variation 12° East.

40,00 Set stone for temporary Quarter Sec. Corner.

79,30 Intersected the West Boundary of the Township 64 lks. North of Corner to secs. 7 & 18

Township 2 N. Range 1 E. 6th P.M. Mdn.

from which Corner I run
East on a true line between sec. 7 & 18
Variation 12° 27' East

39.50 Set a Sandstone, 22 in. long, 13 in. wide, & 3 in. thick, for 2 quarter sec. Corner

79.50 The Corner to Secs. 7, 8, 17, & 18
Surface gently rolling
Soil 1st rate.

North between sections 7 & 8.
Variation 11° 45' East

40.00 Set a Sandstone, 18 in. long, 10 in. wide, & 3 in. thick, for 2 quarter sec. Corner.

80.00 Set a Sandstone, 20 in. long, 16 in. wide & 3 in. thick, for Corner to secs. 5, 6, 7, & 8.
Surface gently rolling
Soil 1st rate

East on a random line between secs. 5 & 8.
Variation 11° 45' East

Township 2 N. Range 1 E. 6th P.M. Mdn.

23.00 Road bears N. W. & S. E.

40.00 Set a stone for temporary 2 quarter sec. Cor.

79.66 Intersected the N. & S. line 48 lks. South of the Cor. to secs. 4, 5, 8 & 9 from which Cor. I run West on a true line between secs. 5 & 8.
Variation 12° 06' East

39.83 Set a Sandstone 18 in. long, 12 in. wide & 3 in. thick, for 2 quarter section Corner

79.66 The Corner to secs. 5, 6, 7 & 8.
Surface gently rolling.
Soil 1st rate.

West on a random line between secs. 6 & 7.
Variation 12° East

40.00 Set a stone for temporary 2 quarter sec. Corner.

80.04 Intersected the West Boundary of the Township 77 lks. North of Corner to secs. 6 & 7 from which Corner I run
East on a true line between secs. 6 & 7.
Variation 12° 32' East

Township 2 N. Range 1 East, 6th P.M. Mer.

40,04 Set a Sandstone, 20in. long, 20in. wide & 3in. thick, for Quarter section Corner

80,04 The Corner to sects 5, 6, 7 & 8.
Surface level - Soil 1st rate,

North on a random line between sects 5 & 6.
Variation 11° 45' East

16,00 Road bears N.W & S.E.

40,00 Set a stone for temporary Quarter sec. Corner

79,30 Intersected the North Boundary of the Township 4 lks. East of Corner to sects 5 & 6, from which Corner Pinn
South on a true line between sects 5 & 6,
Variation 11, 47' East

39,30 Set a Sandstone, 22in. long, 12in. wide, & 3in. thick for Quarter sec. Corner

79,30 The Corner to sects 5, 6, 7 & 8.
Surface gently rolling
Soil 1st rate,

July 14th 1857

General Description

The Quality of the land in this Township is of the Common average. There is a small portion of bottom land situated in two small creeks in the southern portion of the Township.

The uplands are gently rolling except along the North Boundary where it becomes bluffy.

There is no timber of any kind in the Township, and very little running water.

A List of Names

A List of the Names of the individual employed to assist in running, measuring or marking the lines and Corners described in the foregoing field Notes of Township No. two North of the base line of Range No. 1 East of the 6th Principal Meridian, showing the respective capacities in which they acted.

George M. Tilford, Compassman
Robert Mack, Chainman
Zacharius Kohlen, "
Samuel Campbell, Flagman
Frederick Kuhn, Marker

we hereby certify that we assisted in subdeviding Townships number ~~xxx~~ two three and four North of the Base line of Range number one East of the 6th Principal Meridian, and that said Townships have been in all respects to the best of our knowledge and belief, well and faithfully surveyed and the boundary monuments planted according to the instructions furnished by the Surveyor General

George M. Tilford compassman
Robert Mack Chairman
Zacharias Köhler "
Samuel Campbell Flagman
Friedrich Kuhn Marker

Subscribed and Sworn to by the above named persons, before me a Deputy Surveyor for Nebraska Territory this 31th day of July 1857

Thomas H. Doyle
Deputy Surveyor

Plotted

Field Notes

of the survey of the subdivisional lines of Township No. 3 N. of the base line of Range No. 1 East of the 6th Principal Meridian, Nebraska Territory

Surveyed by

D. H. Doyle Dep. Sur.

Under his Contract No. 204, bearing date June 27th 1857.

Subdivision Commenced July 15th 1857

Subdivision Completed July 22d 1857.

Names and duties of Assistants

George M. Tilford Compassman
Robert Mack, Chainman
Zacharias Kohlenz "
Samuel Campbell, Flagman
Frederick Kuhn, Marker

Township 3 N. Range 1 East

6	38	5	27	4	20	3	14	2	8	1
37		36		26		20		13		7
7	36	8	26	9	19	10	13	11	6	12
35		34		25		19		12		5
18	34	17	25	16	18	15	12	14	5	13
33		32		24		18		11		4
19	32	20	23	21	17	22	11	23	4	24
31		30		23		16		10		3
30	29	29	22	28	16	27	9	26	2	25
29		28		22		15		9		2
31	28	32	21	33	15	34	8	35	1	36

Field Notes of the subdivision lines in Township 3 N. R 1 E. 6th P.M.

Chains

To determine the proper adjustment of my Compass for subdividing this Township. I run

North along the East Boundary of section 36.

Variation 12° East.

39.69 To a point 14 lks. E. of Quarter sec. Corner.

79.92 To a point 37 lks. East of Corner to secs. 25 & 36.

To retrace this line or run parallel thereto my Compass must be adjusted to a Variation of 12° 15' East.

Subdivision Commenced July 15th 1857.

From the Corner to secs. 35 & 36. on the South Boundary of the Township I run North. between sections 35 & 36.

Variation 12° 15' East

Township 3 N. Range 1 E. 6th Pl. Mdn.

40,00 Set a limestone, 16 in. long, 14 in. wide, & 3 in. thick, for Quarter section Corner

80,00 Set a limestone, 20 in. long, 16 in. wide & 3 in. thick, for Corner to secs. 25. 26. 35 & 36.

Surface gently rolling - Soil 1st rate

East on a random line between secs. 25 & 36.

Variation 12° East

40,00 Set a stone for temporary Quarter sec. Corner.

79.60 Intersected East Boundary of the Township 10 lks. South of Corner to secs. 25 & 36. from which Corner I run

West, on a true line between secs. 25 & 36

Variation 12° 04' East,

39.80 Set a limestone 18 in. long, 12 in. wide & 3 in. thick, for Quarter sec. Corner.

79.60 The Corner to secs. 25. 26. 35 & 36.

Surface rolling - Soil 1st rate.

North. between sections 25. & 26

Township 3 N. Range 1 E. 6th Pl. Mdn.

Variation 12° 15' East,

40,00 Set a limestone 18 in. long, 15 in. wide & 3 in. thick, for Quarter sec. Corner.

80,00 Set a limestone, 18 in. long, 17 in. wide & 3 in. thick, for Corner to secs. 23, 24, 25 & 26.

Surface gently rolling - Soil 1st rate,

East on a random line, between secs. 24 & 25

Variation 12° East.

40,00 Set a stone for temporary Quarter sec. Corner

79.66 Intersected East Boundary of the Township 18 lks. North of Corner to secs. 24 & 25 from which Corner I run

West on a true line between secs. 24 & 25,

Variation 11° 52' East,

39.83 Set a limestone, 18 in. long, 14 in. wide & 3 in. thick, for Quarter sec. Corner.

79.66 The Corner to secs. 23, 24, 25 & 26.

Surface gently rolling

Soil 1st rate.

Township 3 N. Range 1 E. 6th P.M.

North, between sections 23 & 24.

Variation 12° 30' East.

40,00 Set a Limestone 16 in. long, 14 in. wide & 3 in. thick, for quarter sec. Corner.

44,50 Right Bank of Little Blue - course East.

46,50 Left Bank, of same & Enter timber bears S.E.

50,00 Entered Prairie bears N.W. & S.E.

80,00 Set a Limestone 24 in. long, 12 in. wide & 3 in. thick, for Corner to sec. 13, 14, 23 & 24.

Surface gently rolling - Soil 1st rate.

East on a random line between sec. 13 & 24.

Variation 12° East.

40,00 Set a stone for temporary quarter sec. Corner.

80,20 Intersected East Boundary of the Township 46 lks. South of the Corner to sec. 13 & 24. from which Corner I run West, on a true line between sec. 13 & 24.

Variation 12° 26' East.

40,10 Set a Limestone, 16 in. long, 14 in. wide & 3 in.

Township 3 N. Range 1 E. 6th P.M.

thick, for quarter sec. Corner.

80,20 The Corner to sec. 13, 14, 23 & 24.

Surface rolling - Soil 1st rate.

North, between sections 13 & 14.

Variation 12° 30' East.

40,00 Set a Limestone 16 in. long, 14 in. wide & 3 in. thick, for quarter sec. Corner.

64,00 Road bears S.E. & N.W.

80,00 Set a Limestone 18 in. long, 12 in. wide & 3 in. thick, for Corner to sec. 11, 12, 13 & 14.

Surface gently rolling - Soil 2nd rate.

East on a random line between sec. 12 & 13.

Variation 12° East.

40,00 Set a stone for temporary quarter sec. Corner.

65,00 Entered timber bears N.E. & S.W.

70,50 Creek 50 lks. wide runs South.

71,00 Left timber bears N. & S.

79,62 Intersected East Boundary of the Township

Township 3 N. Range 1 E 6th P.M.

50 lks. South of Corner to sect. 12 & 13, from which Corner I run West on a true line, between sect. 12 & 13.

Variation 12° 21' East.

39.81 Set a Limestone, 16 in. long, 15 in. wide, & 3 in thick, for quarter sec. Corner.

79.62 The Corner to sect. 11, 12, 13 & 14.

Surface level - Soil 1st rate, Timber Oak, & Elm.

July 15th 1857.

North between sections 11 & 12.

Variation 13° 50' East

8.00 Enter scattering timber bears E. & W.

10.00 Creek, 20 lks. wide - course East

11.00 Leave timber bears E. & W.

38.00 Branch 8 lks. wide - course East

40.00 Set a Limestone, 15 in. long, 12 in. wide & 3 in. thick, for quarter sec. Corner.

80.00 Set a Limestone, 16 in. long, 15 in. wide & 3 in thick, for corner to secs. 1, 2, 11 & 12.

Township 3 N. Range 1 E 6th P.M.

Surface level - Soil 1st rate, Timber Oak & Cottonwood

East on a random line between sect. 1 & 12

Variation 12° East

3.60 Branch 6 lks. wide Course South,

40.00 Set a stone for temporary quarter sec. Corner.

73.50 Creek 50 lks wide - course South.

77.74 Intersected the East Boundary of the Township 60 lks. South of Corner to sect. 1 & 12, from which Corner I run West on a true line between sect. 1 & 12.

Variation 12° 26' East

39.87 Set a Limestone, 16 in. long, 13 in. wide & 3 in. thick, for quarter sec. corner

79.74 The Corner to sect. 1, 2, 11 & 12.

Surface rolling - Soil 3d rate,

North on a random line between sect.

Township 3 N. Range 16 E. 6th P.M.

1 & 2.

Variation 13° East.

22,00 Branch 8 lks. wide - Course S.E.

40,00 Set a stone for temporary Quarter sec. Corner

80,10 Intersected North Boundary of the Township 36 lks. East of Corner to sec. 1 & 2. from which Corner Drum

South on a true line between sec. 1 & 2

Variation 13° 15' East

40,10 Set a limestone 14 in. long, 12 in. wide & 3 in. thick, for Quarter sec. Corner

80,10 The Corner to secs. 1, 2, 11 & 12.

Surface rolling - soil 3rd rate.

North, between sections 34 & 35.

Variation 12° 15' East.

40,00 Set a limestone 16 in. long, 14 in. wide, & 3 in. thick, for Quarter sec. Corner.

80,00 Set a limestone 20 in. long, 15 in. wide & 3 in. thick, for Corner to secs. 26, 27, 34 & 35

Township 3 N. Range 16 E. 6th P.M.

Surface gently rolling - soil 1st rate.

East, on a random line between sec. 26 & 35.

Variation 12° East.

40,00 Set stone for temporary Quarter sec. Corner

80,02 Intersected N. & S. line, 6 lks. North of Corner to secs. 25, 26, 35 & 36, from which Corner Drum

West, on a true line between sec. 26 & 35.

Variation 11°, 58' East.

40,02 Set a limestone, 20 in. long, 18 in. wide & 2½ in. thick, for Quarter sec. Corner

80,02 The Corner to secs. 26, 27, 34 & 35.

Surface gently rolling - soil 1st rate.

North between sections 26 & 27.

Variation 12° 15' East

40,00 Set a limestone, 16 in. long, 13 in. wide & 3 in. thick, for Quarter sec. Corner

Township 3 N. Range 1 E. 6th Pr. Md.

80.00 Set a limestone, 20 in. long, 15 in. wide & 3 in thick, for corner to sec. 22.23.26 & 27.
Surface rolling - soil 1st rate

East, on a random line between sec. 23 & 26.
Variation 12° East

4.00 Entered timber - bears N.W. & S.E.
20.00 Leave timber - bears N.E. & S.W.
40.00 Set a stone for temporary quarter sec. Cor
79.60 Intersected N & S. line 20 lks. South of Corner to sec. 23.24.25 & 26. from which Corner I run.
West on a true line between sec. 23 & 26.
Variation 12° 08' East
39.80 Set a limestone 17 in. long, 14 in. wide & 3 in. thick for quarter sec. corner.
79.60 The corner to sec. 22.23.26 & 27.
Surface rolling Soil 1st rate.
Timber Elm, Oak & Cottonwood

Township 3 N. Range 1 E. 6th Pr. Md.

North, between sections 22 & 23.
Variation 12° 30' East
6.20 Right Bank of little Blue Course East.
8.00 Left bank & Entered timber bears E. & W.
9.00 Leave timber bears E & W.
40.00 Set a limestone, 14 in. long, 12 in. wide & 3 in. thick for quarter sec. Corner.
80.00 Set a limestone, 20 in. long, 15 in. wide & 3 in. thick, for corner to sec. 14.15.22 & 23.
Surface level - Soil 1st rate
Timber Cottonwood.

East on a Random line between sec. 14 & 23.
Variation 12° East.
40.00 Set a stone for temporary quarter sec. Corner.
79.26 Intersected the N & S. line 50 lks. S of corner to sec. 13.14.23 & 24. from which Cor. I run
West on a true line between sec. 14 & 23.
Variation 12° 21' E.

Township 3 N. Range 16 E. 5th P. M.

39.63 Set a limestone, 16in. long, 14in. wide & 3in. thick for quarter sec. Corner.

79.26 The Corner to sections 14, 15, 22 & 23. Surface level - Soil 1st rate.

North between sections 14 & 15,
Variation 12° 30' East

40.00 Set a limestone 16in. long, 14in. wide & 3in thick for quarter sec. Corner.

64.00 Road bears E. & W.

80.00 Set a limestone, 18in. long, 15in. wide & 3in. thick, for Corner to secs. 10, 11, 14 & 15 Surface gently rolling - Soil 1st rate.

July 16th 1857

East on a random line between secs. 11 & 14,
Variation 12° East

40.00 Set a stone for temporary quarter sec Cor

79.76 Intersected N. & S. line 63 lks. S. of Corner to Secs. 11, 12, 13 & 14. from which corner I run West on a true line between secs. 11 & 14.

Township 3 N. Range 1 E. 6th P. M.

Variation 12° 27' East

39.88 Set a limestone 17in long 13in wide & 3in thick, for Quarter sec. Corner

79.76 The Corner to secs. 10, 11, 14 & 15 Surface level - Soil 1st rate

---

North between sections 10 & 11
Variation 13° East

40.00 Set a limestone 16in long 12in wide & 3in thick for Quarter sec. Corner

43.50 Creek 40 lks wide Course S. E

80.00 Set a limestone 20in long 14in wide & 3in thick for Corner to secs. 2, 3, 10, & 11 Surface level - Soil 1st rate

---

East on a random line between sec 2 & 11
Variation 12° 30' East

40.00 Set a stone for temporary Quarter sec Corner

72.88 Intersected N & S line 6 lks North of Corner to secs. 1, 2, 11 & 12, from which Corner I run

Township 3 N. Range 1 E. 6th Pr. Md.

West on a true line between secs. 2. & 11
Variation 12°28' East

39,94 Set a limestone 18 in long 12 in wide & 3 in thick for Quarter sec Corner

79,88 The Corner to secs. 2. 3. 10. & 11
Surface rolling - Soil 3rd rate

North on a Random line between sec 2 & 3
Variation 13° 15' East

40,00 Set a Stone for temporary Quarter sec. Corner

79.80 Intersected North Boundary of Township 36 links. East of Corner to secs. 2 & 3 from which Corner Trun

South on a true line between secs 2. & 3
Variation 13° 30' East

39.30 Set a limestone 14 in long 12 in wide & 3 in thick for Quarter sec Corner

79.30 The Corner to secs. 2. 3. 10. & 11
Surface rolling - Soil 3rd rate

Township 3 N. Range 1 E. 6th Pr. Md.

North between sections 33 & 34.
Variation 12° 30' East

40,00 Set a limestone, 18 in, long, 14 in, wide, & 3 in, thick, for quarter sec. Corner.

80,00 Set a limestone, 20 in, long 16 in, wide, & 3 in, thick, for Corner to secs. 27. 28. 33 & 34.
Surface gently rolling - Soil 1st rate.

East, on random line, between secs. 27 & 34.
Variation 12° East.

16,00 Ravine - Crars N. & S.

40,00 Set a stone for temporary Quarter sec. Cor.

80,16 Intersected N. & S. line 32 lks. S. of Corner to secs. 26. 27. 34 & 35. from which Cor. Trun

West, on a true line between secs. 27 & 34.
Variation 12° 13' East.

40.08 Set a limestone, 20 in. long, 16 in. wide, & 2½ in thick, for Quarter sec. Corner.

80,16 The Corner to secs. 27. 28. 33 & 34.
Surface rolling Soil 1st rate.

Township 3 N. Range 1 E 6th P.M. Mds

North between sections 27 & 28.

Variation 12° 30' East.

40.00 Set a limestone, 18 in. long, 12 in. wide & 3 in. thick, for quarter section corner,

41.00 Entered timber bears N.E. & S.W.

65.00 Ravine bears N.E. & S.W.

66.00 Grave timber bears N.E. & S.W.

80.00 Set a limestone 18 in. long 16 in. wide & 3 in. thick. for corner to sections 21, 22, 27 & 28.

Surface rolling Soil 2nd rate,

Timber Oak.

East on a random line between sec. 22 & 27.

Variation 12° 15' East

1.00 Ravine, bears W. & S.

40.00 Set a stone for temporary quarter sec. Corner

77.70 Intersected N. & S. line 12 lks. South of Corner to sec. 22, 23, 26 & 27, from which Cor. bears West on a true line between sec. 22 & 27,

Variation 12° 20' East

Township 3 N. Range 1 E 6th P.M. Mds

39.95 Set a limestone 16 in. long, 12 in. wide & 3 in. thick, for quarter section Corner

77.70 The Corner to sec. 21, 22, 27 & 28.

Surface rolling Soil 2nd rate.

July 18th 1857.

North, between sections 21 & 22

Variation 12° 30' East.

13.00 Enter timber bears E. & W.

16.00 Right bank of Little Blue Course S. E.

18.50 Left bank of " " " "

30.00 Sandy creek 100 lks. wide runs West.

35.00 Leave timber bears E. & W.

40.00 Set a limestone 18 in. long, 12 in. wide & 3 in. thick for a quarter section Corner

75.00 Sand Creek 100 lks. wide Course S. E.

80.00 Set a limestone, 20 in. long, 20 in. wide & 2½ in. thick, for Corner to sec. 15, 16, 21 & 22

Surface level Soil 1st rate

Timber Cottonwood & Elm.

Township 3 N. Range 16 E 4th P.M. M.D.

East on a random line between sec. 15 & 22
Variation 12° 15' East

40,00 Set a stone for temporary quarter sec. Corner
79,88 Intersected N & S. line 28 lks. South of Corner to sec. 14, 15, 22 & 23. from which Corner Drawn

West on a true line between sec. 15 & 22
Variation 12° 37' East

39,94 Set a Limestone, 18 in. long, 12 in. wide & 3 in. thick, for Quarter sec. Corner
79,88 The Corner to sections 15, 16, 21, & 22.
Surface level Soil 1st rate.

North between sec. 15 and 16,
Variation 12° 45' East

30,00 Road bears E. & S. W.
40,00 Set a Limestone 18 in. long, 14 in. wide & 3 in. thick for Quarter section Corner
80,00 Set a Limestone 20 in. long, 16 in. wide & 3 in. thick, for Corner to secs. 9, 10, 15 & 16,

Township 3 N. Range 16 E 4th P.M. M.D.

Surface gently rolling Soil 1st rate

East on a random line between sec. 10 & 15
Variation 12° 15' East

40,00 Set a stone for temporary quarter sec. Corner
79,60 Intersected the N & S. line 70 lks. South of Corner to sec. 10, 11, 14 & 15 from which Corner Drawn

West on a true line between sec. 10 & 15
Variation 12° 45' E.

39,80 Set a Limestone, 15 in. long, 14 in. wide & 3 in. thick, for Quarter sec. Corner
79,60 The corner to sections 9, 10, 15 & 16.
Surface gently rolling Soil, 2nd rate

North between sections 9 & 10,
Variation 13° East

40,00 Set a Limestone, 16 in. long, 14 in. wide & 3 in. thick, for Quater sec. Corner
80,00 Set a Limestone, 20 in. long, 15 in. wide, & 3 in.

Township 3 N. Range 1 E. 6th P.M.

thick, for Corner to sections 3.4.9.& 10
Surface rolling - Soil 3rd rate

East on a random line sections 3 & 10,
Variation 12° 30' East

40.00 Set a Stone for temporary quarter sec. Corner
46.50 Creek 50 lks. wide - Course S. E.
79.50 Intersected N. & S. line 65 lks. South of Corner to secs. 2. 3. 10 & 11, from which Cor. Som. West, on a true line between secs 3 & 10,
Variation 12° 38' East
39.55 Set a Limestone 20 in. long, 11 in. wide & 2½ in. thick, for quarter sec. Corner
79.50 The Corner to secs. 3.4.9.& 10
Surface level - Soil 1st rate

North, on a random line between secs 3 & 4
Variation 13° 30' East
40.00 Set a stone for temporary quarter sec. Corner
44.00 Enter timber bears N. & S. E.

Township 3 N. Range 1 E. 6th P.M.

45.00 A Creek 8 lks. wide Course S. E.
47.00 Leave timber bears N. W. & S. E.
79.30 Intersected the North Boundary 90 lks. East of Corner to secs 3 & 4 from which Cor. Sun South, on a true line between secs 3 & 4,
Variation 14° 9' East
39.30 Set a Limestone, 15 in. long, 12 in. wide & 3 in. thick, for quarter section Corner
79.30 The Corner to secs 3.4.9.& 10
Surface rolling - Soil 2nd rate,
Timber Elm, and Cottonwood,
July 19th 1857

North, between sections 32 and 33
Variation 12° 30' East
40.00 Set a Sandstone, 15 in. long, 12 in. wide, & 4 in. thick, for quarter section Corner
80.00 Set a Sandstone 16 in. long, 12 in. wide, & 5 in. thick, for Corner to secs 28.29.32.& 33
Surface level - Soil 1st rate

Township 3 N. Range 1 E. 6th P.M.

East on a random line between sec. 28 & 33.
Variation 12° 15' East

40.00 Set a stone for temporary quarter sec. Corner
58.00 Entered timber bears N.E. & S.W.
70.00 Ravine bears N.E. & S.W.
71.00 Leave timber bears N.E. & S.W.
79.74 Intersected the N. & S. line 13 lks. South of the corner to secs. 27, 28, 33 & 34. from which corner I run West on a true line between secs. 28 & 33
Variation 12° 17' East
39.87 Set a sandstone, 15 in. long, 12 in. wide & 3 in. thick, for quarter sec. corner.
79.74 The corner to sections 28, 29, 32 & 33
Surface rolling - soil 1st rate
Timber Elm, & Cottonwood.

North between sections 28 & 29.
Variation 12° 45' East
40.00 set a limestone 18 in. long, 14 in. wide, & 3 in. thick

Township 3 N. Range 1 E. 6th P.M.

for quarter section corner
80.00 Sandstone 18 in. long, 12 in. wide, & 3 in. thick for corner to secs. 20, 21, 28 & 29.
Surface rolling soil 1st rate.

East on a random line between secs. 21 & 28.
Variation 12° 15' East

40.00 Set a stone for temporary quarter sec. Corner
80.12 Intersected the N. & S. line 6 lks. S. of corner to secs. 21, 22, 27 & 28, from which I run West, on a true line between secs. 21 & 28.
Variation 12° 17' East
40.06 Set a sandstone 20 in. long, 8 in. wide, & 4 in. thick, for quarter section corner.
80.12 The corner to secs. 20, 21, 28 & 29.
Surface rolling - soil 3rd rate

North between sections 20 & 21.
Variation 12° 45' East
38.90 Set a sandstone 16 in. long, 14 in. wide & 3 in.

Township 3 N. Range 1 E. 6th P.M.

thick, (on Right Bank of Little Blue Course E.)
for a witness Corner.

41.00 Left bank & entered timber bears E. & W.

43.00 Leave timber bears E. & W.

80.00 Set a Sandstone 18 in. long, 14 in. wide & 3 in
thick, for Corner to sec. 16, 17, 20 & 21.
Surface South ½ level, N½ rolling
Soil 1st rate.
Timber Cottonwood & Elm.

East on a random line between sec. 16 & 21.
Variation 12° 15' East

40.00 Set a stone for temporary quarter sec. Corner

73.00 Entered timber bears N.W. & S.E.

76.50 Sand Creek 50 lks. wide course S.E.

77.30 Leave timber bears N.W. & S.E.

80.20 Intersected N. & S. line, 20 lks. South of Corner to sec. 15, 16, 21 & 22, from which Corner
West on a true line between sec. 16 & 21,
Variation 12° 23' East

Township 3 N. Range 1 E. 6th P.M.

80.10 Set a Sandstone, 20 in. long, 15 in. wide, & 3 in
thick, for quarter sec. Corner

80.20 The Corner to sec. 16, 17, 20 & 21.
Surface level Soil 1st rate.
Timber cottonwood & Elm.

North between sections 16 & 17.
Variation 12° 45' East

18.00 Road bears E. & W.

34.00 Entered timber bears E. & W.

36.00 Sand Creek 100 lks. wide - course East.

36.00 Leave timber bears E. & W.

40.00 Set a Sandstone 18 in. long, 14 in. wide, & 3 in.
thick, for quarter sect. Corner

80.00 Set a Sandstone, 20 in. long, 14 in. wide & 3 in
thick, for Corner to sec. 8, 9, 16, & 17.
Surface level Soil 1st rate N.½. swampy.
Timber cottonwood.

East on a Random line between sec. 9 & 16

Township 3 N. Range 1 E. 6th Pr. Mdn

Variation 12° 15' East

40,00 Set a stone for temporary Quarter sec. Corner

80,50 Intersected the N. & S. line 30 lks. S of Corner to secs. 9, 10, 15 & 16 from which Cor. I run

West on a true line between secs. 9 & 16.

Variation 12° 28' East

40.25 Set a Sand Stone 16 in. Long, 8 in. wide & 4 in. thick, for Quarter sec. Corner.

80,50 The corner to secs. 8, 9, 16, & 17.

Surface rolling - Soil 2nd rate,

North, between sections 8 & 9.

Variation 13' East

40,00 Set a sandstone, 18 in. Long, 14 in. wide & 3 in. thick, for Quarter sec. Corner

80.00 Set a sandstone, 18 in. Long, 15 in. wide & 3 in. thick, for corner to secs. 4, 5, 8 & 9.

Surface rolling - Soil 2nd rate,

East on a random line between secs. 4 & 9.

Township 3 N. Range 1. E. 6th Pr. Mdn

Variation 12° 15' East

40,00 Set a stone for temporary Quarter sec. Corner

80,08 Intersected N. & S. line 30 lks. South of Corner to secs. 3, 4, 9 & 10, from which Cor. I run

West on a true line between secs. 4 & 9.

Variation 12° 28' East

40,04 Set a limestone, 14 in. Long, 12 in. wide & 3 in thick, for Quarter sec. Corner

80,08 The corner to secs. 4, 5, 8, & 9.

Surface rolling - Soil 2nd rate

North on a random line between secs. 4 & 5.

Variation 13° 30' East

40,00 Set a stone for temporary Quarter sec. Corner

78.80 Intersected the North Boundary 128 lks East of ~~of~~ Cor. to secs. 4 & 5, from which Cor. I run,

South on a true line between secs. 4 & 5

Variation 14° 28' East

38.80 Set a limestone, 16 in. Long, 12 in. wide & 3.

Township 3 N. Range 1 E. C^n P. M.

in thick for Quarter section Corner

78.80 The Corner to sec^s 4. 5. 8 & 9.

Surface rolling Soil 2nd rate

July 20th 1857

North between sections 31 & 32

Variation 12° 30' East

40.00 Set a Sandstone 18 in long 14 in wide & 3 in thick for Quarter sec Corner

80.00 Set a Sandstone 20 in long 16 in wide & 3 in thick for Corner to sec^s 29. 30. 31. 32

Surface rolling — Soil 1st rate

East on a random line between sec^s 29 & 32

Variation 12° 15' East

30.00 Ravine bears N. & S

40.00 Set a Stone for temporary Quarter sec Corner

80.06 Intersected N. & S. line 30 lks South of Corner to sec^s 28. 29. 32 & 33 from which Corner Run

West on a true line between sec^s ~~30 & 31~~ 29 & 32

Township 3 N. Range 1 E. C^n P^l M^d

Variation 12° 38' East

40.03 Set a Sandstone 16 in long 13 in wide & 3 in thick for Quarter sec Corner

80.06 The Corner to sec^s 29. 30. 31. & 32

Surface rolling — Soil 1st rate

West on a random line between sec^s 30 & 31

Variation 12° 30' East

40.00 Set a Stone for temporary Quarter sec Corner

80.80 Intersected the West Boundary 40 lks South of Corner to sec^s 30 & 31, from which Corner Run

East on a true line between sec 30 & 31.

Variation 12° 13' East

40.80 Set Sandstone 20 in long 16 in wide & 3 in thick for Quarter sec Corner

The Corner to sec^s 29. 30. 31. & 32.

Surface rolling Soil 2nd rate

North between sections 29 & 30.

Variation 12° 45' East

Township 3 N. Range 1 E. 6th P.M.

40.00 Set a Sandstone in long in wide & in thick, for Quarter sec Corner

78.50 Entered scattering timber bears E. & W

80.00 Set a Sandstone 22 in long 14 in wide & 3 in thick for Corner to secs. 19.20.29.&30 from which a

Burr Oak 30 in. dia bears S 12½ E. 36 lks dist

Burr Oak 12 in dia bears N 15 E. 36 lks. dist

No other Trees convenient to mark,

Surface rolling soil 1st Rate.

Timber. Oak.

East on a random line between sec 20 & 29

Variation 12°30' East

1.00 Leave Timber bears S. W. & N. E

37.00 Entered Timber, bears N. & S

38.50 Ravine, course W.

38.60 Leave Timber, bears N. & S

80.20 Intersected N. & S line 39 lks N of Corner to secs. ~~19.20.29 & 30~~ 20.21.28 & 29, from which Corner Run

Township 3 N. Range 1 E. 6th P.M.

West on a true line between secs 20 & 29

Variation 12° 47' East

40.10 Set a Sandstone 17 in long 10 in wide & 3 in thick for Quarter sec. Corner

80.20 The Corner to sec 19.20.29.&30

Surface rolling Soil 1st rate. Timber. Oak

West on a random line between sec 19 & 30

Variation 12° East

6.00 Leave timber bears. N. W. & S. E.

36.00 Enter timber bears N. & S.

40.00 Set a Stone for temporary Quarter sec Corner

42.00 Leave timber bears N. & S

59.00 Road bears. S. W. & N. E.

80.70 Intersected the West Boundary of Township 7 lks North of Corner to sec 19. & 30 from which Run East on a true line between sec 19 & 30

Variation 12° 17' East

40.70 Set Sandstone 18 in long 16 in wide & 3 in thick for Quarter sec Corner from which a

Township 3 N, Range 1, E 6th P.M.

Burr Oak 8 in dia bears S 70 15' W. 11 lk, dis

Burr Oak 20 in dia bears N 31. E. 40. lks, dis

80,70 The corner to secs. 19. 20. 29 & 30

Surface rolling Soil 1st rate, Timber Oak.

North between sections 19 & 20

Variation 12° 15' East

19.50 Right bank of Little Blue Course East & leave timber bears E & W

23.50 Left Bank of little Blue

40,00 Set a limestone 16 in. long, 14 in. wide & 3 in. thick, for a quarter sec. Corner

77.00 Road bears E. & W.

80,00 Set a limestone, 20 in. long, 15 in. wide. & 3 in. thick, for Corner to secs 17. 18. 19. 20

Surface rolling Soil 1st rate, Timber Oak & Cottonwood

East on random line between secs. 17 & 20

Variation 12° 30' East

13,00 Road bears N.E & S.W.

Township 3 N Range 1, E, 6th P.M.

40.00 Set a Stone for temporary Quarter sec, Corner

80.30 Intersected N & S line 9 lks. S, of Corner to secs. 16. 17. 20. & 21 from which Corner I run

West on a true line between secs. 17. & 20

Variation 12° 34' East

40.15 Set a Sandstone, 18 in long, 12 in wide, & 3 in thick, for Quarter sec Corner,

80,20 The Corner to secs. 17. 18. 19. & 20

Surface rolling, Soil 2nd rate

West on a random line between sec 18 & 19

Variation 12° 15' East

11.00 Road bears, N.W. & S.E.

40.00 Set a Stone for temporary Quarter sec Corner

80.50 Intersected the West Boundary of the Township 30 lks North of Corner to sec 17 & 20 from which Corner I run

East on a True line between sec 17. 20

Variation 12° 28' East

40.50 Set a Sandstone 17 in long, 12 in wide &

Township 3 N. Range 1, E. 6th P. M.

3 in thick for Quarter sec Corner

80.50 The Corner to sec 17. 18. 19 & 20

Surface gentley rolling Soil 2nd rate

July 21st 1857,

North between sec 17 & 18,

Variation 12° 45' East

40.00 Set a Sandstone 16 in long, 12 in wide & 3 in thick for Quarter sec Corner

44.00 Entered timber bears N. W. & S. E,

47.00 Sand Creek 80 lks wide. Course. S. E, and Leave timber. bears. N. W. & S. E.

80.00 Set a Sandstone 18 in long, 14 in wide & 4 in thick for Corner to secs 7. 8. 17. & 18

Surface rolling Soil 2nd rate,

Timber, Cottonwood,

East on a random line between sec 8 & 17

Variation 12° 30' East

38.00 Spring branch 10 lks wide, course South

Township 3 N. Range 1 E. 6th P. M.

40.00 Set a Stone for Temporary Quarter sec Corner

80.18 Intersected the N. & S line 30 lks. S. of Corner to secs 8. 9. 16. & 17, from which Corner I run

West on a true lin between sec 8 & 17

Variation 12° 43' East

40.09 Set a Sandstone 18 in long, 12 in wide & 3 in thick, for Quarter sec Corner

80.18 The Corner to sections 7. 8. 17. & 18

Surface, gentley rolling, Soil 1st rate

West on a random line between sec 7 & 18

Variation 12° 30' East

40.00 Set a Stone for temporary Quarter sec, Corner

45.00 Entered, timber, bears. N. W. & S. E,

49.00 Sandy Creek. 50 lks wide, Course. S. E

51.00 Leave timber, bears N. W. & S. E,

80.30 Intersected the West Boundary of the Township 50 lks North of Corner to sec 7 & 18 from which Corner, I run

East on a true line between sec 7 & 18

36

Township 3 N. Range 1, E. 6th P.M.

Variation 12° 48' East

40,30 Set a Sandstone, 16 in long, 12 in Wide, & 3 in thick, for Quarter sec. Corner

80,30 The Corner to secs. 7. 8. 17. 18.

Surface rolling Soil 1st rate,

Timber, Oak, Elm, and, Cottonwood,

North between sec 7. & 8.

Variation 13° East,

40.00 Set a Sandstone 16 in, long, 14 in, Wide & 3 in thick for Quarter sec Corner,

80.00 Set, a, Sandstone, 20, in long, 14, in Wide & 3 in thick for Corner to secs. 5. 6. 7. 8.

Surface, gently rolling, Soil 2nd rate,

East on a random line between sec 5 & 8,

Variation 12° 30' East,

40.00 Set, a Stake for temporary Quarter, sec, Corner

80.28 Intersected the N & S line 80 links S of Corner to secs. 4, 5, 8 & 9 from which Corner Trun

37

Township 3 N, Range 1 E, 6th P.M.

West, on, a true line, between sec, 5 & 8,

Variation 13° 04' East

40,14. Set a Sandstone, 16 in long, 14 in Wide & 3 in thick for Quarter sec Corner

80.28 The Corner to sec. 5. 6, 7 & 8,

Surface rolling, Soil. 3rd rate,

West on a random, line, between sec 6 & 7,

Variation 12° 45' East

40,00 Set, a, Stone, for, temporary Quarter, sec, Corner

80,60 Intersected the West Boundary of Township 50. links North of Corner to secs. 6 & 7. from which Corner Trun

East, on, a, true line, between sec 6 & 7,

Variation 13° 07' East

40,60 Set a Sandstone 18 in long 13 in Wide & 3 in thick for Quarter sec, Corner

80 60 The Corner to secs. 5. 6. 7. & 8

Surface rolling, Soil, 3rd rate

Township 3 N. Range 1, E 6th P.M.

North on a random line between sec 5 & 6,
Variation 13° 30' East

40.00 Set a Stone for temporary Quarter sec, Corner

79.60 Intersected the North Boundary of Township
138 lks East of Corner to sec. 5 & 6,
from, which Corner, I run
South on a true line between sec 5 & 6
Variation 14° 28' East

39.60 Set a Sandstone 18 in long 18 in Wide & 3 in
thick for Quarter sec, Corner

79.60 The Corner to sec. 5, 6, 7 & 8
Surface Rolling Soil 3rd rate
July 22nd 1857,

General Description

The quality of the Land in this Township avarages from 1st to 2nd rate, There is a small portion of it Bottom Land extend along both sides of Little Blue river which runs Easterly through the Township.

Timber not abundant Consisting mostly of Elm & Cottonwood Limestone of an inferior quality found in various portions of Township,

List of Names

A list of the names of the individuals employed to assist in running, measuring & marking the lines and corners described in the foregoing field notes of Township No. 3 North of the base line of Range No. 1 East of the 6th Principal Meridian, showing the respective capacities in which they acted.

George M. Tilford,	Compassman.
Robert Mack	Chainman,
Zacharius Kohlen,	"
Samuel Campbell,	Flagman,
Frederick Kuhn,	Marker,

Platted 18th

Field Notes
of the survey of the subdivisional lines of Township No. 4 North of Range 1 East of the 6th Principal Meridian in the Territory of Nebraska by

T. H. Doyle, Dep. Sur.
Under his Contract No. 204, bearing date June 27th 1857.

Subdivision Commenced July 24th 1857.
Subdivision Completed July 31st 1857.

Names and duties of asistants

George M. Tilford Compassman
Robert Mack Chainman
Zacharius Kohler "
Samuel Campbell Flagman
Frederick Kuhn Marker

Township 4 N. Range 1 East

6	32	5	24	4	18	3	13	2	7	1
32		31		23		18		12		6
7	31	8	23	9	17	10	12	11	6	12
30		30		22		17		11		5
18	29	17	22	16	16	15	11	14	5	13
29		28		21		16		10		4
19	28	20	21	21	15	22	10	23	4	24
27		26		20		15		9		3
30	26	29	20	28	14	27	9	26	3	25
25		25		19		13		8		2
31	24	32	19	33	13	34	8	35	2	36

Field Notes of the Subdivision Lines in Township No. 4 N. Range 1 E. 6th Principal Meridian N. T.

To determine the proper adjustment of my Compass for subdividing this Township I Commence at the Comr of Townships 3 & 4 North, of Ranges 1 & 2 East and run

North on a blank line along the East boundary of section 36.

Variation 12° 30' East

37.72 To a point 30 lks. East of Quarter sec. Corner,

79.88 To a point 68 lks. East of Corner to sections 25 & 36.

To reduce this line or run parallel thereto my Compass must be adjusted to a Variation 15° East.

Subdivision Commenced July 24th 1857

From the Corner to sections, 1, 2, 35, & 36. on the South Boundary of the Township, I run

Township 4 N. Range 1 E. 6th P.M. Mdn

North, between secs. 35 and 36.
Variation 13° East

40,00 Set a sandstone 16 in. long, 14 in. wide & 3 in thick, for a quarter sec. Corner

80,00 Set a Sandstone 18 in. long, 14 in. wide & 3 in thick, for Corner to secs. 25, 26, 35 & 36.

Surface level - Soil 1st rate.

East on a random line between 25 & 36.
Variation 12° 30' E

40,00 Set a stake for temporary quarter sec. Cor.

60,00 Branch 5 lks. wide course South

79,90 Intersected East Boundary, 28 lks. North of Corner to secs. 25 & 36, from which Corner Sun

West, on a true line between secs. 25 & 36.
Variation 12° 15' East

39,95 Set a Sandstone 16 in. long, 14 in. wide & 3 in thick, for quarter sec. Corner

79,90 The Corner to secs. 25, 26, 35 & 36

Township 4 N. Range 1 E. 6th P.M. Mdn

Surface level soil 1st rate

North, between sections 25 & 26.
Variation 13° East.

40,00 Set a Boulder 16 in. long, 14 in. wide & 5 in. thick, for quarter sec. Corner.

80,00 Set a sandstone 14 in. long, 12 in. wide & 3 in. thick, for Corner to secs. 23, 24, 25, 26.

Surface level - Soil 1st rate.

East on a random line between secs. 24 & 25.
Variation 12° 15' E.

40,00 Set a stone for temporary quarter sec. Corner

47,02 Branch, 5 lks. wide - runs South.

80,14 Intersected East Boundary, 7 lks. N. of Corner to secs. 24 & 25. from which Corner Sun.

West on a true line between secs. 24 & 25.
Variation 12° 13' East

40,07 Set a Boulder, 14 in. long, 12 in. wide, & 5 in.

Township 4 N. Range 1 E. 6th P.M.

thick, for a quarter sec. Corner

80.14 The corner to secs. 23, 24, 25, & 26.

Surface level - Soil 1st rate

North, between sections 23 & 24.

Variation 13° East

40.00 Set a Boulder 16 in. long, 14 in. wide, & 6 in. thick for quarter sec. Corner.

80.00 Set a sandstone 16 in. long, 14 in. wide, 5 in thick, for Corner to secs. 13, 14, 23, & 24.

Surface level - Soil 1st rate.

East on a random between secs. 13 & 24

Variation 12° 15' East

40.00 Set a stone for temporary quarter sec. Corner

80.40 Intersected East Boundary, 7 lks. North of Corner, to secs. 13 & 24, from which Cor. Sun

West, on a true line between secs. 13 & 24.

Variation 12° 15' East

40.20 Set a boulder 14 in. long, 12 in. wide, & 5 in.

Township 4 N. Range 1 E. 6th P.M.

thick, for quarter sec. Corner

80.40 The Corner to secs. 13, 14, 23 & 24.

Surface level - Soil 1st rate.

North, between sections 13 & 14.

Variation 12° 45' East

40.00 Set a boulder 15 in. long, 12 in. wide, & 5 in. thick, for quarter sec. Corner

80.00 Set a sandstone 16 in. long, 14 in. wide & 3 in. thick, for Corner to secs. 11, 12, 13, & 14

Surface level - Soil 1st rate.

East on a random line between secs. 12 & 13.

Variation 12° 15' East

40.00 Set a stone for temporary quarter sec. Corner

80.25 Intersected East Boundary, 14 lks. North of corner to secs. 12 & 13, from which Corner Sun

West on a true line between secs. 12 & 13.

Variation 12° 09' E.

Township 4 N. Range 1 E. 6th P. M.

40,12 Set a Boulder 16 in. long, 12 in. wide, & 6 in. thick, for 2 quarter sec. Corner.

80,25 The Corner to secs. 11, 12, 13, & 14.

Surface level - Soil 1st rate.

North, between sections 11 & 12,

Variation 12° 45' E.

40,00 Set a Boulder 18 in. long, 13 in. wide & 6 in thick, for 2 quarter sec. Corner

80,00 Set a Sandstone 17 in. long, 14 in. wide & 3 in thick, for Corner to secs. 1, 2, 11, & 12

Surface gently rolling - Soil 1st rate

East on a random line between sec. 1 & 12

Variation 12° 15' East

40,00 Set a stone for temporary 2 quarter sec. Corner

80,60 Intersected East Boundary of Township 30 lks. North of corner to secs. 1 & 12 from which Corner 3 rem

West, on a true line between secs

Township 4 N. Range 1 E. 6th P. M.

1 & 12.

Variation 12° East

40,30 Set a Boulder, 18 in. long, 14 in. wide, & 6 in. thick, for 2 quarter sec. Corner

80,60 The Corner to secs. 1, 2, 11, & 12

Surface - gently rolling - Soil 1st rate

North between secs. 1 and 2,

Variation 12° 30' E.

40,00 Set a Boulder 16 in. long, 12 in. wide, & 6 in. thick, for a 2 quarter sec. Corner

40,20 Branch 10 lks. wide Course S.E.

77,04 Intersected 1st Standard Parallel 270 lks. West of Corner to secs. 1, 2, 35 & 36, at which point,

Set a 2 quartz rock, 16 in. long, 13 in. wide & 3 in thick, for Corner to secs. 1 & 2

Surface gently rolling - Soil 1st rate

July 24th 1857.

Township 4 N. Range 1 E. 6th P.M.

North between sections 34 & 35
Variation 13° East

40.00 Set a Boulder, 14 in. long, 12 in. wide & 5 in thick, for quarter sec. Corner.

80.00 Set a Sandstone, 18 in. long, 12 in. wide & 3 in. thick, for Corner to sec. 26, 27, 34 & 35

Surface gently rolling - Soil 1st rate.

East on a random line between sec. 26 & 35.
Variation 12° 15' East.

40.00 Set a Stone for temporary quarter sec. Corner

79.56 Intersected N. & S. line, 64 lks. S of Corner to sec. 23, 24, 35 & 36 from which Corner Sun

West on a true line between sec. 26 & 35.
Variation 12° 32' East

39.78 Set a Boulder 14 in. long, 10 in. wide & 8 in. thick for quarter sec. Corner

79.56 The Corner to sec. 26, 27, 34 & 35.

Surface gently rolling Soil 1st Rate.

Township 4 N. Range 1 E. 6th P.M.

North between sections 26 & 27.
Variation 13° 15' East

40.00 Set Boulder, 14 in. long, 10 in. wide, & 6 in. thick, for quarter section Corner

80.00 Set a Sandstone, 16 in. long, 12 in. wide, & 3 in thick, for Corner to sec. 22, 23, 26 & 27.

Surface gently rolling - Soil 1st rate

East on a random line between sec. 23 & 26.
Variation 12° 30' East

40.00 Set a stone for temporary quarter sec. Corner.

79.34 Intersected N. & S. line 13 lks. South of Corner to sec. 23, 24, 25 & 26 from which Corner Sun

West on a true line between sec. 23 & 26
Variation 12° 35' East.

37.67 Set a Quartz Stone, 18 in. long, 12 in. wide & 4 in. thick, for quarter sec. Corner

79.34 The Corner to sec. 22, 23, 26, & 27.

Surface level - Soil 1st rate

Township 4 N. Range 1 E. 6th P.M. Mdn

North between secs. 22, & 23.

Variation 13° 30' East.

40,00 Set a Boulder, 14 in. long, 12 in. wide, & 5 in. thick, for Quarter sec. Corner.

80,00 Set a Sandstone 16 in. long, 12 in. wide & 3 in. thick, for Corner to secs. 14, 15, 22 & 23.

Surface gently rolling - Soil 1st rate

East on a Random line between secs. 14 & 23.

Variation 12° 30' East

40.00 Set a stone for temporary Quarter sec. Cor.

79.66 Intersected N. & S. line 11 lks. North of Corner to secs. 13, 14, 23 & 24, from which Cor. Sum.

West on a true line between secs. 14 & 23.

Variation 12° 26' East

39.83 Set a Boulder 14 in. long, 14 in. wide & 8 in. thick, for Quarter sec. Corner

79.66 The Corner to secs. 14, 15, 22 & 23

Surface level - Soil 1st rate.

Township 4 N. Range 1 E. 6th P.M. Mdn

North between sections 14 & 15.

Variation 13° East.

40,00 Set Boulder, 16 in. long, 12 in. wide, & 5 in. thick, for Quarter sec. Corner

80,00 Set Sandstone 17 in. long, 13 in. wide, & 3 in. thick, for Corner to secs. 10, 11, 14 & 15.

Surface level - Soil 1st rate.

East, on a random line between secs. 11 & 14.

Variation 12° 30' East.

40,00 Set a Stone for temporary Quarter sec. Corner

80,30 Intersected N. & S. line 30 lks. North of Corner to secs. 11, 12, 13 & 14, from which Cor. Sum.

West, on a true line between secs. 11 & 14.

Variation 12° 17' East

40.15 Set Boulder 14 in. long, 10 in. wide & 8 in. thick for Quarter sec. Corner.

80,30 The corner to secs. 10, 11, 14 & 15

Surface gently rolling.

Soil 1st rate.

Township 4 N. Range 1. E. 6th P.M.

North. between sections 10 and 11

Variation 12° 30' East.

40,00 Set a Boulder 14 in. long, 8 in. wide, & 7 in. thick for 2 quarter sec. Corner.

80,00 Set Sandstone 16 in. long, 12 in. wide, & 4 in thick, for Corner to sect 2, 3, 10 & 11.

Surface gently rolling Soil 1st rate

East on a Random line between sect. 2 & 11

Variation 12° 30' East

40,00 Set a stone for temporary 2 quarter sec. Corner

80,04 Intersected N & S. line 16 lks. North of Corner to sect. 1, 2, 11 & 12, from which Corner I run West, on a true line between sect 2 & 11

Variation 12° 24' East

40,02 Set a Boulder, 14 in. long, 6 in. wide & 6 in. thick for 2 quarter section Corner

80,04 The Corner to sect. 2, 3, 10, & 11.

Surface gently rolling-

Soil 1st rate.

Township 4 N. Range 1. E. 6th P.M.

North between sections 2 & 3.

Variation 12° 30' East.

40,00 Set Boulder, 14 in. long, 7 in. wide, & 6 in. thick, for 2 quarter sec. Corner.

78,94 Intersected 1st Standard Parallel 280 lks. West of Corner to sect. 34 & 35, &

Set a Boulder, 14 in. long, 8 in. wide, & 6 in. thick for Corner to sect. 2 & 3.

Surface rolling- Soil 2nd rate.

July 25th 1857.

North, between sections 33 & 34.

Variation 13° East

40,00 Set Boulder 18 in. long 14 in. wide, & 3 in. thick, for 2 quarter sec. Corner

80,00 Set a Sandstone 16 in. long, 12 in. wide & 3 in. thick, for Corner to sect. 27, 28, 33 & 34.

Surface gently rolling- Soil 1st rate,

East, on a random line between sect. 27 & 34.

Township 4 N. Range 1 E. 6th P.M.

Variation 12° 30' East.

40.00 Set a stone for temporary quarter sec. Corner

79.98 Intersected N & S. line 30 lks. South of Corner to secs. 26, 27, 34, & 35, from which corner I run

West, on true line between sec. 27 & 34.

Variation 12° 43' East.

39.99 Set Boulder, 18 in. long, 12 in. wide, & 6 in. thick for quarter sec. Corner

79.98 The Corner to secs. 27, 28, 33, & 34.

Surface gently rolling Soil 1st rate

North, between sections 27 & 28

Variation 13° East.

40.00 Set a Boulder 18 in. long 14 in. wide & 6 in. thick, for quarter sec. Corner

80.00 Set a Sandstone 18 in. long, 12 in. wide & 3 in. thick, for Corner to secs. 21, 22, 27 & 28.

Surface gently rolling Soil 1st rate

Township 4 N. Range 1 E. 6th P.M.

East on a random line between secs. 22 & 27.

Variation 12° 30' E.

40.00 Set Stone for temporary quarter sec. Corner

79.52 Intersected N & S. line 25 lks. S. of Corner to secs. 22, 23, 26 & 27, from which Corner I run

West on a true line between secs. 22 & 27

Variation 12° 41' East.

39.76 Set a Boulder, 14 in. long, 12 in. wide, & 6 in. thick, for quarter sec. Corner.

79.52 The Corner to secs. 21, 22, 27, & 28.

Surface gently rolling Soil 1st rate.

North, between sections 21 & 22,

Variation 13° 15' East.

3.00 Branch 5 lks. wide Course S.W.

40.00 Set a Boulder 20 in. long, 14 in. wide, & 3 in. thick, for quarter sec. Corner

80.00 Set a Sandstone 18 in. long, 12 in. wide & 3 in. thick for Corner to secs. 15, 16, 21 & 22

Surface gently rolling Soil 1st rate

Township 4 N. Range 1 E. 6th P.M.

East, on a random line between sect. 15 & 22,
Variation 12° 30' East.

40.00 Set a Stone for temporary Quarter sec. Corner

79.62 Intersected N & S. line 4 lks. North of Corner to sect. 14, 15, 22 & 23, from which Corner I run West on a true line between sect. 15 & 22,
Variation 12° 29' East.

39.81 Set a Boulder 14 in. long, 10 in. wide, & 8 in. thick, for Quarter sec. Corner

79.62 The Corner to sect. 15, 16, 21 & 22
Surface gently rolling - Soil 1st rate

North, between sections 15 & 16,
Variation 13° 00' East

40.00 Set a Boulder 16 in. long, 12 in. wide, & 6 in. thick, for Quarter sec. Corner

50.00 Set a Sandstone, 15 in. long, 14 in. wide & 3 in. thick, for Corner to sect. 9, 10, 15 & 16,
Surface level - Soil 1st rate

Township 4 N. Range 1 E. 6th P.M.

East on a random line between sect. 10 & 15
Variation 12° 30' East.

40.00 Set a Stone for temporary Quarter sec. Corner,

79.98 Intersected N & S. line, 14 lks. North of Corner to sect. 10, 11, 14 & 15, from which Cor. I run West, on a true line between sect. 10 & 15.
Variation 12° 24' East

39.99 Set a Boulder, 14 in. long, 10 in. wide, & 8 in. thick, for Quarter sec. Corner,

79.98 The Corner to sect. 9, 10, 15 & 16,
Surface level - Soil 1st rate.

North, between sections 9 & 10,
Variation 12° 30' East.

40.00 Set a Boulder 11 in. long, 10 in. wide, & 6 in. thick for Quarter sec. Corner.

50.00 Set a Sandstone, 17 in. long, 15 in. wide, & 3 in. thick, for Corner to sect. 3, 4, 9 & 10.
Surface gently rolling - Soil 1st rate.

Township 4 N. Range 1 E. 6th P.M.

East on a random line between sec. 3 & 10.
Variation 12° 30' East.

40,00 Set stone for temporary Quarter sec. Corner
79,88 Intersected N & S. line 12 lks. N. of Corner to sec. 2, 3, 10 & 11. from which Cor. Chain West on a true line between sec. 3 & 10
Variation 12° 25' East
39,94 Set a Boulder, 13 in. long, 10 in. wide, & 6 ins thick, for Quarter sec. Corner
79,88 The Corner to sec. 3, 4, 9 & 10
Surface level - Soil 1st rate

North between sections 3 & 4.
Variation 12° 30' East
40,00 Set a Boulder, 14 in. long, 10 in. wide, & 8 in. thick for Quarter sec. Corner
79,08 Intersected 1st Standard Parallel 254 lks West of Corner to sec. 34 & 35, at a thick point.
Set a Boulder, 15 in. long, 12 in. wide, & 8 in thick for Corner to sec. 3 & 4

Township 4 N. Range 1 E. 6th P.M.

Surface gently rolling - Soil 1st rate.
July 28th 1857.

North between sections 32 and 33.
Variation 13° East
40,00 Set a Boulder, 20 in. long, 18 in. wide, & 8 in. thick, for Quarter sec. Corner
58,00 Little Sandy 50 lks. wide Course S.E.
80,00 Set a Sandstone 18 ins long, 12 in. wide & 3 in. thick, for Corner to sec. 28, 29, 32 & 33
Surface gently rolling - Soil 1st rate

East on a random line between sec. 28 & 33.
Variation 12° 30' East
40,00 Set a stone for temporary Quarter sec. Corner
53,00 Branch 10 lks. wide - course South.
79,94 Intersected N & S. line 75 lks. South of Corner to sec. 27, 28, 33 & 34. from which Cor. Chain West, on a true line between sec. 28 & 33.
Variation 13° 02' East
39,97 Set a Boulder, 14 in. long, 12 in. wide, & 8 in. thick

Township 4 N. Range 1 E. 6th P.M.

for Quarter sec. Corner.

79.94 The corner to secs. 28. 29. 32 & 33.

Surface gently rolling - Soil 1st rate

North. between sections 28 & 29.

Variation 13° East.

40.00 Set a Boulder 14 in. long, 10 in. wide & 6 in thick, for Quarter sec. Corner.

80.00 Set a Sandstone, 16 in. long, 12 in. wide & 3 in thick, for corner to secs. 20, 21, 28 & 29.

Surface gently rolling - Soil 1st rate

East on a random line between secs. 21 & 28.

Variation 13° East

40.00 Set a stone for temporary Quarter sec. Corner

77.00 Branch 3 lks. wide. Course S.W.

79.82 Intersected W & S. line, 7 lks. North of corner to secs. 21, 22, 27 & 28, from which Cor. Irun

West on a true line between secs. 21 & 28

Variation 12° 58' East

Township 4 N. Range 1 E. 6th P.M.

39.91 Set a Boulder, 12 in. long, 12 in. wide & 6 in thick, for Quarter sec. Corner.

79.82 The corner to secs. 20, 21, 28 & 29.

Surface gently rolling - Soil 1st rate

North. between sections 20 & 21.

Variation 13° 15' East.

40.00 Set a Boulder 14 in. long, 10 in. wide & 8 in. thick, for Quarter sec. Corner.

80.00 Set a Sandstone, 18 in. long, 14 in. wide & 3 in thick, for Corner to secs. 16, 17, 20 & 21.

Surface rolling - Soil 1st rate.

East on a random line between secs. 16 & 21.

Variation 13° East

40.00 Set a stone for temporary Quarter sec. Corner

79.26 Intersected N. & S. line, 30 lks. N. of corner to secs. 15, 16, 21, & 22, from which Cor. Irun

West on a true line between secs. 16 & 21.

Variation 12° 47' East

Township 4 N. Range 1 E. 6th P.M.

39.63 Set a Sandstone, 14 in. long, 8 in. wide & 6 in. thick, for Quarter sec. Corner.

79.26 The Corner to sec. 16, 17, 20 & 21.

Surface rolling - Soil 2nd rate.

North, between sections 16 & 17.

Variation 13° 15' East

40.00 Set a Boulder, 13 in. long, 10 in. wide & 6 in. thick, for Quarter sec. Corner.

80.00 Set a Sandstone, 18 in. long, 13 in. wide, & 3 in. thick, for Corner to sec. 8, 9, 16, & 17

Surface level - Soil, 1st rate.

East on a random line between sec. 9 & 16

Variation 13° East

40.00 Set a Stone for temporary Quarter sec. Corner.

79.30 Intersected N & S. line 20 lks. North of Corner to sec. 9, 10, 15 & 16, from which cor. I am West, on a true line between sec. 9 & 16

Variation 12° 52' East

Township 4 N. Range 1 E. 6th P.M.

39.65 Set a Sandstone, 15 in. long, 12 in. wide, & 3 in. thick, for Quarter sec. Corner.

79.30 The Corner to sec. 8, 9, 16 & 17.

Surface level - Soil 1st rate.

North between sections 8 & 9.

Variation 12° 30' East

40.00 Set a Sandstone, 16 in. long, 12 in. wide, & 3 in. thick, for Quarter sec. Corner

80.00 Set a Sandstone 18 in. long, 16 in. wide & 3 in. thick, for Corner to sec. 4, 5, 8, & 9.

Surface gently rolling - Soil 1st rate.

East, on a random line between sec. 4 & 9.

Variation 13° East.

40.00 Set a stone for temporary Quarter sec. Cor.

79.40 Intersected N & S. line, 12 lks. North of Corner to sec. 3, 4, 9, & 10, from which cor. I run West on a true line between sec. 4 & 9

Variation 12° 55' East

Township 4 N. Range 1 E. 6th P.M.

39.70 Set a Sandstone, 16in. Long, 14in. wide, & 3in. thick, for Quarter sec. Corner

79.40 The Corner to secs. 4, 5, 8, 9.

Surface gently rolling - Soil 1st rate

North, between sections 4 & 5,

Variation 12° 30' East.

40.00 Set a Sandstone, 14in. Long, 12in. wide, & 3in. thick, for Quarter Sec. Corner.

78.96 Intersected the 1st Standard Parallel 196 lks West of Corner to secs. 32 & 33.

Set a Sandstone, 18in. Long, 14in. wide & 3in. thick, for Corner to secs. 4 & 5.

Surface gently rolling - Soil 1st rate.

July 29th 1857.

North, between sections 31 & 32,

Variation 13° East.

40.00 Set a Sandstone 18in. Long, 12in. wide, & 3in. thick for Quarter sec. Corner

80.00 Set a Sandstone 18in. long, 12in. wide & 3in

Township 4 N. Range 1 E. 6th P.M.

thick, for Corner to secs. 29, 30, 31 & 32

Surface gently rolling - Soil 1st rate.

East on a random line between secs. 29 & 32

Variation 12° 45' East.

40.00 Set a Stone for temporary Quarter sec. Corner

75.50 ~~Little Sandy Creek 40 lks. wide Course S.E.~~

79.24 ~~Intersected~~ N & S. line 38 lks. North of Corner to secs. 28, 29, 32, & 33, from which Corner

West on a true line between secs. 29 & 32,

Variation 12° 29' East.

39.97 Set a Sandstone, 16in. long, 14in. wide, & 3in. thick for Quarter sec. Corner.

79.94 The Corner to secs. 29, 30, 31 & 32

Surface gently rolling - Soil 1st rate.

West on a random line between secs. 30 & 31.

Variation 12° 45' East

40.00 Set a Stone for temporary Quarter sec. Corner

79.64 Intersected West Boundary 113 lks. North

Township 4 N. Range 1 E. 6th P.M.

of Comer to secs. 30 & 31, from which cor. Sam
East on a true line between secs. 30 & 31.
Variation 13° 34' E.

39.64 Set a Sandstone, 16 in. long, 13 in. wide, & 3 in.
thick, for quarter sec. Comer.

79.64 The Comer to secs. 29, 30, 31 & 32.
Surface gently rolling. Soil 1st rate.

North, between sections 29 & 30.
Variation 13° East.

40.00 Set a Sandstone, 16 in. long, 12 in. wide, & 3 in.
thick, for quarter sec. Comer.

74.50 Little Sandy Creek 40 lks. wide - Course S.E.

80.00 Set a Sandstone, 18 in. long, 12 in. wide, & 3 in.
thick for Comer to secs. 19, 20, 29 & 30.
Surface rolling - Soil 2nd & 3rd rate.

East on a random line between secs. 20 & 29.
Variation 12° 30' East

40.00 Set a Stone for temporary quarter sec. Cor.

Township 4 N. Range 1 E. 6th P.M.

79.74 Intersected N. & S. line, 16 lks. S. of Comer
to secs. 20, 21, 28 & 29, from which Comer Sam
West, on a true line between secs. 20 & 29.
Variation 12° 37' E.

39.87 Set a Sandstone, 17 in. long, 12 in. wide, & 3 in.
thick, for quarter sec. Comer

79.74 The Comer to secs. 19, 20, 29 & 30.
Surface gently rolling. Soil 1st rate

West on a random line between secs. 19 & 30
Variation 13° 30' East.

8.00 Little Sandy Creek 30 lks. wide Course S.E.

40.00 Set a Stone for temporary quarter sec. Comer

79.60 Intersected West Boundary 16 lks. North
of Comer to secs. 19 & 30. from which Cor. Sam
East on a true line between secs. 19 & 30.
Variation 13° 37' East

39.60 Set Sandstone 16 in. long, 14 in. wide, & 3 in.
thick, for quarter sec. Comer

79.60 The Comer to secs. 19, 20, 29 & 30.

Township 4 N. Range 1 E. 6th P. M.

Surface gently rolling - Soil 1st rate.

North, between sections 19 and 20.
Variation 13° East

40,00 Set a Sandstone, 14 in. long, 14 in. wide, & 3 in. thick, for quarter sec. Corner.

80,00 Set a Sandstone, 20 in. long, 13 in. wide, & 3 in. thick, for corner to secs. 17, 18, 19, & 20

Surface gently rolling Soil 1st rate.

East, on a random line between secs. 17 & 20.
Variation 12° 30' East

40,00 Set a Stone for temporary quarter sec. corner

77,50 Intersected N. & S. line 6 lks. South of corner to secs. 16, 17, 20 & 21, from which corner I run

West on a true line between secs. 17 & 20.
Variation 12° 32' East

39,75 Set a Sandstone, 14 in. long, 14 in. wide & 3 in. thick, for quarter sec. corner

77,50 The corner to secs. 17, 18, 19 & 20.

Township 4 N. Range 1 E. 6th P. M.

Surface level - Soil 1st rate.

West on a random line between secs. 18 & 19.
Variation 13° 30' East

40,00 Set a Stone for temporary quarter sec. corner

48,00 Little Sandy Creek 30 lks. wide course S. E.

79,50 Intersected West Boundary 17 lks. South of corner to secs. 18 & 19, from which corner I run

East on a true line between secs. 18 & 19
Variation 13° 23' East

39,50 Set a Sandstone, 16 in. long 14 in. wide & 3 in. thick, for quarter sec. corner

79,50 The corner to secs. 17, 18, 19 & 20.

Land gently rolling Soil 1st rate.

North between sections 17 & 18.
Variation 13° 15' East

40,00 Set a Sandstone, 16 in. long, 12 in. wide, & 3 in. thick, for quarter sec. corner.

80,00 Set a Sandstone, 16 in. long, 14 in. wide & 3 in

Township 4 N. Range 1 E. 6th P. M.

thick, for corner to sec. 7, 8, 17, & 18.
Surface level Soil 1st rate.

East on a random line between sec. 8 & 17.
Variation 12° 30' East.

40,00 Set a Stone for temporary quarter sec. Corner
79,40 Intersected N. & S. line 18 lks. North of Corner to sec. 8, 9, 16 & 17, from which cor. I run
West, on a true line between sec. 8 & 17.
Variation 12° 22' East

39,70 Set a Sandstone, 14 in. long 12 in. wide & 3 in. thick for quarter sec. Corner.
79,40 The Corner to sec. 7, 8, 17 & 18.
Surface level - Soil 1st rate

July 30th 1857.

West on a random line between sec. 7 & 18.
Variation 13° 30' East.

40,00 Set a Stone, for temporary quarter sec. Corner
78,67 Intersected West Boundary 14 lks. South of Corner to sec. 7 & 18, from which cor. I run

Township 4 N. Range 1 E. 6th P. M.

East on a true line between sec. 7 & 18
Variation 13° 24' East

38,67 Set a Sandstone 16 in. long, 12 in. wide & 3 in. thick, for quarter section Corner
78,67 The Corner to sec. 7, 8, 17, & 18.
Surface level - Soil 1st rate

North, between sections 7 and 8
Variation 12° 45' East

40,00 Set a Sandstone, 14 in. long 12 in. wide & 3 in. thick, for quarter sec. Corner.
80,00 Set a Sandstone 18 in. long, 12 in. wide & 3 in. thick, for Corner to sec. 5, 6, 7 & 8.
Surface level Soil 1st rate.

East on a random line between sec. 5 & 8.
Variation 12° 30' East

40,00 Set a stone for temporary quarter sec. Co
79,42 Intersected N. & S. line 27 lks. North of Corner to sec. 4, 5, 8 & 9, from which cor. I run

Township 4 N. Range 1 E. 6th P. M.

West on a true line between sec. 5 & 8,
Variation 12° 18' East.

39.71 Set a Sandstone 15 in. long, 12 in. wide & 3 in. thick, for 2 quarter sec. corner.

79.42 The corner to sec. 5, 6, 7 & 8.

Surface level Soil 1st rate.

West on a random line between sec. 6 & 7.
Variation 13° 30' East

40.00 Set a Stone for temporary 2 quarter sec. Corner

78.80 Intersected West Boundary, at corner to secs 6 & 7, from which corner I run East on a true line between secs 6 & 7.
Variation 13° 30' East

38.80 Set a Sandstone, 16 in. long 14 in. wide & 3 in. thick, for 2 quarter sec. corner

78.80 The corner to secs 5, 6, 7, & 8

Surface level - Soil 1st rate

North, between sections 6 & 5

Township 4 N. Range 1 E. 6th P. M.

Variation 13° East.

40.00 Set a Sandstone, 16 in. long, 12 in. wide & 3 in. thick, for 2 quarter section Corner

78.88 Intersected 1st Standard Parallel 147 lks. West of corner to secs. 31 & 32.

Set a Sandstone, 18 in. long, 14 in. wide & 3 in. thick, for corner to secs. 5 & 6.

Surface level - Soil 1st rate.

July 31st 1857.

General Description

The Quality of the Land in this Township is averaged as 1st and 2nd rate. It Cannot be valued only for stock grazing as the Township is destitute of timber A Considerable amount of Limestone and some Sandstone but inferior in Quality.

List of Names

A List of the Names of the individuals employed to assist in running, measuring, or marking the lines and Corners described in the foregoing field Notes of Township No. 4, North of the Base line of Range No. 1 East of the sixth Principal Meridian in Nebraska Territory showing the respective Capacities in which they acted.

George M. Tilford, Compassman
Robert Mack, Chainman
Zacharias Koklen, "
Samuel Campbell, Flagman
Frederick Kuhn Marker

General Land Office • Original Field Notes

Book Number

29

The images in this file are photographs of the notes of the original surveys of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The original surveys in Nebraska began in the mid 1850's and were completed in the mid 1880's. The Nebraska office of the Surveyor General was closed June 30, 1886.