General Land Office • Original Field Notes

Book Number

772

W.W. Alt - 5th Standard Parallel through T 47 N

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.

4—679.

FIELD NOTES

OF THE SURVEY OF THE

5th Standard Parallel North
through
Range 47 West

Of the 6th Principal Meridian,
State of Nebraska

AS SURVEYED BY

Willand W. Alt, United States ~~Deputy~~ Surveyor,

Under his Contract ~~No.~~ _____, dated May 26, 1890

Survey commenced Oct. 15, 1890

Survey completed November 27, 1890

6—151

NAMES AND DUTIES OF ASSISTANTS.

Joseph B. Koon, Chainman

Jim A. Winser, " "

Harry Covalt, " "

Earl J. Martin, Moundman.

Herbert Campbell, Flagman

6—151

INDEX DIAGRAM.

5. Bdry. or 5th Standard Parallel.

Township 21 N, Range 47 W

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

3 3 3 2 2 2 Random 2

4 5 6 7 8 8

True line

Meanders Page

6—151

PRELIMINARY OATHS OF ASSISTANTS.

We, ... and .....
do solemnly swear that we will well and faithfully execute the duties of chainmen; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distances to all notable objects, and the true lengths of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of
.....

..... *Chainman.*

..... *Chainman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

.....

.....

We, ... and .....
do solemnly swear that we will well and truly perform the duties of moundmen in the establishment of corners, according to the instructions given us, to the best of our skill and ability, in the survey of
.....

..... *Moundman.*

..... *Moundman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

.....

.....

We, ... and .....
do solemnly swear that we will well and truly perform the duties of axmen in the establishment of corners and other duties, according to instructions given us, to the best of our skill and ability, in the survey of
.....

..... *Axman.*

..... *Axman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

.....

.....

I, ..., do solemnly swear that I will well and truly perform the duties of flagman according to instructions given me, to the best of my skill and ability, in the survey of .....
.....

..... *Flagman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

.....

.....

Re-Survey of 5th Standard Parallel N. R. 47 W. of 6th P. M. Nebraska

Chains

Survey commenced Oct. 15. 1900. and executed with a W. and L. E. Gurley Transit #12. the horizontal limb is provided with two double verniers placed opposite to each other, reading to single minutes of arc. I examine and place instrument in perfect adjustment. I also compare and adjust my chains to "Standard Tape".

The location of the Standard Cor. of T. 21 N. R. 46 and 47 W. not being known and old settlers stating that the original Cor. of Secs. 19, 24, 25 and 30. on the E. bdry of T. 21 N. R. 47 W. had been found and was recognized as an original Government Corner. In order to avoid delay in commencing these surveys at any camp which is located in the N.E. ¼ of the N.W. ¼ Sec. 26. Latitude 41° 45' N. longitude 102° 31' W. I observe Polaris from a tack in stake firmly driven at 5.54 local mean time on Oct. 14. 1900. being 6.47 by my watch which is Central Standard time and create the line thus determined by a tack in stake 3.09 chs. W. At 8. A. M. on Oct. 15th I lay off azimuth of Polaris 1°39' to the W. and mark the true Meridian thus determined by a tack in stake firmly driven 3.09 chs. W. the exact location of these points are recorded in field notes of the Survey of the N.E. of James A. Rodgers owned by John Corratt in T. 21 N. R. 47 W.

I turn an angle of 90° from this meridian and run a tangent E. to a point S. of the old Cor. of Secs. 19, 24, 25 and 30. the approximate distance being 1½ miles the direction of the tangent at the point of intersection will therefore be S. 89° 57' E. I turn an angle of 90°01' from the W. to South and run from the "claimed" original Cor. of Secs. 19, 24, 25 and 30 a random line South to intersect the 5th Standard Parallel. At one mile seventy-eight chains and ninety-nine links intersect the 5th Standard Parallel North at a point E. 54 lks. dist from a leader post in mound 3 ins. sq. and 1 ft. above ground marked T. 21 N. on N. R. 47 W. S. 30 on W. and R. 46 W. S. 31 on E. faces.

Re-Survey of 5th Standard Parallel N. R. 47 W. Continued

Chains	
	I do not rebuild this Cor. at this time wishing to further indentify it. from this Cor. I run
	S. 89° 48' W. on tangent, through Sec. 36.
40.00	Set temp. 1/4 Sec. Cor.
80.00	N. 1 lks. from tang. Set temp. Cor. of Secs. 35 and 36.
	S. 89° 47' W. on tang. through Sec. 35.
0.26	The old Cor. of Secs. 35 and 36 flat mound with reader stake. S. 41 lks. from random line, the true bearing of the Parallel from this Cor. to S.E. Cor. of Sec. is therefore N. 89° 31' E.
40.00	N. 2.2 lks. from tang. Set temp. 1/4 Sec. Cor.
43.22	Old closing Cor. S. 82 lks. from Random line
80.00	N. 3.2 lks. from tang. Set temp. Cor. of Secs. 34 and 35.
	S. 89° 47' W. on tang. through Sec. 34.
40.00	N. 6 lks. from tang. Set temp. 1/4 Sec. Cor.
40.81	Old 1/4 Sec. Cor. S. 56 lks. from random. the old Cor. of Secs. 35 and 36. being S. 40 lks. from random, the true bearing of Parallel from this Cor. to the old Cor. of Secs. 35 and 36. is therefore N. 89° 44' E.
42.05	The old closing Cor. S. 58 lks. from random.
80.00	N. 8 lks. from tang. Set temp. Cor. of Secs. 33 and 34.
	S. 89° 46' W. on tang. through Sec. 33.
0.44	The old Cor. of Secs. 33 and 34. S. 92 lks. from random line. the old 1/4 Cor. on S. bdry. of Sec. 34. being S. 56 lks. from random line. the true bearing of Standard from this Cor. to the old 1/4 Cor. on S. bdry. Sec. 34. is therefore N. 89° 17' E.
40.00	N. 11 lks. from tang. Set temp. 1/4 Sec. Cor.
41.15	Old 1/4 Sec. Cor. S. 103 lks. from random line. The old Cor. of Secs. 33 and 34. being S. 92 lks. from random, the true bearing of the Standard from this Cor. to the old Cor. of Secs. 33 and 34. is therefore N. 89° 34' E.
42.05	The old closing Cor. S. 17 lks. from random line.

Re-Survey of 5th Standard Parallel N. R. 47 W. Continued

Chains	
80.00	N. 14 lks. from tang. Set temp. Cor. of Secs. 32 and 33.
	S. 89° 45' W. on tang. through Sec. 32.
1.38	The old Cor. of Secs. 32 and 33. S. 42 lks. from random. the old 1/4 Cor. on S. bdry of Sec. 33. being S. 113 lks. from random line. the true bearing of the Standard Parallel from this Cor. to the old 1/4 Cor. on S. bdry of Sec. 33 is therefore – S. 89° 20' E.
40.00	The 18 lks. from tang. Set temp. 1/4 Sec. Cor.
41.50	The old 1/4 Sec. Cor. S. 63 lks. from random line. the old Cor. of Secs. 32 and 33. being S. 42 lks. from random line the true bearing of the Standard from this Cor. to the old Cor. of Secs. 32 and 33 is therefore N. 89° 30' E.
41.83	The old closing Cor. S. 63 lks. from random line.
80.00	N. 23 lks. from tang. Set temp. Cor. of Secs. 31 and 32.
	S. 89° 44' W. on tang. through Sec. 31.
1.70	The old Cor. of Secs. 31 and 32. S. 99 lks. from random line. the old 1/4 Cor. on S. of Sec. 32. being S. 63 lks. from random line. the true bearing of the Standard Parallel from this Cor. to the old 1/4 Cor. on S. of Sec. 32 is therefore N. 89° 17' E.
40.10	N. 37 lks. from tang. Set temp. 1/4 Sec. Cor.
80.00	N. 33 lks. from tang. Set temp. Cor. of N. 21 N.R. 47 and 48 W.

R 4877

Thence I run in R. 48 W.

S. 89° 45' W. on tang. through Sec. 36.

41.25 N. 38 lks. from tang. Set temp. 1/4 Sec. Cor. which temp. Cor. is N. 99 lks. dist. from the old 1/4 Sec. Cor. on S. of Sec. 36. stake in flat mound, the old Cor. of Secs. 31 and 32. being S. 99 lks. dist. from random line. the true bearing of the Standard Parallel from this Cor. to the old Cor. of Secs. 31 and 32 is therefore N. 89° 48' E. To establish the Cor. of T. 21 N. R. 47 and 48 W. in its original position The distance from the old Cor. of Secs. 31 and 32.

Re-Survey of 5th Standard Parallel N. R. 47 W. Continued

Chains	
	R. 47 W. to the old 1/4 Cor. on S. of Sec. 36. R. 48 W. being 119.55 chs. the distance from the 1/4 Cor. on S. bdry of Sec. 36. to the Cor. of Tp. will therefore be 119.55 ÷ 3 = 39.85 chs. – from the original 1/4 Cor. on S. bdry of Sec. 36. I run in R. 48 W.
	N. 89° 45' E. on S. bdry of Sec. 36.
	Descend gently over rolling ground on top hill.
13.00	Top of ascent. thence along N. face of hills.
36.00	Descend N. E. slope.
39.85	Set an Oak Post 3 ft. long 4 ins. sq. with marked limestone 24 ins. in the ground for Standard Cor. to T. 21 N. R. 47 and 48 W. marked. S. C. on T. 21 N. on N. R. 47 W. S. 31 on E. and. R. 48 W. S. 36 on W. faces. with 6 grooves on N. E. and W. faces. dig pits 18 x 18 x 12 ins. crosswise on each line. E. and W. 4 ft. and N. of Post. 6 ft. dist and raise a mound of earth 5 ft. base 2½ ft. high N. of Cor.
	Land rolling and broken. Soil sandy 3rd rate. Vegetation sand grass. October 15th 1900.

True Line R 47

Thence I run in R. 47 W. locating the permanent 1/4 and Section Corners on a line defined by the original 1/4 and Sec. Corners found on this line and at intervals of 40 chs. from the S. E. Cor. of Tp. the W. fractional mile will therefore be — 121.25 chs. – 39.85 = 81.40 and the W. fractional 1/2 mile will be 41.40 chs.

Chains	
	N. 89° 45' E. on S. of Sec. 31.
	Along S. E. face hills.
4.00	Descend from low ridge.
12.00	Bottom descent. Ascending gently.
19.40	Wire fence bears N. E. and S. W. from point 1 ch. N. thence over rolling ground

Re-Survey of 5th Standard Parallel N. R. 47 W. Continued

Chains.	
41.40	Deposit marked limestone 12 ins. in the ground for 1/4 Sec. Cor. dig pits 18 x 18 x 12 ins. E. and W. of Cor. 4 ft. dist. and raise a mound of earth 3½ ft. base 1½ ft. high over deposit. In E. pit drive an Oak stake 3 ft. long 2 ins. sq. 12 ins. in the ground marked. S. C. 1/4 S. on N. face.
45.40	Descend very gently.
61.00	Enter N. edge of rolling valley.
61.50	Trail bears N. E. and S. W.
79.70	The old Cor. of Secs. 31 and 32. flat mound with pits E. W. and N. from this Cor. I run. N. 89° 17' E.
81.40	Set an Oak Post 3 ft. long. 4 ins. sq. with a marked limestone 24 ins. in the ground for Standard Cor. of Secs. 31 and 32. marked. S. C. S. 21 N. R. 47 W. on N. S. 32. on E. and. S. 31 on W. face with 5 grooves on E. and 1 groove on W. faces. dig pits 18 x 18 x 12 ins. crosswise on each line. E. and W. 3 ft. and N. of post 7 ft. dist. and raise a mound of earth 4 ft. base 2 ft. high N. of Cor.
	Land rolling. Soil sandy – 3rd rate. Vegetation, sand grass.

	N. 89° 17' E. on S. bdry of Sec. 32.
	Over rolling ground.
12.40	Trail bears N. and S.
14.00	Ascend gently.
29.00	Top of ascent. thence over rolling hills.
38.17	Old closing Cor. on line.
38.50	Original 1/4 Sec. Cor. flat mound with pits E. and W. Thence I run N. 89° 30' E.
40.00	Deposit marked limestone 12 ins. in the ground for 1/4 Sec. Cor. dig pits 18 x 18 x 12 ins. E. and W. of Cor. 4 ft. dist and raise a mound

Re-Survey of 5th Standard Parallel N. R. 47 W. Continued

Chains	
	of earth 3½ ft. base 1½ ft. high over deposit.
	In E. pit drive an Oak stake 2 ft. long 2 ins. sq. 12 ins. in the ground, marked.
	S. C. ¼ S. on N. face.
70.00	Deposit gradual N. E. slope.
78.62	The original Cor. of Secs. 32 and 33, flat mound with pits E. W. and N. Thence I run
	S. 89°20' E. ~
80.00	In W. edge of depression. Set an Oak Post 3 ft. long 4 ins. sq. with a marked limestone 24 ins. in the ground for Standard Cor. of Secs. 32 and 33, marked.
	S. C. T. 21 N. R. 47 W. on N.
	S. 33 on E. and
	S. 33 on W. face with 4 grooves in E. and 2 grooves on W. faces dig pits 18×18×12 ins. crosswise in each line E. and W. 3 ft. and N. of post 7 ft. dist. and raise a mound of earth 4 ft. base 2 ft. high N. of Cor.
	Land, rolling.
	Soil sandy 3rd rate
	Vegetation, sand grass.

	S. 89°20' E. on S. bdry of Sec. 33.
	Ascend S. W. slope low ridge.
6.00	Top of ascent, descend S. E. slope.
23.00	Bottom descent thence over rolling table land.
39.95	Old E. losing Cor. N. 7 Chs.
38.85	Original ¼ Cor. flat mound with thence I run ~
	N. 89°39' E.
40.00	Deposit marked limestone 12 ins. in the ground for ¼ Sec. Cor. dig pits 18×18×12 ins. E. and W. of Cor. 4 ft. dist. and raise a mound of earth 3½ ft. base 1½ ft. high over deposit.
	In E. pit drive an Oak stake 2 ft. long 2 ins. sq. 12 ins. in the ground, marked.
	¼ S. on W. face.
60.00	Ascend gently.
65.00	Top of ascent, descend gentle N. E. slope.

Re-Survey of 5th Standard Parallel N. R. 47 W. Continued

Chains	
70.63	Wire fence bears N. 30° E. and S. 30° W.
79.06	Original Cor. of Secs. 33 and 34, flat mound with pits E. W. and N. thence I run
	N. 89°17' E.
80.00	Set an Oak Post 3 ft. long 4 ins. sq. with marked limestone 24 ins. in the ground for Standard Cor. of Secs. 33 and 34 marked.
	S. C. T. 21 N. R. 47 W. on N.
	S. 34 on E. and
	S. 33 on W. faces. dig pits 24×18×12 ins. crosswise on each line E. and W. 3 ft. and N. of post 7 ft. dist. and raise a mound of earth 4 ft. base 2 ft. high N. of Cor.
	Land, rolling hills.
	Soil sandy 3rd rate
	Vegetation, sand grass.

	N. 89°17' E. on S. bdry of Sec. 34.
	Descend gently.
5.00	Bottom descent thence over rolling ground.
37.95	Old C. C. on line.
39.19	Original ¼ Sec. Cor. mound with indistinct pits E. and W. 5 ft. dist. ~ Thence I run.
40.00	Deposit marked limestone 12 ins. in the ground for ¼ Sec. Cor. dig pits 18×18×12 ins. E. and W. of Cor. 4 ft. dist. and raise a mound of earth 3½ ft. base 1½ ft. high over deposit.
	In E. pit drive an Oak stake 2 ft. long 2 ins. sq. 12 ins. in the ground, marked.
	S. C. ¼ S. on N. face.
45.00	Ascend gradual S. W. slope.
71.00	Top of ascent, on hills or ridge, bearing S. E. and N. W. descend N. E. slope.
80.00	Set an Oak Post 3 ft. long 4 ins. sq. with marked limestone 24 ins. in ground for Standard Cor. of Secs. 34 and 35.
	S. C. T. 21 N. R. 47 W. on N.
	S. 34 on E. and
	S. 33 on W. faces. dig pits 18×18×12 ins. crosswise on each line E. and W. 3 ft. and N. of post 7 ft. dist.

Re-Survey of 5th Standard Parallel N. R. 47 W. Continued

Chains	
	and raise a mound of earth 4 ft. base 2 ft. high N. of Corner.
	Land rolling Soil sandy 3rd rate Vegetation Sand grass.
	N. 89° 44' E. on S. of Sec. 35.
	Descend N. E. slope.
14.00	Bottom descend, thence over rolling ground.
37.78	Old closing Cor. S. 33 Chs. dist.
40.00	Deposit marked limestone 12 ins. in the ground for Stand. 1/4 Sec. Cor. dig pits 18x18x12 ins. E. and W. of Cor. 4 ft. dist and raise a mound of earth 3½ ft. base 1½ ft. high over deposit.
	In E. pit drive an Oak stake 2 ft. long 2 ins. sq. 12 ins. in the ground, marked
	S.C. 1/4 S. on N. face.
	Ascend gently over low hills.
79.74	The original Cor. of Secs. 35 and 36. flat mound with pits E. W. and N. from this old Cor. I run.
	N. 89° 31' E. on S. bdry of Sec. 35
80.00	Set an Oak Post 3 ft. long 4 ins. sq. with marked limestone 24 ins. ground for Standard Cor. of Secs. 35 and 36. marked.
	S.C. T. 21 N. R. 47 W. on N.
	S. 36 on E. and
	S. 35 on W. faces with 1 groove on E. and 3 grooves on W. faces dig pits 24x18x12 ins. crosswise on each line E. and W. 3 ft. and N. of post 7 ft. dist and raise a mound of earth 4 ft. base 2 ft. high W. of Cor.
	Land, rolling hills. Soil sandy 3rd rate. Vegetation, sand grass.
	N. 89° 31' E. on S. bdry of Sec 36.
	Over low broken hills.
40.00	In pocket or depression, deposit marked limestone 12 ins. in the ground. for Standard 1/4 Sec. Cor. dig

Re-Survey of 5th Standard Parallel N. R. 47 W. Concluded.

Chains	
	pits 18x18x12 ins. E. and W. of Cor. 4 ft. dist. and raise a mound of earth 3½ ft. base 1½ ft. high over deposit. In E. pit, drive an Oak stake 2 ft. long 2 ins. sq. 12 ins. in the ground, marked.
	S.C. 1/4 S. on N. face.
	Ascend over low ridges, along S. W. face hills.
52.00	The face of ridge at top of ascent.
57.78	Ridge. descend over broken ground.
80.00	The original Standard Cor. T. 21 N. R. 46 and 47 W. which I consider "fully indentified" which Cor. I rebuild in its original position. Set an Oak Post 3 ft. long 4 ins. sq. with the original cedar post and a marked limestone 24 ins. in the ground for the Standard Cor. of T. 21 N. R. 46 and 47 W. marked.
	S.C. T. 21 N. on N.
	R. 46 W. S. 31 on E. and.
	R. 47 W. S. 36 on W. faces with 6 grooves on N. E. and W. faces. dig pits 18x18x12 ins. crosswise on each line E. and W. 4 ft. and N. of Cor. 8 ft. dist. and raise a mound of earth 5 ft. base 2½ ft. high N. of Cor.
	Land rolling and broken Soil sandy 3rd and 4th rate Vegetation, sand grass. November 27. 1900.

I hereby certify I assisted Willard W Alt as surveyor in surveying and resurveying all those parts and portions of the 5th Standard Parallel North through Range 47 W State of Nebraska which are represented in the foregoing field notes as having been surveyed by him and under his direction and that the said survey has been in all respects, to the best of my knowledge and belief well and faithfully surveyed and the corner monuments established according to the instructions furnished by the Commission or of the General Land Office

(Signed) Jim Weisser

Subscribed and sworn to before me the 25th day of February 1901

(Signed) Willard W Alt
U S Surveyor

Duplicate see page 15

I hereby certify that I assisted Willard W Alt U S Surveyor in surveying and resurveying all those parts and portions of the 5th Standard Parallel North through Range 47 W State of Nebraska which are represented in the foregoing field notes as having been surveyed by him and under his direction and that the said survey has been in all respects to the best of my knowledge and belief well and faithfully surveyed and the corner monuments established according to the instructions furnished by the Commissioner of the General Land Office

(Signed) Jesse A Winser

Subscribed and sworn before me this the 25th day of February 1901

(Signed) Willard W Alt
U S Surveyor

FINAL OATHS OF DEPUTY SURVEYOR AND HIS ASSISTANTS.

LIST OF NAMES.

A list of the names of the individuals employed by Willard W Alt, United States ~~Deputy~~ Surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of 5th Standard Parallel North through Range 47 W State of Nebraska showing the respective capacities in which they acted:

Joseph B Kuon, *Chainman.*
Jesse A Winser, *Chainman.*
Harry Carroll, *Chainman* ~~*Moundman.*~~
Moundman.
Axman.
Axman.
Herbert Campbell, *Flagman.*

FINAL OATH OF ASSISTANTS.

We hereby certify that we assisted Willard W Alt, United States ~~Deputy~~ Surveyor, in surveying all those parts or portions of the 5th Standard Parallel North North through Range 47 West of the 6th ~~Principal~~ meridian, State of Nebraska, which are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the ~~United States Surveyor General for~~ Commissioner of the General Land office

Joseph B Kuon, *Chainman.*
Harry Carroll, *Chainman.*
Earl J Martin, *Moundman.*
Moundman.
Axman.
Axman.
Herbert Campbell, *Flagman.*

Subscribed and sworn to before me this 28th day of January, 1901

SEAL

Willard W Alt
U S Surveyor

151

115
17

FINAL OATH OF UNITED STATES ~~DEPUTY~~ SURVEYOR.

I, Willard W. Ott, United States ~~Deputy~~ Surveyor, do solemnly swear that, in pursuance of a contract received from Commissioner of General Land Office ~~United States Surveyor General for~~, bearing date of the 26 ~~day~~ of May 26 1900, 189 , I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the Commissioner of ~~United States Surveyor General~~ the General Land Office, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of 5th Standard Parallel North through Range 47 West of the 6th Principal meridian, in the State of Nebraska, which are represented in the foregoing field notes as having been surveyed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the Commissioner of the ~~United States Surveyor General for~~ General Land Office and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey; and should any fraud be detected, I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

Willard W. Ott
United States ~~Deputy~~ Surveyor.

Subscribed by said Willard W. Ott, and sworn to before me this 5th day of Oct 1901, 189

SEAL

W H Nichols
Clerk of the District Court
in and for Grant County Nebraska

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

, 189

The foregoing field notes of the survey of 5th Standard Parallel North through Range 47 West

executed by Willard W. Ott - Deputy under his contract No Spl Inst, dated May 26 1900, 189 , having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Bruce Harmon
Commissioner and Ex officio Surveyor General.
for Nebraska

I certify that the foregoing transcript of the field notes of the above-described surveys in the state of Nebraska, has been correctly copied from the original notes on file in this office.

Bruce Harmon
Commissioner and Ex officio Surveyor General.
for Nebraska

6—151

416

General Land Office • Original Field Notes

Book Number

772

W.W. Alt - 5th Standard Parallel through T 47 N

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.