General Land Office • Original Field Notes

Book Number

774

W.W. Alt - East & North boundaries T 23 N, R 34 W

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.

Duplicate

7-8-1903 Ex OK R.H. Except that flag burners on pages 1-4 (sub)

234

4—679.

Rec'd with letter from W. W. Alt, U.S. Surveyor, dated April 21, 1900, 54393

FIELD NOTES

OF THE SURVEY OF THE

East and North boundary of Township No. 23 North, Range 34 West

Of the Sixth Principal Meridian, State of Nebraska

AS SURVEYED BY

Willard W. Alt, United States ~~Deputy~~ Surveyor,

Under his Contract ~~No.~~ ——, dated April 17, 1899

Survey commenced October 16, 1899

Survey completed October 17, 1899

6—151

NAMES AND DUTIES OF ASSISTANTS.

Joseph B. Koon, Chainman.
George M. Stevenson, " "
Percy Adams, Flagman.
William W. Whitehead, Moundman.

INDEX DIAGRAM.

North and East boundary

Township 23 N. Range 34 W.

7	8	9	9	10	11	
6	5	4	3	2	1	2
7	8	9	10	11	12	2
18	17	16	15	14	13	3
19	20	21	22	23	24	4
30	29	28	27	26	25	5
31	32	33	34	35	36	5

Meanders Page

N.

Joseph
George W.
Percy
William

6—151

PRELIMINARY OATHS OF ASSISTANTS.

We, ... and .....
do solemnly swear that we will well and faithfully execute the duties of chainmen; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distances to all notable objects, and the true lengths of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of

.....

....., *Chainman.*

....., *Chainman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

We, ... and .....
do solemnly swear that we will well and truly perform the duties of moundmen in the establishment of corners, according to the instructions given us, to the best of our skill and ability, in the survey of

.....

....., *Moundman.*

....., *Moundman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

We, ... and .....
do solemnly swear that we will well and truly perform the duties of axmen in the establishment of corners and other duties, according to instructions given us, to the best of our skill and ability, in the survey of

.....

....., *Axman.*

....., *Axman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

I, ..., do solemnly swear that I will well and truly perform the duties of flagman according to instructions given me, to the best of my skill and ability, in the survey of .....

....., *Flagman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

6—151

East boundary T. 23 N., Range 34 W.

Chains	
	Preparatory to running this line, I set a flag at the corner of T. 23, and 24 N. R. 33 and 34 W., which flag is plainly visible from the cor. of T. 22, and 23, N., R. 33, and 34; the true bearing of the flag from the cor. of T. 22 and 23 N., R. 33, and 34 W., is N. 0° 10' E. Therefore from the cor. of T. 22, and 23 N., R. 33 and 34 W.; I run a random line.
	N. 0° 10' E. on a random line bet. Secs. 31 and 36
40.00	Old 1/4 Sec. cor. 2 lks. E. of line.
80.00	Set temp. cor. of Secs. 25, 30, 31, and 36.
	N. 0° 10' E., on a random line bet. Secs 25, and 30.
0.06	The Old cor. of Secs. 25, 30, 31, and 36.
40.00	The Old 1/4 Sec. cor., 1 lk. W. of line
80.00	The Old cor. of Secs., 19, 24, 25, and 30 on line.
	N. 0° 10' E., on a random line bet. Secs. 19. and 24.
40.00	The old 1/4 Sec. cor. - on line.
80.00	Set temp. cor. for Secs. 13, 18, 19, and 24.
	N. 0° 10' E. on a random line bet. Secs. 13, and 18.
0.10	The Old cor. of Secs. 13, 18, 19, and 24, on line.
40.10	The Old 1/4 Sec. cor., 3 lks. W. of line.
80.00	Set temp. cor. of secs 7, 12, 13, and 18.
	N. 0° 10' E. on a random line bet. Secs. 7, and 12.
0.10	The Old cor. of Secs. 7, 12, 13, and 18, 7 lks. W. of line.
40.12	The Old 1/4 Sec. cor., 3 lks. W. of line.
80.00	Set temp. cor. of secs. 1, 6, 7, and 12,
	N. 0° 10' E. on a random line bet. Secs. 1, and 6,
0.05	The Old cor. of secs 1, 6, 7, and 12 on line

East Boundary T. 23 N., R. 34 W.,

Chains	
40.05	The Old 1/4 Sec. Cor., on line.
80.06	The Old Cor. of T. 23, and 24 N., R. 33, and 34 W., I consider the alignment and measurement of this line practically correct.- I return on line and rebuild corners, where necessary in their original locations.
	S. 0°10' W. on a true line bet. Secs. 1, and 6. Descent gently along S. face range.
9.00	Descend S. Slope gradually.
30.00	Bottom of descent, over rolling ground
35.50	Old Trail- course N. 60° E.,
40.01	The old 1/4 Sec. Cor. which is a mound of earth, with pits, 18 ins. sq., dug N. and S. 4 ft. dist. with a cedar stake 2 ins. sq. firmly driven in S. pit, marked 1/4 S. on W. face.
68.00	Ascend N. Slope gradually.
80.01	The Old Cor. of Secs. 1, 6, 7, and 12, in good condition, which is a mound of Earth, with pits, 18 ins. sq., dug in each Sec., In the S.E. pit, there is an Oak stake 2 ins. sq., firmly driven, marked T. 23 N. S. 6, on N.E. R. 33 W. S. 7 on S.E. S. 12 on S.W. and R. 34 W. S. 1 on N.W. faces, with 1 notch on N. and 5 notches on S. Edges.

As the old cor. of Secs. 7, 12, 13, and 18 is W. 7 lks. from random line - and the course of the random line being N. 0° 10' W., - The true bearing of Range line from the cor. of Secs. 1, 6, 7, and 12 to the cor. of Secs. 7, 12, 13, and 18 will be S. 0° 13' W.

Chains	
	S. 0° 13' W. on true line bet. Secs. 7, and 12, Ascend gradually
5.00	Top 30 ft. above cor., over rolling ground
15.75	Low sandy bluff, descend S. Slope.

East boundary T. 23 N., R. 34 W.,

Chains	
35.00	Bottom of descent, in rolling valley, bears E. and W.
39.97	The Old 1/4 Sec. Cor., which is a mound of earth with pits 18 ins. sq., dug N. and S. of cor. 4 ft. dist., In the S. pit, there is a cedar stake 2 ins. sq. firmly driven, marked 1/4 S. on W. face
45.00	Ascend gently.
69.00	Top of ascent, over low rolling hills
79.95	The Old Cor. of Secs. 7, 12, 13, and 18, which is a cedar post 4 ins. sq. 12 ins above ground, marked T. 23 N. S. 7 on N.E. R. 33 W. S. 18 on S.E. S. 13 on S.W. and R. 34 W. S. 12 on N.W. faces, with 2 notches on N. and 4 notches on S. Edge; with pits 18 ins sq., dug in each Sec. 5 1/2 ft. dist., with a mound of Earth W. of corner.

As the Cor. of Secs. 7, 12, 13, and 18 is W. 7 lks. from the random line - and the bed cor. of Secs 13, 18, 19 and 24 is on the random line; the true bearing of the range line from cor. of Secs 7, 12, 13, and 18, to cor. of Secs. 13, 18, 19, and 24, is therefore S. 0° 7' W.

Chains	
	S. 0° 7' W. on true line bet. Secs. 13, and 18, over rolling ground
10.10	Ascend N. Slope gently.
23.50	Top of ascent on low sand bluff; thence along W. face low hills.
36.00	Descend S.W. Slope
40.00	The Old 1/4 Sec. Cor., which is a mound of Earth with pits 18 ins. sq., dug N. and S. of cor 4 ft. dist. In the S. pit, there is a Cedar stake 2 ins. sq. firmly driven, marked 1/4 S. on W. face

2
13

4
241

East Boundary T. 23 N., R. 34 W.

chains	
59.00	Bottom of descent, over rolling ground.
80.00	The Old cor. of Secs. 13, 18, 19, and 24, which is a mound of earth, with pits 18 ins. sq.; dug in each sec. 4 ft. dist. In the S.E. pit, there is an Oak stake 2 ins. sq. firmly driven, marked T. 23 N. S. 13 on N.E. R. 33 W. S 19. on S.E. S. 24 on S.W. and R. 34 W. S. 13 on W. W. faces with 3 notches on N. and S. Edges.
	From the cor. of Secs. 13, 18, 19, and 24, the true bearing of the Range line is S. 0° 10' W. S. 0° 10' W. on true line bet. Secs. 19, and 24, ascend gently
12.00	Top. - thence over rolling hills.
30.00	ascend
35.00	Ridge The Old 1/4 Sec. cor. which is a mound of earth, with pits 18 ins. sq., dug N. and S of cor. 4 ft. dist. In S. pit there is a cedar stake 2 ins sq. firmly driven marked 1/4 S. on W. face.
50.00	Bottom of descent, in basin
64.00	ascend abrupt. N.E. slope.
67.00	Top of abrupt ascent. ascend gradually, along N.E. face
75.00	Top of range 100 ft. above basin, descend.
80.10	The Old cor. of Secs. 19, 24, 25, and 30, which is a cedar post 4 ins. sq., 12 ins above ground marked T. 23 N. S. 19 on N.E. R. 33 W. S 30 on S.E. S. 25 on S.W. and R. 34 W. S 24 N.W. faces, with 2 notches on S. and 4 notches on N. Edges.

5
242

...N., R. 34 W.

...dug in each Sec.
...d of Earth W. of Cor.

...Secs. 25, and 30.
...broken ground.
...rolling ground.
...W.
...ich is a mound of
...sq., dug N. and S of
...e S. pit, there is a
...firmly driven, marked

...whills.
...Mallen, Course

...ver low hills
...0, 31, and 36, which
...th with pits 18 ins
...Sec. 4 ft. dist.
...e is an Oak stake
...driven, marked

...aces, with 1 notch on
...N. Edges.

...et Secs 31, and 36

...ver rolling ground.
...N.W. Slope.
...ich is a mound of
...sq.; dug N. and S of
...S. pit, there is a
...firmly driven

2
13r

4
241

East Boundary

chains	
59.00	Bottom of descu
80.00	The Old cor. of Se which is a ma 18 ins. sq.; dug i In the S.E. pit, 2 ins. sq. firmly T. 23 N. S. 13 on N R. 33 W. S 19. on S S. 24 on S.W. and R. 34 W. S. 13 on W. On N. and S. Edg
	From the cor. of S true bearing of S. 0° 10' W. on true lin ascend gently
12.00	Top. - thence over r
30.00	ascend
35.00	Ridge The Old 1/4 of Earth, with pits of cor. 4 ft. dist. In cedar stake 2 ins marked 1/4 S. on W. face.
50.00	Bottom of descent, in
64.00	ascend abrupt. N.E.
67.00	Top of abrupt ascent. along N.E. face
75.00	Top of range 100 ft. abro
80.10	The old cor. of secs. 19, a cedar post 4 ins. s marked T. 23 N. S. 19 on N.E R. 33 W. S 30 on S.E S. 25 on S.W. and R. 34 W. S 24 N.W. face on S. and 4 notches.

5
242

East boundary T. 23 N., R. 34 W.

chains	
	with pits 18 ins. sq. dug in each sec. 5 1/2 ft. dist. and a mound of Earth W. of Cor.
	S. 0° 10' E. on true line bet. Secs. 25, and 30. Descend over very broken ground.
21.00	Bottom of descent, over rolling ground.
23.00	Old Trail, bears E. and W.
40.00	The old 1/4 Sec. cor. which is a mound of Earth, with pits 18 ins. sq., dug N. and S of cor. 4 ft. dist. In the S. pit, there is a Cedar Stake 2 ins. sq. firmly driven, marked 1/4 S. on W. face
50.00	Ascend gently over low hills.
57.00	Trail Dismal River to Mullen. Course N.E. and S.W.
64.40	Low bluff; thence over low hills
79.94	Old cor. of Secs. 25, 30, 31, and 36, which is a mound of Earth with pits 18 ins sq.; dug in each sec. 4 ft. dist. In the S.E. pit there is an Oak stake 2 ins. sq firmly driven, marked T. 23 N. S. 30, on N.E R. 33 W. S. 31. on S.E S. 36 on S.W. and R. 34 W. S. 25. on W.W. faces, with 1 notch on S. and 5 notches on N. Edges.
	S 0° 10' W., on true line bet Secs 31, and 36 over low hills
8.00	Leave hills, thence over rolling ground.
26.00	Ascend gently along N.W. Slope.
40.06	The old 1/4 Sec cor., which is a mound of Earth with pits 18 ins sq.; dug N. and S of cor. 4 ft. dist. In the S. pit, there is a cedar stake 2 ins sq. firmly driven marked 1/4 S. on W. face

East boundary T. 23 N., R. 34 W.

Chains	
80.06	The cor. of T. 22, and 23 N., R. 33 and 34 W.

This line runs over irregular rolling hills and rolling valley lands, for its entire length - except between Secs. 19, and 24, where part of the ground is very broken.

Vegetation consists of a thin sand and buffalo grasses.

Soil, 4th rate, very sand and unfit for cultivation

Oct. 16, 1899.

William W. Alt
U.S. Surveyor.

North boundary T. 23 N.

From the cor. of T. 23 and 24 N., R. 33 and 34 W., which is a cedar post 4 ins. sq., 12 ins. above ground, marked
T. 24. N. S. 31. on N.E.
R. 33 W. S. 6. on S.E.
T. 23 N. S. 1 on S.W. and
R. 34 W. S. 36 on N.W. faces, with 6 notches on each edge, with pits, 24 ins sq., dug on each line N. E. and W. 4 ft., and S. of part 8 ft. dist. - with a mound of earth S. of cor.

Run West on a random line

Chains	
	West on tangent through sec. 1,
40.00	Set temp. 1/4 Sec. cor.
80.00	N. 1 lk. from tangent, set temp cor. of secs 1, 2, 35, and 36.
	S. 89°59' W. on tangent, through sec. 2.
40.00	N. 2 1/2 lks. from tangent set temp 1/4 sec. cor.
80.00	N. 3 1/2 lks. from tangent, set temp. cor. for Secs. 2, 3, 34 and 35.

North boundary T. 23 N., R. 34 W.

Chains	
	S. 89°59' W. on tangent, through sec 3.
40.00	N. 6 lks. from tangent set temp. 1/4 Sec. cor.
80.00	N 8 1/4 lks. from tangent Set temp cor. of Secs. 3, 4, 33, and 34.
	S. 89°58' W. on tangent, through sec. 4.
40.00	N. 11 lks. from tangent, Set temp 1/4 Sec. cor.
80.00	N. 14 lks. from tangent, Set temp cor. of Secs. 4, 5, 32, and 33.
	S 89°57' W. on tangent, through sec 5.
40.00	N. 18 lks. from tangent, Set temp. 1/4 sec. cor
80.00	N. 23 lks from tangent set temp. cor of Secs 5, 6, 31, and 32.
	S. 89°56' W. on tangent through sec 6.
40.00	N. 27 lks. from tangent, set temp 1/4 Sec. cor.
79.30	N 33. lks. from tangent, Set temp. cor. of Township which falls S. 1.56 chs. from cor. of T. 23 and 24 N., R. 34 and 35 W., the temporary corners will be moved North by off-sets, decreasing 13 lks. for each half mile and the true bearing of the town line is S. 89°49' E.
	S 89°49' E. on true line bet Secs. 6 and 31 over low rolling hills.
15.00	Ascend N. W. slope.
39.80	Deposit a charred stake 12 ins. in the ground for 1/4 sec. cor.; dug pits 18 X 18 X 12 ins E. and W. of cor. 4 ft. dist, and raised a mound of earth 3 1/2 ft. base, 1 1/2 ft. high over deposit.

In E. pit, drove a cedar stake 2 ft. long,

North boundary T. 23. N., R. 34 W.

Chains	
	2 ins sq., 12 ins. in the ground, marked 1/4 S. on N. face
43.00	Top of ascent; thence along N. face hills
45.00	Descend gently over broken ground
✓ 79.50	Deposit charred stake 12 ins. in the ground for cor. of secs. 5, 6, 31, and 32, dug pits 18 X 18 X 12 ins in each sec. 4 ft. dist. and raised a mound of earth 3 1/2 ft. base 1 1/2 ft. high, over deposit. In S. E. pit drove an oak stake 2 ft. long. 2 ins. sq., 12 ins. in the ground, marked T. 24 N. S. 32. on N. E. R. 34 W. S. 5. on S. E. T. 23 N. S. 6 on S. W. and S. 31 on N. W. faces, with 1 notch on W. and 5 notches on E. Edges
✓	S. 89° 49' E. on true line bet. secs 5, and 32.
2.00	ascend over very broken ground
24.00	Top of ascent. 50 ft. above cor., over broken ground Descend N. E. Slope.
✓ 40.00	Deposit charred stake 12 ins in the ground for 1/4 Sec. cor.; dug pits 18 X 18 X 12 ins. E. and W. of cor. 4 ft. dist. and raised a mound of earth 3 1/2 ft. base, 1 1/2 ft. high, over deposit. In E. pit, drove a cedar stake 2 ft. long 2 ins sq. 12 ins in the ground, marked. 1/4 S. on N. face
70.60	Bottom of descent; ascend N. Slope.
✓ 80.00	Set a cedar post, 3 ft. long 4 ins sq., with charred stake 24 ins. in the ground for cor. of secs. 4, 5, 32, and 33, marked T. 24 N. S. 33 on N. E. R. 33 W. S. 4 on S. E. T. 23 N. S. 5 on S. W. and S. 32 on N. W. face, with 2 notches

North boundary T. 23 N., R. 34 W.

Chains	
	on W. and 4 notches on E. Edges; dug pits 18 X 18 X 12 ins. in each sec., and raised a mound of Earth 4 ft. base, 2 ft. high, W. of cor.
✓	S. 89° 49' E., bet Secs., 4, and 33. ascend gently along N. Slope.
2.00	Top of ascent 20 ft. above cor.
10.00	Descend gradually along N. E. Slope
✓ 40.00	Deposit a charred stake 12 ins in the ground for 1/4 Sec. cor., dug pits 18 X 18 X 12 ins E. and W. of cor., 4 ft. dist. and raised a mound of earth 3 1/2 ft. base, 1 1/2 ft. high over deposit. In E. pit, drove a cedar stake 2 ft. long, 2 ins. sq., 12 ins in the ground, marked 1/4 S. on N. face
✓ 80.00	Deposit charred stake 12 ins in the ground for cor. of secs. 3, 4, 33, and 34, dug pits; 18 X 18 X 12 ins in each sec. 4 ft. dist. and raised a mound of earth 4 ft. base, 2 ft. high over deposit. In S. E. pit, drove an Oak stake 2 ft. long, 2 ins. sq., 12 ins, in the ground, marked T. 24 N. S. 34 on N. E. R. 34 W. S. 3 on S. E. T. 23 N. S. 4 on S. W. and S. 33. on N. W. faces, with 3 notches on E. and W. Edges.
✓	S. 89° 49' E. bet. secs. 3 and 34. over low foot hills.
✓ 40.00	Deposit charred stake 12 ins. in the ground for 1/4 Sec. cor.; dug pits 18 X 18 X 12 ins E. and W. of cor. 4 ft. dist. and raised a mound of earth 3 1/2 ft. base, 1 1/2 ft. high over deposit In E. pit, drove a cedar stake 2 ft. long. 2 ins sq.; 12 ins. in the ground, marked

North boundary T. 23 N., R. 34 W.

Chains	
	1/4 S. on N. face
44.00	Enter rolling ground.
55.00	Ascend N.W. slope.
79.00	Top on "table".
✓ 80.00	Set a cedar post 3 ft. long 4 ins sq., with charred stake 24 ins in the ground for cor. of secs. 2, 3, 34, and 35. marked T. 24 N. S. 35 on N.E. R. 34 W. S. 2 on S.E. T. 23 N. S. 3 on S.W. and S. 34 on N.W. faces, with 2 notches on E. and 4 notches on W. Edges; dug pits 18X18X12 ins in each sec., 5½ ft. dist. and raised a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
✓	S. 89°49' E. bet. secs. 2, and 35.
	Ascend N.W. Slope
5.00	Top 30 ft. above cor.; thence along N. Slope hills -
22.00	Descend.
32.00	Bottom, in ravine, N. and S.
✓ 40.00	Deposit charred stake 12 ins. in the ground for 1/4 sec. cor. dug pits 18X18X12 ins. E. and W. of cor. 4 ft. dist. and raised a mound of earth 3½ ft. base, 1½ ft. high, over deposit. In E. pit, drove a cedar stake 2 ft. long 2 ins. sq., 12 ins. in the ground, marked 1/4 S. on N. face.
42.00	Ascend along N.W. slope gradually.
70.00	Top of ascent; thence along N. face of hills
✓ 80.00	Deposit charred stake 12 ins. in the ground for cor. of secs. 1, 2, 35, and 36, dug pits 18X18X12 ins in each sec.

North Boundary T. 23 N., R. 34 W.

Chains	
	4 ft. dist. and raised a mound of earth 4 ft. base, 2 ft. high, over deposit. In S.E. pit, drove an Oak stake 2 ft. long 2 ins. sq., 12 ins. in the ground, marked T. 24 N. S. 36 on N.E. R. 34 W. S 1 on S.E. T. 23 N S 2 on S.W. and S. 35 on N.W. faces, with 1 notch on E. and 5 notches on W. Edges.
✓	S. 89°49' E. bet. secs. 1, and 36.
	along N. face of hills - over ridges.
30.50	Descend along N. face.
38.00	Bottom descent, over broken ground
✓ 40.00	Deposit charred stake 12 ins. in the ground for 1/4 sec. cor., dug pits 18X18X12 ins E. and W. of cor. 4 ft. dist. and raised a mound of earth 3½ ft. base, 1½ ft. high, over deposit. In E. pit, drove a cedar stake 2 ft. long 2 ins. sq., 12 ins. in the ground, marked 1/4 S. on N. face.
47.50	Ascend over broken ground and ridges.
67.00	Top of ascent - over broken ground.
79.00	Ridge - course N. and S., descend.
✓ 80.00.	The Cor. of T. 23. and 24 N., R. 33, and 34 W.
	This line runs over top and slope of a nearly regular range of hills; its entire length. Soil, very sandy, 4th rate Vegetation consists of sand and bunch grasses. Oct. 17, 1899
	Willard W. Alt U.S. Surveyor.

2
132

12
249

North Boundary T. 23 N., R. 34 W.

Boundaries of T. 23 N., R. 34 W.

Lines Designated	True Bearing	Lengths chs.	Latitude N	Latitude S	Departure E.	Departure W
S. boundary	N. 89°42 W.	479.00	2.58			479.00
W. boundary	North	480.00	480.00			
N. boundary	S 89°49 E.	479.50		1.56	479.50	
E. boundary	S 0°10 W.			480.00		1.56
Convergency					0.65	
			482.58	481.56	480.15	480.56
			481.56			480.15
Error in Latitude.			1.02			
Error in Departure.						0.41

12
250

FINAL OATHS OF DEPUTY SURVEYOR AND HIS ASSISTANTS.

LIST OF NAMES.

A list of the names of the individuals employed by .....

....., United States Deputy Surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of .....

.....

showing the respective capacities in which they acted:

....., *Chainman.*

....., *Chainman.*

....., *Moundman.*

....., *Moundman.*

....., *Axman.*

....., *Axman.*

....., *Flagman.*

FINAL OATH OF ASSISTANTS.

We hereby certify that we assisted .....

....., United States Deputy Surveyor, in surveying all those parts or portions of the .....

.....

..... of the .....

..... meridian, ... of ....., which are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the United States Surveyor General for .....

....., *Chainman.*

....., *Chainman.*

....., *Moundman.*

....., *Moundman.*

....., *Axman.*

....., *Axman.*

....., *Flagman.*

.....

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

.....

.....

6—151

14
251

FINAL OATH OF UNITED STATES DEPUTY SURVEYOR.

I, ..., United States Deputy Surveyor, do solemnly swear that, in pursuance of a contract received from ..... United States Surveyor General for ....., bearing date of the ..... day of ....., 189 , I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States Surveyor General for ....., the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of .....

.....

.....

.....

.....of the.....

..... meridian, in the..... of....., which are represented in the foregoing field notes as having been surveyed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the United States Surveyor General for.....and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey; and should any fraud be detected, I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

.....
United States Deputy Surveyor.

Subscribed by said....., and sworn to before me this..... day of....., 189

.....

SEAL

APPROVAL.

General Land OFFICE OF THE UNITED STATES ~~SURVEYOR GENERAL~~,

Wash. D.C. June 30, 1900, ~~189~~

The foregoing field notes of the survey of East and North Boundary of Township No. 23 North Range 36 West.

executed by Willard H. Alf U.S. Surveyor under his contract No. —, dated April 15, 1899, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Binger Hermann
~~United States Surveyor General.~~
Commissioner and Ex-Officio Surveyor General for Nebraska

~~I certify that the foregoing transcript of the field notes of the above-described surveys in~~ ....., has been correctly copied from the original notes on file in this office.

.....
United States Surveyor General.

6—151

General Land Office • Original Field Notes

Book Number

774

W.W. Alt - East & North boundaries T 23 N, R 34 W

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.