General Land Office • Original Field Notes

Book Number

774

W.W. Alt - East & North bdy. T 23 N, East bdy. T 24 N, R 36 W

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.

Field Notes

of the survey of the

East & North Boundaries

of

Township No. 23 N.

and

East Boundary

of

Township No 24 N

of

Range No 36 W.

of the

Sixth Principal Meridian

in

Nebraska

Surveyed by

N. S. Dixon U.S. Deputy Surveyor

Under contract dated Dec. 22 1894

Survey commenced July 1st 1895

Survey commenced July 6th 1895

—"—

INDEX DIAGRAM.

Township 23 North, *Range* 36 West.

5	6	6	7	8	8	
6	5	4	3	2	1	4
7	8	9	10	11	12	3
18	17	16	15	14	13	3
19	20	21	22	23	24	2
30	29	28	27	26	25	2
31	32	33	34	35	36	1

Meanders Page.....

Preliminary Oaths of Assistants.

WE, ...

.....

.....

do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain over even and uneven ground, and plumb the tally-pins either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true lengths of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us in the survey of the .....

.....

.....

.....

.....

..... *, Chainman.*

..... *, Chainman.*

..... *, Chainman.*

..... *, Chainman*

Subscribed and sworn to before me this .....
day of ..... , 18 .

.....

.....

WE, ...

.....

do solemnly swear that we will well and truly perform the duties of axemen in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of the .....

.....

.....

.....

.....

Subscribed and sworn to before me this .....
day of ..... , 18 .

..... *, Axeman.*

..... *, Axeman.*

.....

.....

INDEX DIAGRAM.

Township 24 N. *Range* 36 W.

6	5	4	3	2	1	13
7	8	9	10	11	12	12
18	17	16	15	14	13	12
19	20	21	22	23	24	11
30	29	28	27	26	25	10
31	32	33	34	35	36	10

Meanders Page .....

E. Bdy of T. 23 N., R 36 W. 6th Om.

Chains

July 1st 1895. at the cor of Ts 22 & 23 N., Rs 35 & 36 W., I observe Polaris at 10h 01m, P.M. by my watch which is 46m fast of l.m.t. and fix a point on the line thus determined by a nail on a wooden plug firmly set in the ground N. of my station.
On July 2nd I lay off the azimuth of Polaris 1°03½ to the west, and note the magnetic bearing of the meridian at 9h 40m am. N. 12°55' W. which, corrected by Table G. in the Manual, makes the mean declination 12°50' E.

I begin at the cor of Ts 22 & 23 N. Rs 35 & 36 W which is a post, mkd & witnessed as described by Mr Chambers.
Thence I run
North, betu secs 31 & 36.
descend gradually.
27.00 To foot of range. & over low foot hills.
40.00 Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24 x 24 x 12 ins N & S of cor 4 ft dist & raise a mound of earth 4 ft base 2 ft high over deposit. In S pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on West face.
Note:- See E Bdy T 21 N. R 38 W.
53.00 Road to Whitman, bears NW & SE.
75.00 Same road, bears NE & SW.
80.00 Deposit a brick 12 ins in the ground for cor of secs 25. 30. 31 & 36. dig pits 24 x 24 x 12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high over deposit. In SE. pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd
T 23 N S 30. on NE.
R 35 W S 31. on SE.
S 36. on SW. and
R 36 W S 25., on NW faces. with 1 notch on S & 5. on Nedges.
Note:- See E. Bdy. T. 21 N., R 38 W.
Land. broken prairie.
Soil sandy: 3rd rate.

E. Bdy of T. 23 N., R 36 W. 6th Om.

Chains.

North, betu secs 25 & 30.
over dry valley.
20.00 Leave valley & enter hills: bear S. 80° W & NE.
ascend abruptly: & over chop-hills.
40.00 Deposit a brick 12 ins in the ground for ¼ sec cor dig pits 24 x 24 x 12 ins N & S of cor 4 ft dist & raise a mound of earth 4 ft base 2 ft high over deposit. In S. pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on W face.
41.00 Summit: descend.
80.00 Set an oak post 3 ft long. 3 x 4 ins. with a brick 24 ins in the ground for cor of secs 19. 24. 25. & 30 mkd T 23 N S 19. on NE
R 35 W S 30. on SE.
S 25. on SW. and
R 36 W. S 24. on NW faces. with 2 notches on S & 4 on Nedges. dig pits 24 x 24 x 12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high West of corner.
Note:- See E. Bdy. T. 21 N. R. 38 W.
Land. broken prairie.
Soil. sandy: 3rd rate.

North, betu secs 19 & 24.
over undulating ground.
3.05 Road to Whitman, bears N 10° W & SE.
26.00 Enter hills
40.00 Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24 x 24 x 12 ins N & S of cor 4 ft dist & raise a mound of earth 4 ft base 2 ft high over deposit. In S pit drive an oak stake 2 ft long 2 ins square. 12 ins in the ground mkd ¼ S. on West face
80.00 Deposit a brick 12 ins in the ground for cor of secs 13. 18. 19. & 24. dig pits 24 x 24 x 12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high over deposit. In SE pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd
T 23 N S 18. on NE.
R 35 W S 19. on SE.

E. Bdy. T. 23 N., R. 36 W.

Chains

S 24 on SW. and
R 36 W S 13. on NW faces. with 3
notches on N & S edges.
Land broken prairie.
Soil sandy: 3rd rate.

North, betn secs 13 & 18
over chopphills.

28.90 Road to Whitman. bears SE & NW.
34.00 Leave hills & enter Cherry Valley, bears E & W.
40.00 Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24 x 24 x 12 ins N & S of cor 4 ft dist raise a mound of earth 4 ft base 2 ft high over deposit. In S pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on West face.
53.04 Local road, bears E & W.
59.00 Leave Cherry Valley & enter hills ascend abruptly.
66.00 Sod house of Geo Moran bears S. 60½ E.
79.00 Summit: descend.
80.00 Set an oak post 3 ft long 3 x 4 ins with a brick 24 ins in the ground for cor of secs 7, 12, 13, & 18 mkd.
T 23 N S 7. on NE.
R 35 W S 18. on SE.
S 13. on SW. and
R 36 W S 12. on NW faces with 2 notches on N & 4 on S edges. dig pits 24 x 24 x 12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high West of corner.
Land. 25 chs level land in Cherry Valley. balance broken.
Soil. sandy: ~~2nd~~ 3rd rates.

North, betn secs 7 & 12.
in hills.

29.00 Foot of N slope of ridge, bears E & W. & over low rough chop-hills
40.00 Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24 x 24 x 12 ins N & S of cor 4 ft dist & raise a mound of earth 4 ft base 2 ft high over deposit. In S pit drive an oak stake 2 ft long 2 ins square

E. Bdy T. 23 N., R. 36 W. 6th P.M.

Chains

12 ins in the ground mkd ¼ S., on W face.
72.06 Wire fence, bears S. 84° 25' E & reverse.
80.00 Deposit a brick 12 ins in the ground for cor of secs 1, 6, 7, & 12. dig pits 24 x 24 x 12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high over deposit. In SE pit drive an oak stake 2 ft long. 2 ins square 12 ins in the ground mkd
T 23 N S 6. on NE
R 35 W S 7. on SE.
S 12. on SW and
R 36 W. S 1. on NW faces, with 5 notches on S & 1 on N edges.
Land. broken prairie.
Soil sandy: 3rd rate.

North. betn secs 1 & 6.
over low chop-hills.

40.00 Deposit a brick 12 ins in the ground, for ¼ sec corner. dig pits 24 x 24 x 12 ins N & S of cor 4 ft dist raise a mound of earth 4 ft base 2 ft high over deposit. In S pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on West face.
42.00 Break in hills: S & W.
72.00 Summit: descend.
80.00 Set an oak post 3 ft long 3 x 4 ins with a brick 24 ins in the ground for the cor of Ts. 23 & 24 N., Rs 35 & 36. W., mkd.
T. 24 N. S. 31. on NE.
R. 35 W. S. 6. on SE.
T. 23 N. S. 1. on SW. and
R. 36 W. S. 36. on NW faces. with 6 notches on each edge. dig pits 24 x 24 x 12 ins on each line N. E. & W. 4 ft & S. of post 8 ft dist & raise a mound of earth 5 ft base 2½ ft high South of corner.
Land. broken prairie.
Soil. sandy: 3rd rate.
July 2nd 1895.

Chains

Through sec 1. West. on the tangent.

40.00 N. 0¼ lks from the tangent set temp ¼ sec cor.

80.00 " 1 " " " " " " Cor secs 1.2.35 & 36.

Through Sec 2.

S. 89°59' W. on the tangent.

40.00 N. 2½ lks from the tangent set temp ¼ sec cor.

80.00 " 3½ " " " " " " Cor secs 2.3.34 & 35.

Through Sec 3.

S. 89°58' W. on the tangent.

40.00 N 6 lks from the tangent set temp ¼ sec cor.

80.00 " 8¼ " " " " " " cor secs 3.4.33 & 34.

Through Sec 4.

S. 89°58' W. on the tangent.

40.00 N 11 lks from the tangent set temp ¼ sec cor.

80.00 " 14 " " " " " " Cor secs 4.5.32 & 33.

Through Sec 5.

S. 89°57' W. on the tangent.

40.00 N. 18¼ lks from the tangent set temp ¼ sec cor.

80.00 " 23 " " " " " " cor secs 5.6.31 & 32

Through Sec 6.

S. 89°56' W. on the tangent.

40.00 N. 27½ lks from the tangent set temp ¼ sec cor.

82.04 " 33 " " " " " " Cor of Tp. which falls 50 lks N of the cor of To. 23 & 24 N., Rs 36 & 37 W.

Therefore the true return course is N. 89°56' E. and the permanent corners will be set S. from the random line by offsets decreasing 4⅙ lks per half mile.

Therefore from the cor of To 23 & 24 N. Rs 36 & 37 W. which is a post. mkd & witnessed as described by Mr Alt. I run

N. 89°56' E. betn secs 6 & 31.

over chop-hills.

42.04 Deposit a brick 12 ins in the ground for ¼ sec

Chains.

cor. dig pits 24 x 24 x 12 ins E & W of cor 4 ft dist raise a mound of earth 4 ft base 2 ft high over deposit. In E pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on North face.

63.54 Road to Whitman, bears N & S.

82.04 Deposit a brick 12 ins in the ground for cor of secs 5. 6. 31. & 32. dig pits 24 x 24 x 12 ins in each sec 5 ft dist raise a mound of earth 5 ft base 2½ ft high over deposit. In SE pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd

T 24 N S 32. on NE.
R 36 W S 5. on SE.
T 23 N S 6. on SW. and
S 31. on NW faces with 1 notch on W. & 5 on E edges.

Land. broken prairie.
Soil. sandy: 3rd rate.

N. 89°56' E. betn secs 5 & 32.

40.00 Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24 x 24 x 12 ins E & W of cor 4 ft dist raise a mound of earth 4 ft base 2 ft high over deposit. In E pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on North face

80.00 Set an oak post 3 ft long 3 x 4 ins. with a brick 24 ins in the ground for the cor of secs 4. 5. 32. & 33. mkd.

T 24 N S 33. on NE.
R 36 W S 4. on SE.
T 23 N S 5. on SW. and
S 32. on NW faces. with 2 notches on W. & 4 on E edges. dig pits 24 x 24 x 12 ins in each sec 5 ft dist raise a mound of earth 5 ft base 2½ ft high N of cor.

Land. broken prairie.
Soil. sandy: 3rd rate.

Chains

N. 89°56' E. betn secs 4 & 33.
over chop-hills.

26.25 Wire fence bears N 2° E. & reverse.

40.00 Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24x24x12 ins E & W of cor 4 ft dist raise a mound of earth 4 ft base 2 ft high over deposit. In E pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on North face.

46.00 Break in hills. N W & S..

80.00 Deposit a brick 12 ins in the ground for cor of secs 3. 4. 33. & 34. dig pits 24x24x12 ins in each sec 5 ft dist raise a mound of earth 5 ft base 2½ ft high over deposit. In SE pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd T 24 N S 34. on NE.
R 36 W. S 3. on SE.
T 23 N S 4. on SW. and
S 33. on NW faces with 3 notches on E & W. edges
Land. rough broken prairie.
Soil sandy; 3rd rate.

N. 89°56' E. betn secs 3 & 34.
in chop-hills.

40.00 Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24x24x12 ins E & W of cor 4 ft dist raise a mound of earth 4 ft base 2 ft high over deposit. In E pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on North face.

50.00 Set an oak post 3 ft long 3x4 ~~ins with~~ a brick 24 ins in the ground for cor of secs 2. 3. 34 & 35. mkd
T 24 N S 35. on NE.
R 36 W S 2 on SE.
T 23 N S 3. on SW. and
S 34. on NW faces with 4 notches on W. & 2 on E edges. dig pits 24x24x12 ins in each sec 5 ft dist raise a mound of

Chains.

earth 5 ft base 2½ ft high West of corner
Land. broken prairie.
Soil. sandy; 3rd rate.

N. 89°56' E. betn secs 2 & 35.
in chop-hills.

17.00 Summit: descend.

40.00 Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24x24x12 ins E & W of cor 4 ft dist raise a mound of earth 4 ft base 2 ft high over deposit. In E pit drive an oak stake 2 ft long. 2 ins square 12 ins in the ground mkd ¼ S., on North face.

53.24 Local road, bears NW & SE. in pass.

60.00 Ascend.

80.00 Deposit a brick 12 ins in the ground for cor of secs 1. 2. 35. & 36. dig pits 24x24x12 ins in each sec 5 ft dist raise a mound of earth 5 ft base 2½ ft high over deposit. In SE pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground. mkd
T 24 N S 36. on NE.
R 36 W S 1. on SE.
T 23 N S 2. on SW. and
S 35. on NW faces. with 5 notches on W. & 1 on E edges.
Land. broken prairie.
Soil. sandy; 3rd rate.

N. 89°56' E. betn secs 1 & 36.
over hilly ground.

5.00 Summit: descend.

12.00 Narrow break, or pass through hills; N & S; ascend.

30.00 Summit; & along ridge; bears E & W.

40.00 Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24x24x12 ins E & W of cor 4 ft dist raise a mound of earth 4 ft base 2 ft high over deposit. In E pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on N face.

N. Bdy T. 23 N. R 36 W.

Chains	
47.00	Bottom of large depression, 75 ft deep; grassed over.
80.00	The cor of Ts 23 & 24 N., Rs 35 & 36 W.

Land: rough, broken prairie.
Soil: sandy; 3rd rate.

July 3 1895.

Boundaries of T 23 N. R. 36 W.
Latitudes, departures, and closing errors.

Line designated	True bearing	Distance chs	Latitudes N.	Latitudes S.	Departures E.	Departures W.
S. Bdy.	S. 89° 50' W.	481.70		1.40		481.70
W. "	North	480.00	480.00			
N. "	N. 89° 56' E	482.04	.56		482.04	
E. "	South	480.00		480.		
					.65	
Comp'ds.			480.56	481.40	482.69	481.70
				480.56	481.70	

Error in Lat. - - - .84, Dep. .99

E. Bdy T. 24 N., R 36 W., 6th P.M.

Chains	
	N. betw secs 31 & 36.
	descend N slope of ridge; extends E & W.
	(I note the magnetic bearing of meridian at 8h 30m A.M. central standard time, N 12° 55' W which corrected by Table G. in Manual, gives the mean magnetic declination 12° 49' E.)
14.00	Narrow pass; bears NW & SE.; ascend.
40.00	Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24 x 24 x 12 ins N & S of cor 4 ft dist & raise a mound of earth 4 ft base 2 ft high over deposit. In S pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S. on W. face
	Note:- See E. Bdy. T. 21 N., R. 38 W.
72.00	Trail in pass, bears E & W.
80.00	Set an oak post 3 ft long 3 x 4 ins with a brick 24 ins in the ground for cor of secs 25. 30. [illegible] & 36. mkd
	T 24 N S 30. on NE.
	R 35 W S 31. on SE.
	S 36. on SW. and
	R 36 W S 25. on NW faces. with

1 notch on S & 5 on N edges. dig pits 24 x 24 x 12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high West of corner.
Note:- See E. Bdy. T. 21 N. R 38 W.

Land. broken prairie.
Soil; sandy; 3rd rate.

	North betw secs 25 & 30.
	over ridge.
32.00	Summit: descend.
40.00	Deposit a brick 12 ins in the ground for ¼ sec cor. dig pits 24 x 24 x 12 ins. N & S of cor 4 ft dist & raise a mound of earth 4 ft base 2 ft high. over deposit. In S pit drive an oak stake 2 ft long. 2 ins square 12 ins in the ground mkd ¼ S., on West face.
	Note:- See E. Bdy. T. 21 N. R. 38 W.
70.00	Foot of ridge & enter narrow valley. E & W.

E. Bdy. T. 24 N., R. 36 W.

Chains.

73.74 Road. Weir to Whitman.
77.77 Wire fence, bears N. 75°15' W. & reverse.
77.87 Road: along fence.
80.00 Set an oak post 3 ft long. 3x4 ins. with a brick 24 ins in the ground for the cor of secs 19. 24. 25. & 30. mkd.

T24NS19. on NE.
R35W. S30. on SE.
S25. on SW. and
R36WS24. on NW faces. with 2 notches on S. and 4. on N edges. dig pits 24x24x12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high West of cor.
Land. broken prairie.
Soil: sandy: 3rd rate.

North, betn secs 19 & 24.

1.45 Center of Track. Burlington & Missouri river rail-road bears N. 76° 31' W & reverse - at 6 chs E. curves to left.
2.14 Telegraph line along railroad: ascend moderately.
40.00 Deposit a charred stake 12 ins in the ground for ¼ sec cor. dig pits 24x24x12 ins N & S of cor 4 ft dist & raise a mound of earth 4 ft base 2 ft high over deposit. In S pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼ S., on W. face.
80.00 Set an oak ~~post 3~~ ft long. 3x4 ins with a ~~charred~~ stake 24 ins in the ground for cor of secs 13. 18. 19. & 24. mkd.

T24NS18. on NE.
R35WS19. on SE.
S24. on SW. and
R36WS13. on NW faces. with 3 notches on E & S. edges. dig pits 24x24x12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high West of corner.
Land. broken prairie.
Soil. sandy: 3rd rate.

E. Bdy. T. 24 N., R. 36 W., 6th P.M.

Chains

North, betn secs 13 & 18.
over chop-hills.

40.00 Deposit a charred stake 12 ins in the ground for ¼ sec cor. dig pits 24x24x12 ins, N & S of cor 4 ft dist & raise a mound of earth 4 ft base 2 ft high over deposit. In S pit. drive an oak stake 2 ft long. 2 ins square 12 ins in the ground mkd ¼ S., on West face.
47.59 Sod house of D. F. Fording. bears N. 79° W.
" " " G. D. Shepardson. " N 6° 47' W.
54.77 Local road. bears E & W; & enter dry valley.
67.40 Road: bears N 80° W. & reverse.
78.00 Leave bottom & enter hills; bear E & W. ascend abruptly.
80.00 Set an oak post 3 ft long. 3x4 ins. with a charred stake 24 ins in the ground for cor of secs 7. 12. 13. & 18. mkd

T24NS7. on NE.
R35WS18. on SE.
S13. on SW. and
R36WS12 on NW. faces. with 2 notches on N & 4 on S edges. dig pits 24x24x12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high West of corner.
Land. 20 chs dry valley, balance broken ridges.
Soil. sandy: 3rd rate.

North, betn secs 7 & 12.
ascend abruptly & over rough chop-hills.

1.42 Sod house of D. F. Fording bears S. 57° 50' W.
" " " G. D. Shepardson " S. 24° 20' W.
" " " S. 66° E.
40.00 Deposit a charred stake 12 ins in the ground for ¼ sec cor. dig pits 24x24x12 ins N & S of cor 4 ft dist & raise a mound of earth 4 ft base 2 ft high over deposit. In S pit drive an oak 2 ft long. 2 ins square 12 ins in the ground mkd ¼ S., on West face.
54.76 Local road, bears E & W.; through break in ridge.
80.00 Set an oak post 3 ft long 3x4 ins. with a

E. Bdy. T. 24 N., R. 36 W. 6th P.M.

chains

charred stake 24 ins in the ground for cor of secs 1. 6. 7. & 12, mkd
T24NS6. on NE.
R35WS7. on SE.
S12. on SW. and
R36WS1. on NW faces. with 1 notch on N & 5 on S edges. dig pits 24x24x12 ins in each sec 5 ft dist & raise a mound of earth 5 ft base 2½ ft high West of corner.
Land. broken prairie.
Soil. sandy: 3rd rate.

North, betn secs 1 & 6.
descend gradually.
11.85 Local road; bears NW & SE. in edge of valley.
17.73 Road: bears E & W.
33.57 Sod house of bears S. 82°40' E.
40.00 Deposit a charred stake 12 ins in the ground for ¼ sec cor. dig pits 24x24x12 ins. N & S of cor 4 ft dist. & raise a mound of earth 4 ft base 2 ft high over deposit. In S pit drive an oak stake 2 ft long 2 ins square 12 ins in the ground mkd ¼S., on West face.
47.00 Leave bottom, & enter hills; bears E & W.
51.67 Wire fence, bears N. 31°40' W. & reverse.
87.00 Enter valley; bears E & W.
91.00 Road to Whitman; bears E & W.
91.93 Intersect the 6th Standard Parallel. 20.08 chs S. 89°42' E. of the Standard Corner of Secs 31 & 32. T25N, R35W.
Set an oak post 3 ft long. 3x4 ins. with a charred stake 24 ins in the ground for cor of secs 1 & 6. T24N. Rs 35 & 36 W. marked.
CCT24N, on S.
R35WS6. on E. and
R36WS1, on W. faces. with 6 grooves on E. S. & W faces. dig pits 24x24x12 ins. crosswise on each line. E & W. 4 ft & S of post 8 ft dist & raise a mound of earth 5 ft base 2½ ft high South of corner.
40 chs Valley. 2nd rate, balance chop hills: 3rd rate. July 6 1895

For Affidavits see class of Exhibit of R. 35 W.

General Land Office • Original Field Notes

Book Number

774

W.W. Alt - East & North bdy. T 23 N, East bdy. T 24 N, R 36 W

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.