General Land Office • Original Field Notes

Book Number

775

W.W. Alt - East & North boundaries T 23 N, R 38 W

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.

107

Duplicate X

(4—679.)

108

Received with Letter from W. W. Alt, U.S. Surveyor, dated Sept 13, 1896. 98725—'96

FIELD NOTES

OF THE SURVEY OF

East and North Boundaries

of

Township 23 N., Range 38 W.,

Of the 6th Principal Meridian.

State of Nebraska

AS SURVEYED BY

William W. Alt, United States ~~Deputy~~ Surveyor,

Under his Contract ~~No.~~ , *dated* December 26, 1894

Survey commenced November 14, 1895.

Survey completed November 15, 1895.

(1014—2,500.)

Names and Duties of Assistants.

Clarence P. Haggard, Chainman
Sidney Blout, Chainman
Theodore Neeland, Flagman
James C. Rosengren, Mounsman

INDEX DIAGRAM.

Exteriors

Township 23 . Range 38W

7	8	9	10	11	12	
6	5	4	3	2	1	5
7	8	9	10	11	12	4
18	17	16	15	14	13	4
19	20	21	22	23	24	3
30	29	28	27	26	25	2
31	32	33	34	35	36	1

Meanders Page

6—151

32.0 0 Top of ascent 75 ft above valley, thence over rolling
over broken ground.

Preliminary Oaths of Assistants.

We, ... and .....
do solemnly swear that we will well and faithfully execute the duties of chainmen; that we will level the chain upon even and uneven ground, and plumb the tally pins either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true lengths of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us in the survey of
.....

..... , *Chainman.*

..... , *Chainman.*

Subscribed and sworn to before me this .....
day of ....., 189 .

SEAL

.....

.....

We, ... and .....
do solemnly swear that we will well and truly perform the duties of moundmen in the establishment of corners, according to the instructions given us, to the best of our skill and ability, in the survey of .....
.....

..... , *Moundman.*

..... , *Moundman.*

Subscribed and sworn to before me this .....
day of ....., 189 .

SEAL

.....

.....

We, ... and .....
do solemnly swear that we will well and truly perform the duties of axmen in the establishment of corners and other duties, according to instructions given us, to the best of our skill and ability, in the survey of
.....

..... , *Axman.*

..... , *Axman.*

Subscribed and sworn to before me this .....
day of ....., 189 .

SEAL

.....

.....

I, ..., do solemnly swear that I will well and truly perform the duties of flagman according to instructions given me, to the best of my skill and ability in the survey of .....

..... , *Flagman.*

Subscribed and sworn to before me this .....
day of ....., 189 .

SEAL

.....

.....

For Brackett's oaths see East boundary T. 23 N. R. 38 W. 21 & 22 N.

East boundary T. 23 N. R. 38 W.

Chains

I commence at the cor of Tps. 22 & 23 N., Rs. 37 and 38 W., which is an oak post 1 ft above ground, and 4 ins sq.: marked
T 23 N S 31, on NE.
R 37 W S 6. on SE.
T 22 N S 1. on SW. and
R 38 W S 36. on NW. faces. with 6 notches on each edge; and pits 24 x 24 x 12 ins. dug on each line N., E., and W. of post 4 ft, and S. of post 8 ft dist. and a mound of earth 5 ft base 2½ ft high, raised S. of cor.

I observe Polaris at western elongation, at 4.13 central standard time, on the morning of November 14. 1895, and mark the line thus determined by point in stake driven N. of cor. At 8 a.m.; I lay off azimuth of Polaris, 1°41' to the east. and mark the true meridian thus determined by a tack in stake firmly driven in the ground. 5 chs. North of corner.

The magnetic bearing of the true meridian at 8 am. is N. 13°02' W.; which reduced by the table on page 100 of the Manual gives the mean mag. decl. 12°59' E.

From the Tp. Cor.; I run

North. bet. secs. 31 and 36.
Over rolling ground along top of range.
5.00 Begin descent along N.E. slope.
20.00 Bottom of descent, thence over rolling ground in west end of valley.
34.50 Trail: S. 80° E.; N. 80° W.; thence over broken ground.
40.00 Deposit a charred stake 12 ins in the ground for ¼ sec. cor.; dug pits 18 x 18 x 12 ins. N. & S. of cor. 4 ft. dist. and raised a mound of earth. 3½ ft base 1½ ft high, over deposit.
In S. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground. marked
¼ S. on W. face.
49.00 Begin abrupt ascent along S. slope range.
52.00 Top of ascent 75 ft above valley, thence over rolling ground.

Chains.	
	ground, descending along N.E. slope.
80.00	Deposit a charred stake 12 ins in the ground for cor. of secs. 25. 30. 31. and 36.; dug pits 18 x 18 x 12 ins in each sec. 4 ft dist., and raised a mound of earth 4 ft base 2 ft high over deposit.
	In S.E. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground, marked
	T 23 N S 30. on N.E.
	R 37 W S 31. on S.E.
	S 36. on S.W. and
	R 38 W S 25. on N.W. faces. with 1 notch on S. and 5 notches on N. edges.
	Land. rolling sand hills.
	Soil. sandy: 3rd rate.
	Bunch and sand grass.
	North, bet. secs. 25 and 30.
	Descend over rolling ground sloping to N.E.
18.00	Bottom of descent. 40 ft below cor.; ascend along S.W. slope of range.
39.00	Top of ascent on W. face of range.
40.00	Deposit a charred stake 12 ins in the ground for ¼ sec. cor.; dug pits 18 x 18 x 12 ins N & S. of cor. 4 ft dist. and raised a mound of earth 3½ ft base 1½ ft high over deposit.
	In S. pit, drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground. marked
	¼ S, on W. face.
	Ascend along S.W. face "Lookout Knob"
58.10	Top of ascent 150 ft above valley, descend along N.W. slope.
80.00	Set an oak post 3 ft long 4 ins sq. with a charred stake 24 ins in the ground for cor of secs 19. 24. 25. and 30., marked
	T 23 N S 19. on N.E.
	R 37 W S 30. on S.E.
	S 25. on S.W. and
	R 38 W S 24. on N.W. faces, with 2 notches on S. and 4 on N. edges; dug pits 18 x 18 x 12 ins in each sec 5½ ft dist. and raised a mound of earth

Chains	
	4 ft base 2 ft high W. of corner.
	Land rolling sand hills.
	Soil. sandy, 3rd rate.
	Bunch grass.
	North, bet. secs. 19. and 24.
	Descend along N. slope.
17.00	Bottom descent.
19.00	Foot of range of sand hills. course E. and W. ascend abruptly.
25.00	Top of ascent. 75 ft.; thence along E. face.
32.00	Top of range, course E & W.; descend along N.E. slope.
40.00	Deposit a charred stake 12 ins in the ground for ¼ sec. cor.; dug pits 18 x 18 x 12 ins N & S of cor 4 ft dist. and raised a mound of earth 3½ ft base 1½ ft high over deposit.
	In S. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground, marked
	¼ S, on W. face.
54.85	Trail: course S. 80° E., N. 80° W.
56.00	Enter basin like valley: E. and W.
73.10	Trail to Hyannis.; Course E. & W.
80.00	Deposit a charred stake 12 ins in the ground for cor of secs 13. 18. 19. and 24.; dug pits 18 x 18 x 12 ins in each sec. 4 ft. dist. and raised a mound of earth 4 ft base 2 ft high, over deposit.
	In S.E. pit drove an oak stake 2 ft long, 2 ins sq. 12 ins in the ground, marked
	T 23 N S 18. on N.E.
	R 37 W S 19. on S.E.
	S 24. on S.W. and
	R 38 W S 13. on N.W. faces, with 3 notches on N. and S. edges.
	Land. level valley and rolling sand hills.
	Soil. sandy: 3rd rate.
	Sand and bunch grass.

E. boundary T. 23 N., R. 38 W. continued.

Chains.

North, bet. secs. 13 and 18.
ascend gradually along S. W. slope.

20.00 Top of ascent - 50 ft above cor. on W. face bluffs. or range; ascend slightly.

38.00 Top of range: 75 ft above valley; descend along N. W. slope.

40.00 Deposit a charred stake 12 ins in the ground for ¼ sec. cor. dug pits 18x18x12 ins. N. & S. of cor 4 ft dist. and raised a mound of earth 3½ ft base 1½ ft high over deposit. In S. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground. marked
¼ S, on W. face.

65.00 Bottom descent; enter basin like valley: Course E. & W.

76.00 Trail to Hyannis; course N. 80° E.; S. 80° W.

80.00 Set an oak post 3 ft long 4 ins. sq. with a charred stake 24 ins. in the ground. for cor. of secs 7, 12, 13. and 18; marked.
T 23 N S 7. on NE.
R 37 W S 18. on SE.
S 13. on SW. and
R 38 W S 12. on NW. faces. with 4 notches on S. and 2 on N. edges.: dug pits 18x18x12 ins. in each sec 5½ ft dist. and raised a mound of earth 4 ft base 2 ft high W. of corner.
Land. level. and rolling sand hills.
Soil. sandy: 3rd rate.
Sand grass and bunch grass.

North, bet. secs. 7 and 12.
Over level land.

8.00 Foot of range of sand hills; course N. 70° E.; S. 70° W. ascend abruptly.

16.50 Top of abrupt ascent 75 ft.; thence ascend along S. face of range.

32.00 Top of range, 100 ft above valley; Course E. & W. thence over broken ground.

40.00 Deposit a charred stake 12 ins in the ground for ¼ sec. cor.; dug pits 18x18x12 ins N. & S. of cor. 4 ft dist. and raised a mound of earth 3½ ft base

E. boundary T. 23 N., R. 38 W, continued.

Chains

1½ ft high over deposit. In S. pit. drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground. marked
¼ S, on W. face.

65.00 Bottom of descent, in ravine or pass. Course E. and W.

66.00 Begin abrupt ascent along S.E. slope of range.

80.00 Deposit a charred stake 12 ins in the ground. for cor. of secs. 1. 6. 7. and 12.; dug pits 18x18x12 ins in each sec. 4 ft dist, and raised a mound of earth 4 ft base 2 ft high, over deposit. In SE. pit. drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground. marked
T 23 N S 6. on NE.
R 37 W S 7. on SE.
S 12. on SW. and
R 38 W S 1. on NW. faces. with 5 notches on S. and 1 notch on N. edges.
Land. rolling and broken sand hills.
Soil. sandy; 3rd rate.
Sand grass, and bunch grass.

North, bet. secs. 1 and 6.
Ascend along S.E face of range.

17.00 Top of ascent on E. face of sand bluff. 150 ft above valley; Course E. and N.; descend along N. slope over broken ground.

40.00 Deposit a charred stake 12 ins in the ground for ¼ sec. cor. dug pits 18x18x12 ins N. & S. of cor. 4 ft dist.; and raised a mound of earth 3½ ft base 1½ ft high over deposit. In S. pit. drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground. marked
¼ S, on W. face.

47.00 Trail; course E. & W.; at bottom descent. ascend along S. slope.

66.00 Top of ascent 50 ft above valley; thence along N. face of range; over ridges and ravines

78.10 Descend from low ridge.

80.00 Set an oak post 3 ft. long. 4 ins sq. with charred stake 24 ins in the ground. for cor. of Tps. 23 and 24 N., Rs. 37 and 38 W. marked
T 24 N S 31. on NE.

E. boundary T. 23 N., R. 38 W. concluded.

Chains

R 37 W S 6. on SE.
T 23 N S 1. on SW. and
R 38 W S 36. on NW. faces, with 6 notches on each edge.; dug pits 24 x 24 x 12 ins. on each line N.E. & W. 4 ft., and S. of post 8 ft dist. and raised a mound of earth 5 ft base 2½ ft high S. of cor.
Land. rolling and broken sand hills.
Soil, sandy: 3rd rate.
Bunch grass.

November 14, 1895.

End

N bdry T. 23 N

At the corner of Tps. 23 and 24 N. Rs. 37 and 38 W. I turn an angle of 90° from the range line, to the west; and run

Through Sec. 1.

West, on the tangent.

40.00 N. ½ lk. from the tangent set temp ¼ sec cor.
80.00 N. 1 lk " " " " Cor. secs 1. 2. 35. & 36.

Through Sec. 2.

S. 89° 59' W., on the tangent.

40.00 N. 2½ lks. from the tangent set temp ¼ sec cor.
80.00 N. 3½ lks. " " " " cor of secs 2. 3. 34, and 35.

Through Sec. 3.

S. 89° 58' W., on the tangent.

40.00 N. 6 lks. from the tangent set temp ¼ sec. cor.
80.00 N. 8½ lks. " " " " cor. of secs. 3. 4. 33. and 34.

Through Sec. 4.

S. 89° 58' W., on the tangent.

40.00 N. 11 lks. from the tangent. set temp ¼ sec cor.
80.00 N. 14 lks. " " " " Cor. of secs. 4. 5. 32. and 33.

N. boundary T. 23 N., R. 38 W., continued.

Chains

Through Sec. 5.

S. 89° 57' W., on the tangent.

40.00 N. 18½ lks. from the tangent. set temp ¼ sec cor.
80.00 N. 23 lks. " " " " Cor of secs 5. 6. 31. and 32.

Through Sec. 6.

S. 89° 56' W., on the tangent.

40.00 N. 27½ lks from the tangent set temp ¼ sec cor.
80.00 N. 33 " " " " " cor of Tps.

which falls 174 lks. S. of cor. of Tps. 23 and 24 N., Rs. 38 and 39 W.

Therefore the true course is S. 89° 48' E., and the permanent corners will be set N. from the random line by offsets decreasing 14½ lks. per half mile.

Boundaries of T. 23 N., R. 38 W.
Latitudes, Departures, and closing errors.

Lines Designated	True Bearing	Distance	Latitude N.	Latitude S.	Departure E.	Departure W.
		chs.	chs.	chs.	chs.	chs.
South boundary	N. 89° 51' W.	482.26	1.26			482.26
W. "	North	480.00	480.00			
N. "	S. 89° 48' E.	481.00		1.74	481.00	
E. "	South.	480.00		480.00		
Convergency					0.65	
Totals			481.26	481.74	481.65	482.26
				481.26		481.65
Error in Latitude				0.48		
Error in Departure						0.61

Chains

Start

Thence I run
S. 89° 48' E., bet. secs. 6 and 31.
Over level land.

1.35 Wire fence parallel to railroad.
11.05 Center of track of Burlington and Missouri River Railroad in Nebraska: Course N. 80° 02' E., S. 80° 02' W.
14.34 Telegraph line, parallel to railroad.
20.10 Wire fence, parallel to railroad.
35.44 Wire fence, N. and S.

N. boundary T. 23 N., R. 38 W., continued.

Chains

39.52 Intersect W. boundary, townsite of Hyannis, at a point S. 1°10' W., 13.90 chs dist. from the N.W. cor of Townsite, which is a Limestone 3x2x2 ins above ground. Deposit a marked stone 12 ins in the ground for Closing Corner. dug pits 18x18x12 ins. S. and W. of cor. 4 ft dist. and raised a mound of earth 3½ ft base 1½ ft high, over deposit.
In W. pit drove an oak stake 2 ft long 2 ins sq. 12 ins. in the ground, marked
CC. on W. and
H. on E. faces.

Thence I run on a blank line through Townsite

41.00 Point for ¼ cor falls in Townsite.

81.00 Point for cor of secs 5. 6. 31, and 32. falls in Townsite.
Land. level - and rolling sand hills.
Soil. sandy: 2nd and 3rd rates.
Prairie. and bunch grass.

S. 89°48' E. bet. secs. 5 and 32.
On blank line through Townsite of Hyannis.

18.95 Intersect E. boundary of Townsite of Hyannis at a point S. 1°16' W. 12.51 chs. dist. from the N.E. cor. of Townsite, which is a Limestone 4x2x2 ins above ground. Deposit a marked stone 12 ins in the ground for closing corner. dug pits 18x18x12 ins S. and W. of cor. 4 ft dist. and raised a mound of earth 3½ ft base 1½ ft high. over deposit.
In W. pit. drove an oak stake 2 ft long 2 ins sq 12 ins in the ground, marked
CC. on W. and
R.S.P. (for Russell S. Perkins) on E. faces.

ascend gently over rolling ground along S. face of range.

20.00 Top of ascent 20 ft above cor; thence over rolling ground.

40.00 Deposit a charred stake 12 ins in the ground for

N. boundary T. 23 N., R. 38 W. continued.

Chains

¼ sec. cor. dug pits 18x18x12 ins. E. and W. of cor. 4 ft dist. and raised a mound of earth 3½ ft base 1½ ft high, over deposit.
In E. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground. marked
¼ S., on N. face.

41.00 Descend over broken ground.

43.00 Bottom descent in ravine or pass. 30 ft deep.
ascend over low bluffs and ridges.

60.00 Top of ascent 40 ft above ravine; thence along top of range over broken ground.

64.00 Trail; course N. and S.

80.00 Set an oak post 3 ft long 4 ins sq. with chared stake 24 ins in the ground. for cor of secs 4. 5. 32. and 33.; marked
T 24 N S 33. on NE.
R 38 W S 4. on SE
T 23 N S 5. on SW. and
S 32. on NW. faces with 4 notches on E. and 2 on W. edges. dug pits 18x18x12 ins. in each sec. 5½ ft dist. and raised a mound of earth 4 ft base 2 ft high, W. of cor.
Land rolling sand hills.
Soil. sandy; 3rd rate.
Bunch grass.

S. 89°48' E. bet. secs 4. and 33.
Over rolling ground along top of range.

0.70 Descend along N.E. slope of ridge.

2.00 Bottom of descent in ravine 30 ft deep: Course NW. and SE.; ascend along W. slope over broken ground.

20.00 Top of ascent on high point of range. 100 ft above valley: thence descend along S.E. face; over rolling ground.

40.00 Deposit a charred stake 12 ins in the ground for ¼ sec. cor.: dug pits 18x18x12 ins. E. and W. of cor. 4 ft dist. and raised a mound of earth 3½ ft base 1½ ft high over deposit.
In E. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground, marked
¼ S. on N. face.

N. boundary T. 23 N. R. 38 W. continued.

chains

54.00 Begin descent over low bluffs and ridges.

80.00 Deposit a chained stake 12 ins in the ground for cor of secs. 3. 4. 33. and 34., dug pits 18x18x12 ins. in each sec 4 ft. dist. and raised a mound of earth 4 ft base 2 ft high over deposit.
In SE. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground, marked
T24N S34. on NE.
R38W S3. on SE.
T23N S4. on SW. and
S33. on NW faces. with 3 notches on E. and W. edges.
Land. rolling sand hills.
Soil. sandy; 3rd rate.
Bunch grass.

S. 89°48' E. bet. secs. 3 and 34.
Descend over rolling ground.

0.50 Trail: course N. and S.

3.00 Bottom descent 20 ft. below cor.; ascend gently over rolling ground along SW. slope.

23.00 Top of ascent 50 ft above cor.: thence over broken ground along S. face of low range.

40.00 Deposit a chained stake 12 ins in the ground for ¼ sec cor. dug pits 18x18x12 ins. E and W. of cor. 4 ft dist. and raised a mound of earth 3½ ft base 1½ ft high over deposit.
In E. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground, marked
¼ S., on N. face
Descend over rolling ground, along SE. face.

65.97 Wire fence. parallel to Railroad.

66.17 Telegraph line. parallel to Railroad.

67.18 Center of track of Burlington and Missouri River railroad, on 2° curve. Course N. 58°35' E., S 58°35' W.

68.43 Wire fence. parallel to railroad.

71.43 Trail. Hyannis to Whitman. Course N 66° E., S 66° W. thence through basin like land

80.00 Set an oak post 3 ft long 4 ins sq. with chained stake 24 ins in the ground for cor of secs 2. 3. 34. and

N. boundary T. 23 N. R. 38 W. continued

chains

35. marked
T24N S35. on NE.
R38W S2. on SE.
T23N S3. on SW. and
S34. on NW. faces. with 2 notches on E. and 4 on W. edges. dug pits 18x18x12 ins in each sec 5½ ft dist; and raised a mound of earth 4 ft base 2 ft high W. of cor.
Land. rolling sand hills.
Soil. sandy; 3rd rate.
Sand and bunchgrass.

S. 89°48' E. bet. secs 2 and 35.
Over level land, through basin.

10.00 Leave level land, ascend along W. slope bluffs or range.

39.00 Top of ascent 100 ft above corner; thence over rolling ground along N. face of range.

40.00 Deposit a chained stake 12 ins in the ground for ¼ sec cor. dug pits 18x18x12 ins. E. and W. of cor. 4 ft dist. and raised a mound of earth 3½ ft base 1½ ft high over deposit.
In E. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground, marked
¼ S., on N. face.

75.00 Begin abrupt descent along E. slope.

80.00 Deposit a chained stake 12 ins in the ground for cor of secs 1. 2. 35. and 36.; dug pits 18x18x12 ins in each sec 4 ft. dist. and raised a mound of earth 4 ft base 2 ft high over deposit.
In SE. pit drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground, marked
T24N S36. on NE.
R38W. S1. on SE.
T23N S2. on SW. and
S35. on NW. faces, with 1 notch on E. and 5 notches on W. edges.
Land. level, and rolling sand hills.
Soil. sandy; 3rd rate.
Sand and bunch grass.

N. boundary T. 23 N., R. 38 W., concluded.

Chains

S. 89°48' E. bet. secs 1 and 36.
Descend over broken ground.
6.00 Descend over rolling ground along E. slope.
19.00 Bottom descent, enter basin like valley. course N. and S.
33.00 Leave valley; N.W. and S.E. ascend over rolling ground.
40.00 Deposit a chained stake 12 ins in the ground for ¼ sec cor. dug pits 18x18x12 ins. E. & W. of cor 4 ft dist. and raised a mound of earth 3½ ft. base 1½ ft high over deposit.
In E. pit. drove an oak stake 2 ft long 2 ins sq. 12 ins in the ground. marked
¼ S., on N. face.
Ascend gently along W. slope foot hills.
59.00 Begin ascent along W. slope of range.
80.00 The cor. to Tps. 23 and 24 N., Rs. 37 and 38 W.
Land. level and rolling.
Soil. sandy; 3rd rate.
Brush and sand grass.
November 15 1895.

Esd

General Description

This township is very rough and broken consisting of a series of ranges of sand hills with a general course of E. and W.; between the ranges there are narrow valleys or basins which produce a good hay.
Land unfit for cultivation, but very good for grazing purposes. No timber of any description in township.

Willard H. Alt.
U. S. Deputy Surveyor.

November 15, 1895.

Final Oaths of Deputy Surveyors and their Assistants.

LIST OF NAMES.

A list of the names of the individuals employed by .....
....., United States Deputy Surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of .....
..... showing the respective capacities in which they acted:

....., *Chainman.*
....., *Chainman.*
....., *Moundman.*
....., *Moundman.*
....., *Axman.*
....., *Axman.*
....., *Flagman.*

FINAL OATH OF ASSISTANTS.

We hereby certify that we assisted .....
....., United States Deputy Surveyor, in surveying all those parts or portions of the .....
..... of the ..... base and ..... meridian, ... of ....., which are represented in the foregoing field notes as having been surveyed by him and under his direction: and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the United States Surveyor General for .....

....., *Chainman.*
....., *Chainman.*
....., *Moundman.*
....., *Moundman.*
....., *Axman.*
....., *Axman.*
....., *Flagman.*

Subscribed and sworn to before me this .....
day of ....., 189 .

SEAL

14/125

Final Oath of United States Deputy Surveyor.

I, ..., United States Deputy Surveyor, do solemnly swear that, in pursuance of instructions received from ....., United States Surveyor General for ....., bearing date of the ..... day of ....., 189 , I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States Surveyor General for ....., the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of .....

..... of the ..... base and ..... meridian, in the ..... of ....., which are represented in the foregoing field notes as having been surveyed by me, and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the United States Surveyor General for ..... and in the specific manner described in the field notes, and that the foregoing are the *true* field notes of such survey; and should any fraud be detected, I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

.....
United States Deputy Surveyor.

Subscribed by said ....., United States Deputy Surveyor, and sworn to before me this ..... day of ....., 189 .

SEAL

APPROVAL.

Commissioner of the General Land Office
Office of the ~~United States Surveyor General~~,
Washington D.C. April 30, 1897.

The foregoing field notes of the re survey of the East and North boundary lines of Township No. 23 North Range No. 38 West of the 6th principal Meridian State of Nebraska

..... executed by Willard W. Alt N.S. Surveyor under his Contract No. ....., dated December 26, 1894, having been critically examined, the necessary corrections and explanations made, the said field notes, and the re surveys they describe, are hereby approved.

Binger Hermann
~~United States Surveyor General~~.
Commissioner and ex officio Surveyor General for Nebraska

I certify that the foregoing transcript of the field notes of the above-described surveys ~~in~~ of the East and North boundary of T23N R38W, has been correctly copied from the original notes on file in this office.

Binger Hermann
~~United States Surveyor General~~.
Commissioner and ex officio Surveyor General for Nebraska.

126

1/32

... W., ascend over broken ground.

General Land Office • Original Field Notes

Book Number

775

W.W. Alt - East & North boundaries T 23 N, R 38 W

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.