General Land Office • Original Field Notes

Book Number

775

W.W. Alt - South bdy. T 23 N, North & East bdy. T 22 N, R 37 W

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.

12

Duplicate.

Ex Ck/RH 7-5-1900

13

4—679.

Rec'd with letter from W. W. Alt, U.S. Surveyor, dated April 30, 1900. 58498/1900

FIELD NOTES

OF THE SURVEY OF THE

South Boundary T. 23 N.
North Boundary T. 22 N.,
and the
East Boundary of
Township 22 North,
Range 37 West

Of the 6th Principal Meridian,
State of Nebraska

AS SURVEYED BY

Willard W. Alt, United States ~~Deputy~~ Surveyor,

Under his Contract ~~No.~~ ——, dated April 17, 1899

Survey commenced May 29, 1899

Survey completed June 2, 1899

6—151

NAMES AND DUTIES OF ASSISTANTS.

Arthur H. Nieling, Chainman.
Archie J. ~~Stratton~~, "
Eugene C. Paine, " Flagman
Daniel H. Templeton, " Moundsman

6—151

INDEX DIAGRAM.

Township 22, *Range* 37

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Meanders Page

6—151

PRELIMINARY OATHS OF ASSISTANTS.

WE, ... and .....
do solemnly swear that we will well and faithfully execute the duties of chainmen; that we will level the chain over even and uneven ground, and plumb the tally pins, either by sticking or dropping the same; that we will report the true distances to all notable objects, and the true lengths of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of

.....

....., *Chainman.*

....., *Chainman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

.....

.....

WE, ... and .....
do solemnly swear that we will well and truly perform the duties of moundmen in the establishment of corners, according to the instructions given us, to the best of our skill and ability, in the survey of

.....

....., *Moundman.*

....., *Moundman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

.....

.....

WE, ... and .....
do solemnly swear that we will well and truly perform the duties of axmen in the establishment of corners and other duties, according to instructions given us, to the best of our skill and ability, in the survey of

.....

....., *Axman.*

....., *Axman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

.....

.....

I, ..., do solemnly swear that I will well and truly perform the duties of flagman according to instructions given me, to the best of my skill and ability, in the survey of .....

....., *Flagman.*

Subscribed and sworn to before me this .....
day of ....., 189

SEAL

.....

.....

6—151

South Boundary T. 23 N. and
North Boundary T. 22 N., R. 37 W.

1/16

	Chains	
		Survey commenced May 29th 1899 and executed with an W. and L.E. Gurley Surveyor's Transit No. 12. the horizontal limb having two double verniers placed opposite to each other, reading to 1' of arc.
		I examine adjustment and place it in perfect adjustment – I also examine and adjust my chains to U.S. Standard tape –
		I begin at the corner of T. 22 and 23 N., R. 36 and 37 W., which is an Oak Post 4 inches square 12 ins. above ground, marked and witnessed as follows:
		T. 23 N.S. 31 ow N.E.
		R 36 W. S. 6 ow S.E.
		T. 22 N.S. 1 ow N.W. and
		R. 37 W.S. 36 ow N.W. faces, with 6 notches on each edge, with pits 24x24x12 ins on each line N, E, and W. 4 ft. dist and S of post 8 ft. dist with a flat mound S. of corner
		Drove a tack in corner post at 3:35 A.M. central standard time. I observe Polaris at eastern elongation in accordance with instructions in the manual, and mark the line thus determined by tack in stake North of Station
		At 7 A.M. I lay off azimuth of Polaris 1°39' to West and ~~mark~~ the true meridian thus determined by a tack in wooden peg firmly driven in ground 1.49 chs. North, the magnetic bearing of said true meridian is N. 13°00' W. which reduced by table on page 100 of the Manual, gives the mean magnetic declination 12°54' E.
		I turn an angle from true meridian of 90°11' from North to West and run S. 89°49' W on tangent through Sec 1
40.06		Old 1/4 cor. 1 link N. of tangent

South boundary T. 23 N. and
North boundary T. 22 N., R. 37 W.

chains	
80.00	N. 1 lk. from tangent set temp cor of secs. 1, 2, 35 and 36
	S 89° 48' W. on a tangent through sec. 2
0.11	Old cor. of secs. 1, 2, 35 and 36 – 2 lks. S. of random line
40.12	Old 1/4 Cor. 4 1/2 lks. S of random line
80.00	N. 3 1/2 lks from tangent – set temp cor of secs. 2, 3, 34 and 35
	S 89° 48' W. on tangent, through sec. 3
0.10	Old cor. of secs. 2, 3, 34 and 35 – 7 1/2 lks S. of random
40.00	Old 1/4 cor. 12 lks. S. of random
80.00	N. 8 1/4 lks from tangent, set temp cor. secs. 3 and 4
	S 89° 47' W. on tangent, through sec. 4
0.50	Old cor. of secs. 3, 4, 33 and 34 – 15 lks S. of random line.
40.65	Old 1/4 cor. 20 lks. S. of random line
80.00	N. 14 lks. from tangent set temp cor. secs 4 and 5
	S 89° 46' W. on tangent through sec. 5.
0.60	Old cor. Secs. 4, 5, 32 and 33 – 23 lks S. of random line
40.70	Old 1/4 Sec cor. 27 lks. S. of random line
80.00	N. 23 lks from tangent. set temp. cor. secs. 5 and 6
	S 89° 45' W. on tangent through sec. 6
0.85	Old cor. secs. 5, 6, 31 and 32. 31 lks S. of random line
41.05	Old 1/4 cor. 35 lks. S. of random line
81.48	Intersect West boundary at a point 38 lks. North of cor. of T. 22 and 23 N. R. 37 and 38 W., with random line. The true course of the line is therefore N. 89° 46' E.

South boundary T. 23 N. and
North boundary T. 22 N., R. 37 W.

chains	
	N. 89° 46' E. on true line bet. secs. 6 and 31
	Descend along N.E. slope broken hill
4.53	Wire fence N. 30° E. over very broken ridges and ravines on top hill.
36.00	Ridge
40.43	Old 1/4 Sec. cor. which is a flat mound with pits 18x18 ins. E and W. 4 ft. dist. in E. pit there is an Oak stake 2 ins. sq. marked 1/4 S. on N. face
41.20	Ridge N. and S. – descend
44.50	Ravine – thence over very broken ground
80.63	Old cor. of sec. 5, 6, 31 and 32 – flat mound with pits 24x24 ins. 4 ft. dist. in each sec. – in the S.E. pit. Drove an Oak stake 2 ft. long 2 ins. sq. 12 ins. in the ground marked for cor. of secs 31 and 32, thus:– T. 23 N.S. 32 on N.E. and R. 37 W.S. 31 on N.W. sides with 5 notches on E. and 1 notch on W. edges.
81.48	Deposit a charred stake 12 ins in the ground for cor. of secs 5 and 6, dug pits 24x24x12 ins. in each sec. 4 ft. dist. and raised a mound of earth 4 ft. base 2 ft. high over deposit. In S.E. pit drove an Oak stake 2 ft. long 2 ins. sq. 12 inches in ground, marked T. 22 N.S. 5 on S.E. and R. 37 W.S. 6 on N.W. sides with 5 notches on E and 1 notch on W. edge.
	N. 89° 46' E on a true line bet. secs 5 and 32
	Over low broken sand bluffs.
8.80	Descend
14.18	Bottom descent, Trail to Hyannis course N. 20° W. – over low foot hills.
28.00	Low ridge – descend
32.20	Trail to Hyannis course N.W. and S.E.
39.30	Old 1/4 Cor. – flat mound with shallow pits 18x18 ins. E. and W. 4 ft dist. in E. pit

South boundary T. 23 N. and
North boundary T. 22 N. R. 37 W.

chains

there is and Oak Stake 2 ins. sq. firmly driven marked
1/4 S. on N face
Ascend over broken ground, S. slope
72.00 Top of ascent on ridge, thence along S. face hills
79.40 Old cor. 4, 5, 32, and 33 which is a cedar post 5 ins. sq. 12 ins. above ground with shallow pits 18 x 18 ins – 5½ ft. dist. in each sec. with flat mound W. of cor. I remark post for cor. of secs. 32 and 33 – thus:–
T. 23 N.S. 33 on N.E. and
R 37 W.S. 32 on N.W. faces with 4 notches on E and 2 notches on W edge
80.00 Deposit charred stake 12 ins. in ground for cor. of secs. 4 and 5, dug pits 24 x 24 x 12 ins. in each sec. 4 ft. dist and raised a mound of earth 4 ft. base 2 ft. high over deposit
In S.E. pit drove an Oak Stake 2 ft. long 2 ins. sq. 12 ins. in ground, marked
T. 22 N.S. 4 on S.E. and
R. 37 W.S. 5 on S.W. face with 4 notches on E and 2 notches on W edge –

N. 89° 46' E bet. secs 4 and 33
Ascend, over broken ground
2.50 Ridge, at top ascent – thence along S. face hills.
30.50 Descend along S. face
39.35 Old 1/4 Sec. cor. flat mound with shallow pits 18 ins sq. E and W. 4 ft. dist., Oak Stake firmly driven in East pit. marked
1/4 S. on N. face
Over very broken ridge along S. face hills –
79.50 Old cor. of secs. 3, 4, 33 and 34 – flat mound with shallow pits 18 ins. sq. in each sec. 4 ft. dist. In the S.E. pit. I drive an

South boundary T. 23 N. and
North boundary T. 22 N. R. 37 W.

chains

Oak Stake 2 ft. long 2 ins sq. 12 ins. in the ground, marked for cor. of secs 33 and 34 thus:–
T. 23 N.S. 34 on N.E. and
R. 37 W.S. 33 on N.W. faces with 3 notches on E. and W. edges
80.00 Deposit charred stake 12 ins. in ground for cor. of secs. 3 and 4, dug pits 24 x 24 x 12 ins. in each sec. 4 ft dist. and raised a mound of earth 4 ft base 2 ft. high over deposit.
In S.E. pit drove an Oak Stake 2 ft. long 2 ins. sq., 12 ins in the ground, marked
T. 22 N.S. 3 on S.E. and
R. 37 W.S. 4 on S.W. faces with 3 notches on E. and W. edges.

N. 89° 46' E bet. secs. 3 and 34
Over broken ground on S. face range
Ascending gently
1.00 Top – along S. face over broken ground
22.65 High sand bluff – descend over very broken ground
40.00 Old 1/4 Sec. cor. flat mound with shallow pits 18 ins. sq. E. and W. 4 ft. dist. – In E pit an oak stake 2 ins. sq. is firmly driven marked
1/4 S. on N. face
Descend gully
60.20 Wire fence runs easterly on line and S.W. from this point.
67.00 Descend.
71.50 Enter rolling ground
79.90 The old cor. of secs. 2, 3, 34 and 35 which is a cedar post 4 ins. sq. 12 ins. above ground, marked
T. 23 N.S. 35 on N.E.
R. 37 W.S. 2 on S.E.
T. 22 N.S. 3 on S.W. and
S. 34 on N.W. sides with 2 notches on E

South boundary T. 23 N. and
North boundary T. 22 N. R. 37 W.

chains	
	and 4 notches on W. edges – with shallow pits 2 ft. sq. dug in each sec. 5½ ft. dist. and with flat mound W. of cor.
80.00	Set no new cor.

N. 89°46' E. bet. secs. 2 and 35
Over rolling ground

39.88	Old ¼ Sec. cor. flat mound with shallow pits 18 ins. sq. E. and W. 4 ft. dist. In E. pit an Oak stake 2 ins. sq. is firmly driven marked ¼ S. on N. face
79.89	The Old cor. of secs. 1, 2, 35 and 36 which is a flat mound with pits 18 ins. sq. dug in each sec. 4 ft. dist. – in the S.E. pit there is an Oak stake 2 ins. sq. firmly driven marked T. 23 N. S. 36 on N.E. R. 37 W. S. 1 on S.E. T. 22 N. S. 2 on S.W. and S. 35 on N.W. faces with 1 notch on E. and 4 notches on W. face
80.00	Set no new cor.

N. 89°46' E. bet. secs. 1 and 36
Over rolling ground

39.94	Old ¼ Sec. cor. flat mound with shallow pits 18 ins. sq. – E. and W. 4 ft. dist. In E. pit an Oak stake 2 ins. sq. is firmly driven, marked ¼ S. on N. face
50.00	Ascend gradual W. slope
70.30	Wire fence runs westerly on line
71.00	Top of ascent, along N. face
78.00	Descend
80.00	Cor. of T. 22 and 23 N., R. 36 and 37 W.

The last four miles of this line runs over very rough and broken ground – the eastern portion rolling
Soil Sandy 3rd rate – unfit for cultivation
Vegetation – Sand grass

May 29" 1899

Begun
East boundary T. 22 N., R. 37 W.

chains	
	As the bearing of the N. boundary of T. 22 N. R. 37 W. – is N. 89°46' E. the northing will be 1.92 chs – therefore the North practical distance of the east boundary of T. 22 N. R. 37 W. should be 80 chs + 1.92 = 81.92 chs
	From the cor of T. 22 and 23 N. R. 36 and 37 W. Run South on random line
	South bet. Secs. 1 and 6
41.92	Set temp. ¼ Sec. Cor.
81.92	Set. temp. cor. of secs. 1, 6, 7 and 12

South bet. secs. 7 and 12

40.00	Set. temp ¼ Sec. cor.
80.00	Set. temp cor. of secs 1, 3, 18, 19 and 24.

South bet. secs 13 and 18

40.00	Set. temp ¼ Sec. cor.
80.00	Set. temp cor. of secs. 13, 18, 19 and 24

South bet. secs. 19 and 24

40.00	Set. temp ¼ sec. cor.
80.00	Set temp cor. of secs. 19, 24, 25 and 30

South bet secs. 25 and 30

40.00	Set. temp. ¼ Sec. cor.
80.00	Set. temp cor. of secs. 25, 30, 31 and 36

South bet secs 31 and 36

40.00	Set. temp ¼ Sec. cor.
80.00	Set. temporary cor. of Tps. 21 and 22 N. R. 36 and 37 W.

May 30" 1899.

East boundary T. 22 N., R. 37 W.

chains

As the Dismal River correction line intersected the E. boundary of T. 22 N. R. 37 W., at a point 1.12 north of the Temporary S.W. cor. of Township. - The temporary corner should therefore be moved North 1.12 chs.

At the point of intersection I set an Oak Post 3 ft. long 4 ins. sq. with a charred stake 24 ins. in the ground for corner of T. 21 and 22 N. R. 36 and 37 W. marked.

T. 22 N. S. 31 on N.E.
R. 36 W. S. 6 on S.E.
T. 21 N. S. 1 on S.W. and
R. 37 W. S. 36 on N.W. sides, with 6 notches on each edge - dug pits 24 x 24 x 12 ins. on each line N., E. and W. 4 ft. dist. and S. of post 8 ft. dist. and raised a mound of earth 5 ft. base 2½ ft. high, S. of corner

North bet. secs. 31 and 36
Along W. face hills Descending gradually
24.00 Bottom descent, over low foot hills.
40.00 Deposit a charred stake 12 ins. in the ground for ¼ Sec. cor. - dug pits 18 x 18 x 12 ins. N. and S. of cor. 4 ft. dist. and raised a mound of earth 3½ ft. base 1½ ft. high, over deposit
In S. pit drove an Oak Stake 2 ft. long 2 ins. sq. 12 ins. in the ground, marked ¼ S. on W. face
50.00 Low ridge descend
55.00 Bottom over level ground
80.00 Deposit charred stake 12 ins. in ground for cor of secs. 25, 30, 31 and 36, dug pits 18 x 18 x 12 ins. in each sec. 4 ft dist. and raised a mound of earth 2 ft. base 2 ft. high, over deposit
In S.E. pit drove an Oak stake 2 ft. long 2 ins. sq. 12 ins. in the ground, marked

East boundary T. 22 N. R. 37 W.

chains

T. 22 N. S. 30 on N.E.
R. 36 W. S. 31 on S.E.
S. 36 on S.W. and
R. 37 W. S. 25 on N.W. sides with 1 notch on S. and 5 notches on N. edge

North bet. secs 25 and 30.
Over level ground
7.00 Ascend along S. slope.
14.14 Wire fence course E. and W.
39.50 Top of ascent 75 ft. above valley - thence over broken ground on top hill
40.00 Deposit charred stake 12 ins. in the ground for ¼ Sec. cor. dug pits 18 x 18 x 12 ins. N. and S. of cor. 4 ft. dist., and raised a mound of earth 3½ ft. base 1½ ft. high over deposit
In S. pit drove an Oak stake 3 ft. long 2 ins sq. 12 ins in ground, marked ¼ S. on W. face
41.00 Descend
64.00 Bottom descent - thence over low foot hills ascending gently
80.00 Set an Oak Post 3 ft. long 4 ins sq. with charred stake 24 ins. in ground for cor. of secs. 19, 24, 25 and 30, marked
T. 22 N. S. 19 on N.E.
R. 36 W. S. 30 on S.E.
S. 25 on S.W. and
R. 37 W. S. 24 on N.W. sides, with 2 notches on S. and 4 notches on N. edge, dug pits 18 x 18 x 12 ins. in each sec. 5½ ft. dist. and raised a mound of earth 4 ft. base 2 ft. high. W. of cor.

June 1st 1899

East boundary T. 22 N. R. 37 W.

chains	
	North bet. secs. 19 and 24
	Over low foot hills
35.40	Low ridge, course NW. and SE. descend
40.00	Deposit charred stake 12 ins. in ground for 1/4 sec. cor. dug pits 18x18x12 ins. N. and S. of cor. 4 ft. dist. and raised a mound of earth 3 1/2 ft. base 1 1/2 ft. high over deposit. In S. pit drove Oak Stake 2 ft. long 2 ins. sq. 12 ins. in the ground, marked 1/4 S. on W. face
	Corner under wire fence course E. and W.
42.00	Bottom descent over low hills
57.80	Trail to Whitman course N. 80° E.
59.00	Ascend abrupt. SE. slope
64.00	Top on E. face hills ascend gradually
80.00	Deposit charred stake 12 ins. in the ground for cor. of secs. 13, 18, 19 and 24, dug pits 18x18x12 ins. in each sec. 4 ft. dist. and raised a mound of earth 4 ft. base 2 ft. high over deposit. In S.E. pit drove an Oak Stake 2 ft. long 2 ins. sq 12 ins. in ground, marked T. 22 N.S. 18 on N.E. R. 36 W.S. 19 on S.E. S. 24 on S.W. and R. 37 W.S. 13 on NW sides, with 3 notches on N. and E. edges

North bet. secs 13 and 18
Ascend along S.E. face

5.30	Top of ascent, descend gradually
40.00	Deposit charred stake 12 ins. in ground for 1/4 sec. cor. dug pits 18x18x12 ins N. and S. of cor. 4 ft. dist. and raised a mound of earth 3 1/2 ft. base 1 1/2 ft. high over deposit
	In S. pit drove an Oak Stake 2 ft. long

East boundary T. 22 N. R. 37 W.

chains	
	2 ins sq. 12 ins. in the ground, marked 1/4 S. on W. face
41.00	Bottom descent - over low foot hills
80.00	Set an Oak Post 3 ft. long 4 ins sq. with charred stake 24 ins. in ground, for cor. of secs 7, 12, 13 and 18, marked T. 22 N.S. 7 on N.E. R. 36 W.S. 18 on S.E. S. 13 on S.W. and R. 37 W.S. 12 on N.W. faces with 4 notches on S. and 2 notches on N. edge. dug pits 18x18x12 ins in each sec. 5 1/2 ft. dist. and raised a mound of earth 4 ft. base 2 ft. high W. of cor.

North bet. secs 7 and 12
Descend gutly over low hills

18.80	Trail to Whitman N.E. and S.W. enter rolling ground
28.00	Ascend along S.E. slope
31.00	Top abrupt ascent, ascend along S.E. face
60.00	Top descend
69.00	Bottom descent in ravine
70.80	Trail course N.W. and S.E. ascend along S.W. slope
80.00	Deposit a charred stake 12 ins in the ground for cor of secs 1, 6, 7 and 12. dug pits 18x18x12 ins. in each sec. 4 ft. dist and raised a mound of earth 4 ft. base 2 ft. high over deposit. In S.E. pit drove an Oak Stake 2 ft. long 2 ins. sq. 12 ins. in the ground, marked T. 22 N.S. 6 on N.E. R. 36 W.S. 7 on S.E. S. 12 on S.W. and R. 37 W.S. 1 on N.W. face with 5 notches on S. and 1 notch on N. edge.

East boundary T. 22 N. R. 37 W.

chains	
	North bet. secs. 1 and 6
	Ascend S.W. slope
10.00	Top 50 ft. above cor. – over broken ground
38.00	Descend along N.E. slope
40.00	Deposit charred stake 12 ins. in the ground for 1/4 Sec. cor. dug pits 18x18x12 ins. N and S. of cor. 4 ft. dist. and raised a mound of earth 3 1/2 ft. base 1 1/2 ft high over deposit. In S. pit drove an Oak stake 2 ft. long 2 ins sq. 12 ins. in the ground, marked 1/4 S. on W. face
51.00	Bottom descent, in neck of valley extending to east.
54.00	Ascend abrupt slope
58.00	Top – ascend S. face.
67.00	Top of range 150 ft. above valley
78.00	Ridge – descend
80.80	Cor. of Township 22 and 23 N. R. 36 and 37 W. Line runs over broken sand hills for its entire length, except bet. secs 31 and 36. Soil sandy 3rd rate, unfit for cultivation

Willard W. Alt.
U.S. Surveyor.
June 2" 1899

Boundaries of T. 22 N. R. 37 W.

Lines Designated	Bearing	Dist.	Latitude N.		Latitude S.		Departure E.		Departure W.	
		ch.	ch.		ch.		ch.		ch.	
N. bdry	N. 89 46 E	481.48	1	48			481	48		
E. bdry	South	480.80			480	80				
S. bdry	West	482.00							482	00
W. bdry	North	478.38	478	38						
Convergency							0	65		
			479	86	480	80	482	13	482	00
Error in Latitude					479	86				
Error in Departure					0	94	482	00		
								13		

Willard W. Alt.
U.S. Surveyor.

FINAL OATHS OF DEPUTY SURVEYOR AND HIS ASSISTANTS.

LIST OF NAMES.

A list of the names of the individuals employed by ....., United States Deputy Surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of ..... showing the respective capacities in which they acted:

....., *Chainman.*
....., *Chainman.*
....., *Moundman.*
....., *Moundman.*
....., *Axman.*
....., *Axman.*
....., *Flagman.*

FINAL OATH OF ASSISTANTS.

We hereby certify that we assisted ....., United States Deputy Surveyor, in surveying all those parts or portions of the ..... of the ..... meridian, ... of ....., which are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established, according to the instructions furnished by the United States Surveyor General for .....

....., *Chainman.*
....., *Chainman.*
....., *Moundman.*
....., *Moundman.*
....., *Axman.*
....., *Axman.*
....., *Flagman.*

Subscribed and sworn to before me this ..... day of ....., 189 .....

SEAL

6—151

12/27

29

FINAL OATH OF UNITED STATES DEPUTY SURVEYOR.

I, ..., United States Deputy Surveyor, do solemnly swear that, in pursuance of a contract received from ....., bearing date of the United States Surveyor General for ....., ... day of ....., 189 , I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States Surveyor General for ....., the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of .....

..... of the ..... meridian, in the ..... of ....., which are represented in the foregoing field notes as having been surveyed by me, and under my direction; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the United States Surveyor General for ..... and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey; and should any fraud be detected, I will suffer the penalty of perjury under the provisions of an Act of Congress approved August 8, 1846.

.....
United States Deputy Surveyor.

Subscribed by said ....., and sworn to before me this ..... day of ....., 189

SEAL

APPROVAL.

General Land OFFICE OF THE UNITED STATES ~~SURVEYOR GENERAL~~, Wash. D.C. June 30, 1900, ~~189~~

The foregoing field notes of the survey of South Boundary T 23 N. North Boundary T 22 N. and the East Boundary of Township 22 North, Range 3 of West.

executed by Willard H. Alt, U.S. Surveyor under his contract No. —, dated April 17, 1899, having b critically examined, and the necessary corrections and explanations made, the said field notes, and surveys they describe, are hereby approved.

Bruce Hermann
~~United States Surveyor Gen~~
Commissioner and
~~Ex-officio Surveyor General for Nebraska~~

I ~~certify that the foregoing transcript of the field notes of the above described surveys in~~ ....., has been correctly copied from the original notes on file in this offic

United States Surveyor Ge

6—151

30

General Land Office • Original Field Notes

Book Number

775

W.W. Alt - South bdy. T 23 N, North & East bdy. T 22 N, R 37 W

The images in this file are microfilm images of the notes of W.W. Alt resurveys of portions of the State of Nebraska on file in the Office of the Nebraska State Surveyor located in Lincoln, Nebraska.

The W.W. Alt resurveys began in the mid 1890's and were completed in the early 1900's.